

# EUCOLASTIC SEALANTS

## 1NS & 1SL Color Selection Guide



**\*GRAY**



**\*LIMESTONE**



**WHITE**



**STONE**



**BRONZE**



**BLACK**



**REDWOOD TAN**



**OFF WHITE**



**TAN**

**\*DENOTES COLOR AVAILABLE IN EUCOLASTIC 1SL**

The color chips shown are simulated. Each has been color matched as closely as possible to production standards. Variations between the finished product and this color chart will occur. The Euclid Chemical Company always recommends a test panel be reviewed and approved for final appearance.



**EUCRID CHEMICAL**

19215 Redwood Road • Cleveland, Ohio 44110 • (800) 321-7628 • Fax: (216) 531-9596  
[www.euclidchemical.com](http://www.euclidchemical.com)

CC06

**Color samples are approximations.**

## **EUCOLASTIC 1NS**

Eucolastic 1NS is a single-component, non-sag, low-modulus, moisture-cure, polyurethane hybrid joint sealant. Eucolastic 1NS is formulated with a unique silane-terminated polyurethane polymer, that provides unequalled performance against stand-alone polyurethane sealants. Eucolastic 1NS is an extremely durable sealant in dynamic joints, offering persistent adhesion once fully cured.

## **EUCOLASTIC 1SL**

Eucolastic 1SL is a single-component, low-modulus, moisture-cure, self-leveling, polyurethane joint sealant. Eucolastic 1SL is formulated to be extremely durable in dynamic joints. It provides superior wear resistance to rubber tires and pedestrians in high traffic areas.