



# PORTABLE MAGNETIC DRILLS

		HMD130	HMD900	HMD904	HMD905	HMD906	HMD927	HMD2MT	HMD920	HMD918	HMD934	
		Low Profile	Fabricating					Heavy Duty Drilling				
Cutters	RotaLoc Plus™		With Adapter	With Adapter	With Adapter	With Adapter	With Adapter	With Adapter	With Adapter	With Adapter		
	"12,000-Series"											
	Copperhead™ Carbide Tipped											
Model Specifications	Diameter Min./Max.	7/16" to 1-3/8" (12 - 35mm)	7/16" to 1-1/2" (12 - 38mm)	7/16" to 1-1/2" (12 - 38mm)	7/16" to 2" (12 - 50mm)	7/16" to 2" (12 - 50mm)	7/16" to 1-5/8" (12 - 41mm)	7/16" to 1-5/8" (12 - 41mm)	7/16" to 2-3/8" (12 - 60mm)	7/16" to 2-3/8" (12 - 60mm)	5/8" to 3-1/16" (16 - 77mm)	
	Depth Max.	1" (25mm)	2" (50mm)	2" (50mm)	2" (50mm)	2" (50mm)	2" (50mm)	2" (50mm)	3" (76mm)	6" (152mm)	4" (100mm)	
	Cutter Mounting	Bayonet Style	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat or Fusion2™	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat	
	No-Load R.P.M.	450	450	450	250 / 450	350 / 650	250 / 450	250 / 450	250 / 450 / 700	250 / 450	70 / 120 / 200 / 332	
	Model Weight	23.8 lbs (10.8 kg)	27.7 lbs (12.6 kg)	30 lbs (13.6 kg)	35 lbs (15.9 kg)	35 lbs (15.9 kg)	43 lbs (19.5 kg)	40.2 lbs (18.1 kg)	49 lbs (22.2 kg)	44.2 lbs (20.1 kg)	72 lbs (32.6 kg)	
	Thru-the-Tool Coolant											
	Carrying Case Included											
Available Accessories	Swivel Base			Optional	Optional	Optional	Optional		Optional			
	#2 Morse Taper								With Adapter	With Adapter		
	Pipe Adapter						Manual Mode					
	Tap Attachment						Manual Mode					
	Vac-Pad™											
	Coolant Bottle			Optional	Included	Included	Included	Included	Included	Pressurized	Included	
	Countersink Kit						Manual Mode					
	Twist Drill Adapter						Manual Mode					
	Ratchet Drive											
	Arbor Extender						Manual Mode					
	Drill Chuck						Manual Mode					
	RotaLoc™ Spindle Adapter						Manual Mode					