



600GL Coatings Remover

Formerly SOY•Gel™ Paint and Urethane Remover

EASILY REMOVE MULTIPLE LAYERS

- Removes Paints, Urethanes, Enamels, Sealers, Some Epoxies, Lead Paint, and Many Other Coatings
- Gel Formula for Easy Application
- SAFE! No Methylene Chloride
- Non-Caustic and Biodegradable
- Made with 100% American-Grown Soybeans



Horizontal Coverage: 125 sq ft per gallon
Vertical Coverage: 75 sq ft per gallon

Find Out More About 600GL Coatings Remover

Visit: www.franmar.com or
Call: 800.538.5069





PRODUCT DATA



600GL Coatings Remover (Formerly SOY•Gel™ Paint and Urethane Remover)

Franmar's most-asked-for product, **600GL**, continues to impress contractors with its ease of use and powerful removal properties. With three times the coverage rate of traditional petroleum removers, **600GL** effectively removes multiple layers of topical sealers, acrylics, enamels, urethanes, latex, some epoxies, other single-component coatings, and lead-based paint.* Made with soybeans, **600GL** is a safe, low-odor, non-caustic, green coating remover.

As a leading innovator in green cleaning products, Franmar Chemical, Inc. introduced **600GL** as a soy based paint remover, and changed the industry. **600GL** is 100% biodegradable, practically odorless, and is safe for your hands, your work, and your customers.

**Ideal for lead-based paint removal. The lead becomes encapsulated in the gel, preventing airborne particles and allowing for safe removal. Dispose of in accordance with all existing local, state, and federal ordinances.*

Coverage: Coverage per square foot varies depending on type and age of coating, number of layers and method of application.

Horizontal: Average coverage is 125 sq ft per gallon (max 200 sq ft per gallon)

Vertical: Average coverage is 75 sq ft per gallon

Test Area:

Due to variances in surfaces and conditions, always test in a small, inconspicuous area before using on complete project.

Application:

Apply a thick layer of **600GL** by pouring, brushing, squeegee, or commercial airless sprayer. Applying too thin will cause **600GL** to dry out before removal is complete. Use a scraper to check if the coating is softened down to the surface. If not, wait longer and recheck. When the coating is completely softened, remove with a scraper.

Clean Up:

Use **BLUE BEAR 700DG Degreaser** or water and a scrub brush, mop, or power washer to clean remaining thin residue. Remove excess coating(s) and **600GL** before using a power washer for final cleaning. Allow surface to dry before further preparations.

Usage Tips from the Pros:

- For large application areas, use a professional airless sprayer or a 4-stage HVLP sprayer.
- For tough coatings or numerous layers, use a notched 1/2" squeegee or 1/4" gauge rake. Square footage will be greatly reduced.
- When used outdoors, cover with a 2mil or thicker plastic to help keep **600GL** wet and working.

Biodegradable: Meets or exceeds ASTM standards

Precautions: Concrete surfaces may darken with use of **600GL**. Protect plants and vegetation with a plastic drop cloth. Always use care to prevent overspray from getting on surfaces other than the one being prepped or cleaned.

Warnings: May cause skin irritation. May cause eye irritation. May cause respiratory irritation or may cause drowsiness and dizziness. May be harmful if swallowed. This product contains a chemical known to the state of California to cause birth defects or other reproductive harm. Keep out of reach of children.

Flash Point: Above 200°F (93.3°C)

pH Level: 8.1 pH of 1/10 wt/wt solution in soft water

VOC (Volatile Organic Compounds): 49%, 4.249 lb/g, 509 g/l
California and OTC Compliant

Ingredients: N-Methyl Pyrrolidone, Dibasic Ester LVP, Soy Ester, Proprietary Thickening and Surfactant Blend

Safe for Use On: Concrete, masonry, wood, and metal

Do Not Use On: PVC, drywall, limestone, plastic, veneer, terrazzo tile, or rubber

WARNING: This product can expose you to chemicals including n-methyl-2-pyrrolidone which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

NON-EMERGENCY
Call: 800.538.5069

www.franmar.com

CHEMICAL EMERGENCY:

Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night
USA and Canada: **800.242.9300**
CCN717946 or **+1 703.527.3887**
(Collect Calls Accepted)



PO Box 5565
Bloomington IL 61702
Rev. 3/29/2015