

#### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: **Abrasive Product** 

SDS Manufacturer Number: TW\_All

Manufacturer Name: Saint-Gobain Abrasives, Inc.

1 New Bond Street Address: Worcester, MA 01615

Website: www.Nortonabrasives.com General Phone Number: 508-795-5000

Emergency Phone Number: 508-795-5000



HMIS	
Health Hazard	1
Fire Hazard	0
Reactivity	1
Personal Protection	x

#### SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS# Ingredient Percent		EC Num.
Inorganic fluorides	Not Applicable	1 - 5 by weight	
Sulfates/Sulfides	No Data	1 - 5 by weight	
Phenol formaldehyde polymer	9003-35-4	10 - 30 by weight	
Fiberglass	65997-17-3	1 - 5 by weight	266-046-0
Calcium carbonate	1317-65-3	1 - 5 by weight	215-279-6
Aluminum Oxide, Non-fibrous	1344-28-1	60 - 100 by weight	215-691-6
Titanium dioxide	13463-67-7	1 - 5 by weight	236-675-5

# SECTION 3: HAZARDS IDENTIFICATION

Potential Health Effects:

Eve: Dust may cause slight irritation.

Skin: Dust from this product may cause temporary mechanical irritation.

Inhalation: Dusts from this product may cause mechanical irritation of the nose, throat and respiratory tract. Ingestion: Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal

irritation and disturbances.

Chronic Health Effects: Chronic health effects are not expected as long as good hygiene and proper safety precautions are

practiced.

**Fiberglass** 

Fiberglass contained in wheels have fiber diameters greater than 10 um, therefore considered non-Inhalation:

SECTION 4: FIRST AID MEASURES

Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers.

Get medical attention, if irritation or symptoms of overexposure persists. Eye Contact:

Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists. Skin Contact:

Inhalation: If dust from cutting or drilling is inhaled, remove the affected person to fresh air. If symptoms persist,

Ingestion: Accidental ingestion of this material is unlikely. If this does occur, watch person for several days to

make sure intestinal blockage does not occur. If symptoms persist, call a physician.

Note to Physicians: No information available.

#### SECTION 5: FIRE FIGHTING MEASURES

Flammable Properties: Non Flammable Flash Point: Does not apply. Auto Ignition Temperature: Not determined. Lower Flammable/Explosive Limit: Not available. Upper Flammable/Explosive Limit: Not available.

Extinguishing Media: Use any extinguishing media appropriate for the surrounding fires.

Unsuitable Media:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or Protective Equipment:

equivalent) and full protective gear.

NFPA Ratings:

NFPA Other:

NFPA Health: 0 NFPA Flammability: 0 NFPA Reactivity: 1

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

Methods for containment: Containment of this material should not be necessary.

Methods for cleanup: Shovel or sweep up for re-use or disposal. Avoid creating dusty conditions. Evaluate residue to determine if it is a hazardous waste by characteristic.

Dispose of in accordance with Local, State, Federal and Provincial regulations.

#### SECTION 7: HANDLING and STORAGE

Handling: Always HANDLE AND STORE wheels in a CAREFUL manner.

Always VISUALLY INSPECT all wheels before mounting.
Always CHECK MACHINE SPEED against the established maximum safe operating speed MARKED ON THE WHEEL.

Always CHECK MOUNTING FLANGES for equal and correct diameter. Always USE MOUNTING BLOTTERS.

Always be sure WORK REST is properly adjusted. Always USE A SAFETY GUARD covering at least one-half of the grinding wheel.

Always allow NEWLY MOUNTED WHEELS to run at operating speed, with guard in place, for at least one minute before grinding.

Always TURN OFF COOLANT before stopping wheel to avoid creating an out-of-balance wheel.

Storage: No special storage conditions required.

Hygiene Practices: Wear suitable gloves and eye/face protection.

# SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

**Engineering Controls:** General dilution ventilation and/or local exhaust ventilation should be provided as necessary to

maintain exposures below occupational exposure limits

Always WEAR SAFETY GLASSES or some type of eye protection when grinding. Eye/Face Protection:

Skin Protection Description: Protective gloves

Long sleeved shirt and long pants.

Respiratory Protection: When workers are facing airborne particulate/dust concentrations above the exposure limit they must use appropriate certified respirators.

A properly fitted NIOSH approved disposable N 95 type dust respirator or better is recommended.

Other Protective: Use of this product may create elevated sound levels. Hearing protection should be worn where required (see OSHA 29 CFR 1910.134 and other applicable regulations).

Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. General Hygiene Considerations:

Avoid getting dust into boots and gloves through wrist bands and pant tucks.

# **EXPOSURE GUIDELINES**

Ingredient	Guideline OSHA	Guideline NIOSH	Guideline ACGIH	Quebec Canada	Ontario Canada
Inorganic fluorides	PEL-TWA 2.5 mg/m3	REL-TWA 2.5 mg/m3	TLV-TWA 2.5 mg/m3		
Fiberglass	PEL-TWA: 1 f/cc as Continuous filament glass		TLV-TWA: 1 f/cc as Continuous filament glass TLV-TWA: 5 mg/m3 as Continuous filament glass		
Calcium carbonate				VEMP-TWA: 10	

				mg/m3 Total particulate/dust (T)	
Aluminum Oxide, Non- fibrous	PEL-TWA: 5 mg/m3 Respirable fraction (R) PEL-TWA: 15 mg/m3 Total particulate/dust (T)		TLV-TWA: 10 mg/m3	VEMP-TWA: 10 mg/m3 Total particulate/dust (T)	OEL-TWAEV: 10 mg/m3 Total particulate/dust (T)
Titanium dioxide			TLV-TWA: 10 mg/m3	VEMP-TWA: 10 mg/m3 Total particulate/dust (T)	OEL-TWAEV: 10 mg/m3 Total particulate/dust (T)
Ingredient	Alberta Canada	Mexico	British Columbia Canada		
Calcium carbonate	OEL-TWA: 10 mg/m3		OEL-TWA: 10 mg/m3 Total particulate/dust (T) OEL-TWA: 3 mg/m3 Respirable fraction (R) OEL-STEL: 20 mg/m3 Total particulate/dust (T)		
Aluminum Oxide, Non- fibrous	OEL-TWA: 10 mg/m3	MPE-PPT: 0.1 mg/m3 Respirable fraction (R)	OEL-TWA: 3 mg/m3 Respirable fraction (R) OEL-TWA: 10 mg/m3 OEL-TWA: 10 mg/m3 Total particulate/dust (T) OEL-STEL: 20 mg/m3 Total particulate/dust (T)		
Titanium dioxide	OEL-TWA: 10 mg/m3 Total particulate/dust (T)	MPE-PPT: 0.1 mg/m3 Respirable fraction (R)	OEL-TWA: 10 mg/m3 Total particulate/dust (T) OEL-TWA: 3 mg/m3 Respirable fraction (R)		

# SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Solid article. Odor: Odorless. Flash Point: Does not apply. Auto Ignition Temperature: Not determined.

# SECTION 10: STABILITY and REACTIVITY

Chemical Stability: Stable under normal conditions.

Hazardous Polymerization: Hazardous polymerization does not occur.

In use, dust and decomposing odors may be generated. In most cases, the material removed from the workplace will be significantly greater than the grinding wheel components. Coolants may produce other decomposition products. Special Decomposition Products:

# SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity: This product has not been tested for its toxicity.

Carcinogens:						
	ACGIH	NIOSH	OSHA	IARC	NTP	
Aluminum Oxide, Non-fibrous	A4 Not Classifiable as a Human Carcinogen	No Data	No Data	No Data	No Data	
Titanium dioxide	No Data	No Data	No Data	No Data	No Data	

# Phenol formaldehyde polymer:

RTECS Number: SM8542500

Administration onto the skin - Rat LD50 : >2 gm/kg [Details of toxic effects not reported other than lethal dose value ] (RTECS) Skin:

Ingestion: Oral - Rat LD50 : >5 gm/kg [Details of toxic effects not reported other than lethal dose value ]

(RTECS)

Fiberglass:

RTECS Number: LK3651000

Calcium carbonate:

RTECS Number: EV9580000

Aluminum Oxide, Non-fibrous:

RTECS Number: BD1200000

Inhalation - Rat TCLo: 200 mg/m3/5H/28W (Intermittent) [Lungs, Thorax, or Respiration - Structural or functional change in trachea or bronchi; Lungs, Thorax, or Respiration - Chronic pulmonary edema; Related to Chronic Data - death] (RTECS) Inhalation:

#### <u>Titanium dioxide</u>:

RTECS Number: XR2275000

Skin - Human Standard Draize test. : 300 ug/3D-I - [mild] (RTECS) Skin:

Inhalation: Inhalation - Rat TCLo - Lowest published toxic concentration: 1 mg/kg - [Lungs, Thorax, or Respiration

- Other changes Biochemical - Metabolism (Intermediary) - Effect on inflammation or mediation of inflammation ] (RTECS)

Oral - Rodent rat TDLo - Lowest published toxic dose: 60 gm/kg - [Gastrointestinal - Hypermotility, diarrhea Gastrointestinal - Other changes ] (RTECS) Ingestion:

#### SECTION 12: ECOLOGICAL INFORMATION

Biodegradation: Vitrified products do not appreciably decay.

#### SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal: Use standard landfill methods consistent with applicable Federal, State, Provincial and local laws.

# SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Not regulated as hazardous material for transportation. DOT UN Number: Not regulated as hazardous material for transportation.

IATA Shipping Name: Not regulated as hazardous material for transportation.

Canadian Shipping Name: This product is Not Regulated under the Transportation of Dangerous Goods Act. (CAN).

# SECTION 15: REGULATORY INFORMATION

Canada Reg. Status: Controlled - Class: D2B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products

Regulations.

Phenol formaldehyde polymer:

TSCA Inventory Status: Listed Canada DSL: Listed

Fiberglass:

TSCA Inventory Status: Listed Canada DSL: Listed 266-046-0 EC Number:

Calcium carbonate:

TSCA Inventory Status: Listed Massachusetts: Listed Pennsylvania: Listed Canada NDSL: Listed 215-279-6 FC Number:

**Aluminum Oxide, Non-fibrous:** 

TSCA Inventory Status: Listed EINECS Number: 262-373-8

Listed: NJ Hazardous List: Substance Number: 2891 New Jersev:

Listed Massachusetts: Pennsylvania: Listed Minnesota: Listed No Data Rhode Island: Listed Canada DSL: Listed

Canada IDL: Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 0.1%.50(1298)

EC Number: 215-691-6

<u>Titanium dioxide</u>:

TSCA Inventory Status: Listed New Jersey: No Data Massachusetts:ListedPennsylvania:ListedMinnesota:ListedIllinois:No DataRhode Island:ListedCanada DSL:ListedEC Number:236-675-5

# SECTION 16: ADDITIONAL INFORMATION

**HMIS Ratings**:

HMIS Health Hazard: 1
HMIS Fire Hazard: 0
HMIS Reactivity: 1
HMIS Personal Protection: X

SDS Creation Date: August 15, 2009
SDS Revision Date: July 01, 2013

Copyright© 1996-2015 Actio Corporation. All Rights Reserved.