

## **SAFETY DATA SHEET**

## THE DOW CHEMICAL COMPANY

Product name: DOWSIL™ 795 Silicone Building Sealant Issue Date: 08/21/2018

White

Print Date: 08/22/2018

THE DOW CHEMICAL COMPANY encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

## 1. IDENTIFICATION

Product name: DOWSIL™ 795 Silicone Building Sealant White

Recommended use of the chemical and restrictions on use

Identified uses: Adhesive, binding agents

**COMPANY IDENTIFICATION** 

THE DOW CHEMICAL COMPANY 2030 DOW CENTER MIDLAND MI 48674-0000 UNITED STATES

Customer Information Number: 800-258-2436

SDSQuestion@dow.com

**EMERGENCY TELEPHONE NUMBER** 

24-Hour Emergency Contact: CHEMTREC +1 800-424-9300

**Local Emergency Contact:** 800-424-9300

## 2. HAZARDS IDENTIFICATION

#### Hazard classification

GHS classification in accordance with 29 CFR 1910.1200 Not a hazardous substance or mixture.

## Label elements

## **Precautionary statements**

#### Prevention

Use only outdoors or in a well-ventilated area.

#### Other hazards

No data available

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Issue Date: 08/21/2018

Chemical nature: Silicone elastomer

This product is a mixture.

Component	CASRN	Concentration
Diisopropoxydi(ethoxyacetoacetyl)titanate	27858-32-8	>= 0.6 - <= 1.08 %
Methanol	67-56-1	>= 0.16 - <= 0.23 %

## 4. FIRST AID MEASURES

## Description of first aid measures General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air; if effects occur, consult a physician.

Skin contact: Wash off with plenty of water.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

**Ingestion:** No emergency medical treatment necessary.

#### Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

## Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

## 5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical

Unsuitable extinguishing media: None known.

Special hazards arising from the substance or mixture

Hazardous combustion products: Metal oxides Formaldehyde Carbon oxides Silicon oxides

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health.

Page 2 of 12

#### Advice for firefighters

**Fire Fighting Procedures:** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

**Special protective equipment for firefighters:** Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures:** Follow safe handling advice and personal protective equipment recommendations.

**Environmental precautions:** Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

**Methods and materials for containment and cleaning up:** Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. See sections: 7, 8, 11, 12 and 13.

#### 7. HANDLING AND STORAGE

**Precautions for safe handling:** Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

**Conditions for safe storage:** Keep in properly labelled containers. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents. Unsuitable materials for containers: None known.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## **Control parameters**

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value/Notation
Methanol	ACGIH	TWA	200 ppm
	ACGIH	STEL	250 ppm
	ACGIH	TWA	SKIN
	OSHA Z-1	TWA	260 mg/m3 200 ppm
	ACGIH	STEL	SKIN

Isopropanol	ACGIH	TWA	200 ppm
	ACGIH	STEL	400 ppm
	OSHA Z-1	TWA	980 mg/m3 400 ppm

Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

The following substance(s), which have Occupational Exposure Limit(s) (OEL), may be formed during handling or processing:

Isopropanol

**Biological occupational exposure limits** 

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI
Isopropanol	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI

#### **Exposure controls**

**Engineering controls:** Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

## Individual protection measures

**Eye/face protection:** Use safety glasses (with side shields). **Skin protection** 

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Natural rubber ("latex"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Other protection:** Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

**Respiratory protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed;

however, if handling at elevated temperatures without sufficient ventilation, use an approved air-purifying respirator.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** 

Physical state paste
Color off-white
Odor slight

Odor Threshold

PH

Not applicable

Melting point/range

No data available

No data available

No data available

No data available

Not applicable

Flash point Seta closed cup 91 °C (196 °F)

**Evaporation Rate (Butyl Acetate** 

= 1)

Not applicable

Flammability (solid, gas) Not classified as a flammability hazard

Lower explosion limitNo data availableUpper explosion limitNo data availableVapor PressureNot applicableRelative Vapor Density (air = 1)No data available

Relative Density (water = 1) 1.52

Water solubility No data available Partition coefficient: n- No data available

octanol/water

Auto-ignition temperature

Decomposition temperature

Dynamic Viscosity

Kinematic Viscosity

Explosive properties

No data available
No data available
Not applicable
Not applicable
Not explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

Molecular weightNo data availableParticle sizeNo data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

## 10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Product name: DOWSIL™ 795 Silicone Building Sealant White

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents. Vapours may form

explosive mixture with air.

Conditions to avoid: None known.

Incompatible materials: Oxidizing agents

Hazardous decomposition products: Formaldehyde. Benzene. Isopropanol.

## 11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

#### **Acute toxicity**

#### Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):

LD50, Rat, > 5,000 mg/kg Estimated.

## **Acute dermal toxicity**

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):

LD50, > 2,000 mg/kg Estimated.

#### Acute inhalation toxicity

Brief exposure (minutes) is not likely to cause adverse effects. Vapor from heated material may cause respiratory irritation.

As product: The LC50 has not been determined.

#### Skin corrosion/irritation

Prolonged exposure not likely to cause significant skin irritation.

#### Serious eye damage/eye irritation

May cause slight temporary eye irritation.

May cause mild eye discomfort.

#### Sensitization

For skin sensitization:

No relevant data found.

For respiratory sensitization:

No relevant information found.

**Specific Target Organ Systemic Toxicity (Single Exposure)** 

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

## Specific Target Organ Systemic Toxicity (Repeated Exposure)

Contains a component(s) that is/are encapsulated in the product and are not expected to be released under normal processing conditions or foreseeable emergency

#### Carcinogenicity

For similar material(s): Did not cause cancer in long-term animal studies which used routes of exposure considered relevant to industrial handling. Positiveresults have been reported in other studies using routes of exposure not relevant to industrial handling. Contains an additional component(s) that is/are encapsulated in the product and are not expected to be released under normal processing conditions or foreseeable emergency.

#### **Teratogenicity**

Contains component(s) which did not cause birth defects or any other fetal effects in lab animals.

#### Reproductive toxicity

Contains component(s) which did not interfere with reproduction in animal studies.

#### Mutagenicity

Contains a component(s) which were negative in in vitro genetic toxicity studies. Contains component(s) which were negative in animal genetic toxicity studies.

#### **Aspiration Hazard**

Based on physical properties, not likely to be an aspiration hazard.

#### COMPONENTS INFLUENCING TOXICOLOGY:

#### Diisopropoxydi(ethoxyacetoacetyl)titanate

#### Acute inhalation toxicity

For similar material(s): LC50, Rat, male and female, 4 Hour, vapour, > 198.65 mg/l No deaths occurred at this concentration.

#### **Methanol**

#### Acute inhalation toxicity

Easily attainable vapor concentrations may cause serious adverse effects, even death. At lower concentrations: May cause respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness. Inhalation of methanol may cause effects ranging from headache, narcosis and visual impairment to metabolic acidosis, blindness, and even death. Effects may be delayed.

LC50, Rat, 4 Hour, vapour, 3 mg/l

#### 12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

#### **Toxicity**

## Diisopropoxydi(ethoxyacetoacetyl)titanate

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). LC50. Rasbora heteromorpha (Harlequin fish), static test, 96 Hour, 4,200 mg/L

## Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), static test, 48 Hour, > 100 mg/l, OECD Test Guideline 202 or Equivalent

## Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), static test, 72 Hour, Growth rate inhibition, > 100 mg/l, OECD Test Guideline 201 or Equivalent NOEC, Pseudokirchneriella subcapitata (green algae), static test, 72 Hour, Growth rate inhibition, 100 mg/l, OECD Test Guideline 201 or Equivalent

#### Methanol

## Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). LC50, Bluegill sunfish (Lepomis macrochirus), flow-through test, 96 Hour, 15,400 mg/l

## Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), 48 Hour, > 10,000 mg/l

## Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 96 Hour, Growth rate, 22,000 mg/l, OECD Test Guideline 201 or Equivalent

#### Toxicity to bacteria

IC50, activated sludge, 3 Hour, Respiration rates., > 1,000 mg/l, OECD Test Guideline 209

## Chronic toxicity to fish

NOEC, Oryzias latipes (Orange-red killifish), 200 Hour, 15,800 mg/l

#### Persistence and degradability

#### Diisopropoxydi(ethoxyacetoacetyl)titanate

**Biodegradability:** For similar material(s): Material is readily biodegradable. Passes OECD

test(s) for ready biodegradability.

10-day Window: Pass **Biodegradation:** 66 % **Exposure time:** 28 d

Method: OECD Test Guideline 301D

#### **Methanol**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

Theoretical Oxygen Demand: 1.50 mg/mg

Chemical Oxygen Demand: 1.49 mg/mg Dichromate

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	72 %
20 d	79 %

## Photodegradation

Test Type: Half-life (indirect photolysis)

**Sensitization:** OH radicals **Atmospheric half-life:** 8 - 18 d

Method: Estimated.

## Bioaccumulative potential

#### <u>Diisopropoxydi(ethoxyacetoacetyl)titanate</u>

Bioaccumulation: For similar material(s): Bioconcentration potential is low (BCF < 100 or

Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 0.05 Bioconcentration factor (BCF): 3 Fish Estimated.

#### **Methanol**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): -0.77 Measured

Bioconcentration factor (BCF): < 10 Leuciscus idus (Golden orfe) Measured

## Mobility in soil

## Diisopropoxydi(ethoxyacetoacetyl)titanate

For similar material(s):

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 1.53 Estimated.

#### **Methanol**

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 0.44 Estimated.

#### 13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

Page 9 of 12

**Treatment and disposal methods of used packaging:** Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

## 14. TRANSPORT INFORMATION

DOT

Not regulated for transport

## Classification for SEA transport (IMO-IMDG):

Not regulated for transport

Consult IMO regulations before transporting ocean bulk

Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

## 15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

No SARA Hazards

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

# Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

Calculated RQ exceeds reasonably attainable upper limit.

Components	CASRN	RQ (RCRA Code)
Methanol	67-56-1	5000 lbs RQ
Methanol	67-56-1	100 lbs RQ (F003)
Toluene	108-88-3	1000 lbs RQ
Toluene	108-88-3	100 lbs RQ (F005)

Page 10 of 12

 Methanol
 67-56-1
 5000 lbs RQ

 Methanol
 67-56-1
 100 lbs RQ (F003)

## Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components	CASRN
Calcium carbonate treated with stearic acid	Not available
Polydimethylsiloxane hydroxy-terminated	70131-67-8
Siloxanes and silicones, dimethyl	63148-62-9
Amorphous fumed silica	112945-52-5

#### California Prop. 65

WARNING: This product can expose you to chemicals including Methanol, Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

## **United States TSCA Inventory (TSCA)**

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

## 16. OTHER INFORMATION

## **Hazard Rating System**

#### NFPA

	Health	Flammability	Instability
	0	1	0
Н	MIS		
	Health	Flammability	Physical
	Пеанн	Fiaminability	Hazard
	0/	1	0

#### Revision

Identification Number: 3310426 / A001 / Issue Date: 08/21/2018 / Version: 8.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

#### Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air
	Contaminants
SKIN	Absorbed via skin
STEL	Short-term exposure limit
TWA	8-hour, time-weighted average

## Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic

Page 11 of 12

Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice: HMIS - Hazardous Materials Identification System: IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA -Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA -Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

#### **Information Source and References**

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.