

TECHNICAL DATA SHEET

PowerSaw

Synthetic Machining Metalworking Fluid Concentrate

DESCRIPTION

PowerSaw is a quality moderate to heavy-duty synthetic metalworking fluid with non-chlorinated extreme-pressure additives formulated specifically to meet the needs of sawing operations.

APPLICATIONS

- Moderate to heavy-duty
- Band and circular sawing, machining, grinding

MATERIALS COMPATIBILITY

- Recommended for ferrous metals and alloys
- Limited use for aluminum
- Not recommended for titanium, brass, bronze, and copper

PHYSICAL PROPERTIES

Concentrate Color	Dark blue
Dilute Color	Clear bright blue
pH at 10%	9.0
Specific Gravity	
Density	8.9 lbs/gal (1063 kg/m ³)
Flash Point	
Boiling Point	212°F (100°C)
Chlorine	
Mineral Oil	0%
Refractometer Readings	10:1 = 3.5
· ·	20:1 = 1.8
	30:1 = 1.0

DILUTION RATIOS

•	Band, circular, and general sawing	20:1
•	Machining, grinding	10:1 – 20:1

AVAILABLE IN

5 gal	. 76205
55 gal	. 76255

HEALTH AND SAFETY

Refer to SDS (Safety Data Sheet) for complete information on health and safety on our web site at www.itwprofessionalbrands.com.

For additional information please contact our Customer Service Department at 800-241-8334.