

Revision Number: 005.0 Issue date: 09/15/2014

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:Quickset Epoxy Part AIDH number:1427733Product type:Epoxy resinItem number:1395391\_588019Restriction of Use:None identifiedRegion:United States

Restriction of Use: None identified Region:
Company address: Contact information:
Henkel Corporation Telephone: (860) 571-

Henkel Corporation
One Henkel Way
Telephone: (860) 571-5100
MEDICAL EMERGENCY Phone: Poison Control Center

Rocky Hill, Connecticut 06067

1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

WARNING: CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1

# PICTOGRAM(S)



### **Precautionary Statements**

Prevention: Avoid breathing vapors, mist, or spray. Wash thoroughly after handling. Contaminated work

clothing should not be allowed out of the workplace. Wear eye and face protection. Wear

protective gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical

attention. Take off contaminated clothing.

Storage: Not prescribed

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
------------------------	------------	-------------

Epoxy resin Proprietary 60 - 100

### 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. If symptoms develop and persist, get medical attention. Wash clothing before reuse. Thoroughly clean shoes before

reuse.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

**Ingestion:** DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical

attention.

Symptoms: See Section 11.

### 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: Closed containers may rupture (due to build up of pressure) when exposed to

extreme heat. In case of fire, keep containers cool with water spray.

**Hazardous combustion products:** Oxides of carbon. Phenolics. Toxic fumes. Irritating vapors.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Ensure adequate ventilation. Wear appropriate personal protective equipment.

Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed

container for disposal.

## 7. HANDLING AND STORAGE

**Handling:** Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Use only with adequate ventilation. Keep

container closed.

Storage: Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials. Keep away from heat, spark and flame. Protect from

direct sunlight.

IDH number: 1427733 Product name: Quickset Epoxy Part A

<sup>\*</sup> Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Epoxy resin	None	None	None	None

**Engineering controls:** Local exhaust ventilation is recommended when general ventilation is not

sufficient to control airborne contamination.

Use a NIOSH approved respirator if ventilation is inadequate. Respiratory protection:

Safety goggles or safety glasses with side shields. Full face protection should Eve/face protection:

be used if the potential for splashing or spraying of product exists.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Color: Translucent, Clear

Odor: None

Odor threshold: Not available. Not applicable pH: Vapor pressure: 0.03 mm hg

> 260.2 °C (> 500.4 °F) Boiling point/range:

Melting point/ range: Not available. 1.17

Specific gravity:

Vapor density: Not available.

> 249 °C (> 480.2 °F) Pensky Martens closed cup Flash point:

Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Evaporation rate: Not available. Solubility in water: Slight

Partition coefficient (n-octanol/water): Not available.

**VOC** content: 0.1 % (value for resin and hardener together)

Viscosity: Not available. **Decomposition temperature:** Not available.

## 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

**Hazardous reactions:** None under normal processing.

Hazardous decomposition

products:

Oxides of carbon. Phenolics. Toxic fumes. Irritating vapors.

Incompatible materials: Strong oxidizing agents. Strong bases. Strong acids. Amines.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials. Protect from direct sunlight.

### **TOXICOLOGICAL INFORMATION**

Relevant routes of exposure: Skin, Inhalation, Eyes

IDH number: 1427733 Product name: Quickset Epoxy Part A

#### Potential Health Effects/Symptoms

Inhalation: Inhalation of vapors or mists of the product may be irritating to the respiratory system.

**Skin contact:** Causes skin irritation. May cause allergic skin reaction.

**Eve contact:** Causes serious eve irritation.

**Ingestion:** Not expected under normal conditions of use.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Epoxy resin	None	Allergen, Irritant	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Epoxy resin	No	No	No

### 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:

Not regulated

Hazard class or division: None Identification number: None Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorhydrin

resin)
Hazard class or division:

Identification number: UN 3082 Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A

Epichlorhydrin resin)

Hazard class or division:

Identification number: UN 3082

Packing group:

Marine pollutant: Bisphenol-A Epichlorhydrin resin

### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis

CERCLA/SARA Section 311/312: Immediate Health

IDH number: 1427733 Product name: Quickset Epoxy Part A

CERCLA/SARA Section 313: None above reporting de minimis

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

**Canada Regulatory Information** 

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Rena Petrides, Regulatory Affairs Specialist

**Issue date:** 09/15/2014

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 1427733 Product name: Quickset Epoxy Part A