

Revision Number: 008.0 Issue date: 08/21/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Loctite(R) 620 Retaining Compound IDH number: 135514

Slip Fit

 Product type:
 Anaerobic Adhesive
 Item number:
 62040

 Restriction of Use:
 None identified
 Region:
 United States

Company address:Contact information:Henkel CorporationTelephone: (860) 571-5100

One Henkel Way

MEDICAL EMERGENCY Phone: Poison Control Center
Rocky Hill, Connecticut 06067

1-877-671-4608 (toll free) or 1-303-592-1711

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

TOXIC IF INHALED.

| HAZARD CLASS | HAZARD CATEGORY |
|---------------------------|-----------------|
| ACUTE TOXICITY INHALATION | 3 |
| SKIN IRRITATION | 2 |
| EYE IRRITATION | 2A |
| SKIN SENSITIZATION | 1 |







Precautionary Statements

Prevention: Avoid breathing vapors, mist, or spray. Wash thoroughly after handling. Use only outdoors or in

a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace.

Wear eye and face protection. Wear protective gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Call a poison control center or physician. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention.

Take off contaminated clothing.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* | |
|--|-------------|-------------|--|
| Dimethacrylate ester | Proprietary | 60 - 100 | |
| Resin | Proprietary | 10 - 30 | |
| Hydroxyalkyl methacrylate | 27813-02-1 | 1 - 5 | |
| Cumene hydroperoxide | 80-15-9 | 1 - 5 | |
| Silica, amorphous, fumed, crystal-free | 112945-52-5 | 1 - 5 | |
| Polyglycol dimethacrylate | Proprietary | 0.1 - 1 | |
| Cumene | 98-82-8 | 0.1 - 1 | |
| 1-Acetyl-2-phenylhydrazine | 114-83-0 | 0.1 - 1 | |

^{*} Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. Wash clothing before reuse. Get medical

attention.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical

attention.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Uncontrolled polymerization may occur at high temperatures resulting in

explosions or rupture of storage containers.

Hazardous combustion products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Toxic fumes. Irritating

organic vapours.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to

prevent entry into water system; wear full protective equipment during cleanup. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure

Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Keep container closed. Refer to Section 8.

Storage: For safe storage, store at or below 38 °C (100.4 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|--|--|-------------------------------------|----------------------------------|-------------------------|
| Dimethacrylate ester | None | None | None | None |
| Resin | None | None | None | None |
| Hydroxyalkyl methacrylate | None | None | None | 1 ppm TWA 3 ppm STEL |
| Cumene hydroperoxide | None | None | 1 ppm (6 mg/m3) TWA (SKIN) | None |
| Silica, amorphous, fumed, crystal-free | 10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction. | 20 MPPCF TWA 0.8 mg/m3 TWA | None | None |
| Polyglycol dimethacrylate | None | None | None | None |
| Cumene | 50 ppm TWA | 50 ppm (245 mg/m3) PEL (SKIN) | None | None |
| 1-Acetyl-2-phenylhydrazine | None | None | None | None |

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. Neoprene gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:GreenOdor:MildOdor threshold:Not available.

pH: Not applicable Vapor pressure: <5 mm hg (27 °C (80.6 °F))

Boiling point/range: > 149 °C (> 300.2 °F) **Melting point/ range:** Not available.

Specific gravity:

Vapor density: Not available.

Flash point: > 93.3 °C (> 199.94 °F) Tagliabue closed cup

Flammable/Explosive limits - lower: Not available.
Flammable/Explosive limits - upper: Not available.
Autoignition temperature: Not available.

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

Viscosity:

Decomposition temperature:

Not available.

Not available.

Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing. Polymerization may occur at elevated temperature or in the

presence of incompatible materials.

Hazardous decomposition

products:

Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Toxic fumes. Irritating organic vapours.

Incompatible materials: Strong oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from

incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: Toxic by inhalation.

Skin contact:Causes skin irritation. May cause allergic skin reaction.Eye contact:Causes serious eye irritation.Ingestion:May cause gastrointestinal tract irritation if swallowed.

| Hazardous Component(s) | LD50s and LC50s | Immediate and Delayed Health Effects | |
|--|---|--|--|
| Dimethacrylate ester | None | Irritant, Allergen | |
| Resin | None | No Target Organs | |
| Hydroxyalkyl methacrylate | None | Irritant, Allergen | |
| Cumene hydroperoxide | None | Allergen, Central nervous system, Corrosive, Irritant, Mutagen | |
| Silica, amorphous, fumed, crystal-free | None | Nuisance dust | |
| Polyglycol dimethacrylate | None | Allergen, Irritant | |
| Cumene | Oral LD50 (RAT) = 2.91 g/kg Oral LD50 (RAT) = 1,400 mg/kg Inhalation LC50 (RAT, 4 h) = 8000 ppm | Central nervous system, Irritant, Lung | |
| 1-Acetyl-2-phenylhydrazine | None | Allergen, Blood, Kidney, Mutagen, Some evidence of carcinogenicity | |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|--|----------------|-----------------|--|
| Dimethacrylate ester | No | No | No |
| Resin | No | No | No |
| Hydroxyalkyl methacrylate | No | No | No |
| Cumene hydroperoxide | No | No | No |
| Silica, amorphous, fumed, crystal-free | No | No | No |
| Polyglycol dimethacrylate | No | No | No |
| Cumene | No | Group 2B | No |
| 1-Acetyl-2-phenylhydrazine | No | No | No |

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number:Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: RQ, Environmentally hazardous substances, liquid, n.o.s.

Hazard class or division: 9
Identification number: UN 3082

Packing group:

DOT Hazardous Substance(s): alpha,alpha-Dimethylbenzylhydroperoxide

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s.

Hazard class or division: 9

Identification number: UN 3082 Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard class or division: 9

Identification number: UN 3082 Packing group: III

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
CERCLA/SARA Section 313: This product contains the following

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Cumene hydroperoxide (CAS# 80-15-9).

CERCLA Reportable quantity: Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Sheila Gines, Regulatory Affairs Specialist

Issue date: 08/21/2014

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.