PROBRANDS

SAFETY DATA SHEET

1. Identification

Product identifier LPS® Strong Steel Sticks

Other means of identification

Part Number 60159

Recommended use A "ready-to-mix", fast curing, high strength adhesive epoxy putty for emergency repairs of cracks

and rebuilding of surfaces on metal, concrete, wood, fiberglass and ceramics.

Category 1

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Manufacturer

Company name ITW Pro Brands

Address 4647 Hugh Howell Rd.

Tucker, GA 30084

Country (U.S.A.)

Tel: +1 770-243-8800

In Case of Emergency 1-800-424-9300 (inside U.S.)

+001 703-527-3887 (outside U.S.)

Website www.lpslabs.com

E-mail lpssds@itwprobrands.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Sensitization, skin

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement May cause an allergic skin reaction.

Precautionary statement

Prevention Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be

allowed out of the workplace. Wear protective gloves.

Response If on skin: Wash with plenty of water. Wash contaminated clothing before reuse. If skin irritation or

rash occurs: Get medical advice/attention.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Magnesium Silicate Hydrate	Talc, not containing asbestiform fibres	14807-96-6	30 - 60
Ferrosilicon		8049-17-0	10 - 30

Material name: LPS® Strong Steel Sticks
60159 Version #: 02 Revision date: 05-01-2017 Issue date: 04-07-2015

Chemical name	Common name and synonyms	CAS number	%
Glass, oxide, chemicals		65997-17-3	10 - 30
Reaction product: bisphenol-A-(epichlorhydrin); epresin	роху	25068-38-6	10 - 30
Nepheline syenite		37244-96-5	1 - 5
Crystalline Silica	Quartz	14808-60-7	0.1 - 1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

symptoms/effects, acute and delayed

May cause an allergic skin reaction. May cause redness and pain. Rash. Dermatitis.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

None known.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Use water spray to cool unopened containers.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Dike far ahead of spill for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

,

8. Exposure controls/personal protection

Occupational exposure limits

			
US. OSHA Table	Z-1 Limits for Ai	r Contaminants ((29 CFR 1910.1000)

Components	Туре	Value	
Crystalline Silica (CAS 14808-60-7) US. OSHA Table Z-3 (29 CFI	PEL B 1910 1000)	0.05 mg/m3	
Components	Туре	Value	Form
Crystalline Silica (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
,		2.4 mppcf	Respirable.
Magnesium Silicate Hydrate (CAS 14807-96-6)	TWA	0.3 mg/m3	Total dust.
/		0.1 mg/m3	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
Crystalline Silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Magnesium Silicate Hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Crystalline Silica (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
Magnesium Silicate Hydrate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.
logical limit values	No biological exposure limits noted	for the ingredient(s).	

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica **Exposure guidelines**

should be monitored and controlled.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Wear appropriate chemical resistant clothing. Other

Use a particulate filter respirator for particulate concentrations exceeding the Occupational Respiratory protection

Exposure Limit.

Thermal hazards Not applicable.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

9. Physical and chemical properties

Appearance

Physical state Solid. **Form** Solid.

Color Dark grey; Black Sulphurous. Pungent. Odor

Odor threshold Not available.

Material name: LPS® Strong Steel Sticks

pH Not applicableMelting point/freezing point Not available.Initial boiling point and boiling Not available.

range

Flash point > 199.9 °F (> 93.3 °C) Setaflash

Evaporation rate Not available.

Flammability (solid, gas) Flammable solid.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density 2.247

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature > 3632 °F (> 2000 °C)

Viscosity Not applicable

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Temperatures above 35 °C

Incompatible materials None known.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact May cause an allergic skin reaction. Frequent or prolonged contact may defat and dry the skin,

leading to discomfort and dermatitis.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and

Direct contact with eyes may cause temporary irritation. May cause redness and pain. Rash.

Dermatitis.

toxicological characteristics

Information on toxicological effects

Acute toxicity May cause an allergic skin reaction.

Components Species Test Results

Glass, oxide, chemicals (CAS 65997-17-3)

Acute Oral

LD50 Rat > 2000 mg/kg

Material name: LPS® Strong Steel Sticks

60159 Version #: 02 Revision date: 05-01-2017 Issue date: 04-07-2015

Components **Species Test Results**

Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (CAS 25068-38-6)

Acute Dermal

LD50 Rat > 800 mg/kg, 24 Hours

Oral

Rat LD50 > 500 mg/kg

Skin corrosion/irritation Serious eye damage/eye Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

May cause an allergic skin reaction. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

ACGIH Carcinogens

Crystalline Silica (CAS 14808-60-7) A2 Suspected human carcinogen.

Magnesium Silicate Hydrate (CAS 14807-96-6) A4 Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline Silica (CAS 14808-60-7) 1 Carcinogenic to humans.

Magnesium Silicate Hydrate (CAS 14807-96-6) 2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not likely, due to the form of the product.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

No data available.

Mobility in soil No data available. Other adverse effects None known.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Crystalline Silica (CAS 14808-60-7)

Magnesium Silicate Hydrate (CAS 14807-96-6)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No

Material name: LPS® Strong Steel Sticks

SDS US

On inventory (yes/no)* Country(s) or region Inventory name

Japan Inventory of Existing and New Chemical Substances (ENCS) Existing Chemicals List (ECL) Korea No

New Zealand New Zealand Inventory No No

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

04-07-2015 Issue date 05-01-2017 **Revision date**

Version # 02

ITW Pro Brands cannot anticipate all conditions under which this information and its product, or Disclaimer

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless

specified in the text.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: LPS® Strong Steel Sticks

7/7 60159 Version #: 02 Revision date: 05-01-2017 Issue date: 04-07-2015