## SELLARS. 🚽 The NATURAL choice for all Sorbents your wiping & spill control needs. EverSoak<sup>®</sup> Preferred Sorbent Pads Preferred **Sorbent Pads** Coverstock on top of pad Absorbs up to 23.5 gallons of oil per bale \* Extra thick Coverstock on absorbant bottom of pad core made with Q-Cel® technology \* per ASTM F726-06 Made in the USA

- Made with 80% recycled cellulose fibers
- Heavy-weight general purpose oil absorbent pads soak up both oil and water as well as grease, transmission fluid, hydraulic fluid, coolants, diesel fuel and many other fluids
- Due to the incredible absorbency of the EVERSOAK® PREFERRED Oil Absorbent Pads, 50 PREFFERED pads will soak up as much as 100 of the leading competitor's oil absorbent pads allowing you to save valuable time and money
- □ Ash content is 1.8% per ASTM D482
- 9,611 BTU/lb per ASTM D5468
- Made with minimal oil derivatives allowing for stable pricing
- Class A fire retardant when pad is dry (lab tested per ASTM E84)
- Helps you comply with 29 CFR 1910.22(a)
  (2)

*Caution: Not intended for use with aggressive acids or caustics. Dispose of all sorbent materials in accordance with local, state and federal regulations.* 



**Preferred Pads Outer Case** 



Preferred Pads Outer Case on a Pallet

## To order, contact your Authorized Sellars<sup>®</sup> Distributor

## PREFERRED Sorbent Pads

Product Number:	22851
Pad Size:	15" x 19"
Quantity Per Case:	50/box
Color:	Grey
Cases Per Pallet:	30 cases/pallet LTL
	30 cases per pallet TL
TI:	6 cases/layer
HI:	5 layers/pallet
Case Dimensions:	Length: 20"
	Width: 16"
	Height: 18.25"
Case Weight:	13 lbs
Pallets Per Truck:	30
UPC:	660708228511
GTIN:	NA

©2011 Sellars Absorbent Materials, Inc. 6.11

