R Print Date 06/01/2016

Revision Date 06/01/2016

#### 1. Identification

Product name : Sikalastic®-391 Part A

Supplier : Sika Corporation

201 Polito Avenue Lyndhurst, NJ 07071

USA

www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300

INTERNATIONAL: 703-527-3887

Recommended use of the chemical and restrictions on

cnemical and res

For further information, refer to product data sheet.

### 2. Hazards identification

### **GHS Classification**

Carcinogenicity, Category 2 H351: Suspected of causing cancer.

#### **GHS** label elements

Hazard pictograms

Signal Word : Warning

Hazard Statements : H351 Suspected of causing cancer.

Precautionary Statements : **Prevention:** 

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P281 Use personal protective equipment as required.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/

attention. Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.



Revision Date 06/01/2016

See Section 11 for more detailed information on health effects and symptoms.

There are no hazards not otherwise classified that have been identified during the classification process.

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

### 3. Composition/information on ingredients

### Hazardous ingredients

| Chemical name    | CAS-No.    | Concentration (%) |
|------------------|------------|-------------------|
| titanium dioxide | 13463-67-7 | >= 2 - < 5 %      |
| Carbon black     | 1333-86-4  | >= 0 - < 1 %      |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

#### 4. First aid measures

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Induce vomiting immediately and call a physician.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

: No known significant effects or hazards.

See Section 11 for more detailed information on health effects

and symptoms.

Protection of first-aiders : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in

attendance.

Notes to physician : Treat symptomatically.



Revision Date 06/01/2016

5. Fire-fighting measures

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Specific extinguishing

methods

: Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Environmental precautions : Use personal protective equipment. Deny access to unprotected persons.

: Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

## 7. Handling and storage

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Store in original container.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

Materials to avoid : No data available

#### 8. Exposure controls/personal protection



Revision Date 06/01/2016

Print Date 06/01/2016

| Component                   | CAS-No.     | Basis ** | Value | Exposure limit(s)* / Form of exposure |
|-----------------------------|-------------|----------|-------|---------------------------------------|
| titanium dioxide            | 13463-67-7  | OSHA Z-1 | TWA   | 15 mg/m3<br>total dust                |
|                             |             | OSHA P0  | TWA   | 10 mg/m3<br>Total dust                |
|                             |             | ACGIH    | TWA   | 10 mg/m3                              |
| Hydrocarbons, C9, aromatics | 128601-23-0 | OSHA Z-1 | TWA   | 500 ppm<br>2,000 mg/m3                |
|                             |             | ACGIH    | TWA   | 200 mg/m3                             |
|                             |             | OSHA P0  | TWA   | 400 ppm<br>1,600 mg/m3                |
| Carbon black                | 1333-86-4   | ACGIH    | TWA   | 3.5 mg/m3                             |
|                             |             | OSHA Z-1 | TWA   | 3.5 mg/m3                             |
|                             |             | OSHA P0  | TWA   | 3.5 mg/m3                             |
|                             |             | ACGIH    | TWA   | 3 mg/m3<br>Inhalable fraction         |
|                             |             | CAL PEL  | PEL   | 3.5 mg/m3                             |

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

## \*\*Basis

ACGIH. Threshold Limit Values (TLV)

OSHA Po. Table Z-1, Limit for Air Contaminat (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

## **Engineering measures**

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

### Personal protective equipment

: Use a properly fitted NIOSH approved air-purifying or air-fed Respiratory protection

respirator complying with an approved standard if a risk

assessment indicates this is necessary.

The filter class for the respirator must be suitable for the

maximum expected contaminant concentration



Revision Date 06/01/2016

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hygiene measures : Wash hands before breaks and immediately after handling the

product.

Remove contaminated clothing and protective equipment

before entering eating areas.

### 9. Physical and chemical properties

Appearance : liquid
Color : gray

Odor : neutral

Odor Threshold : No data available

Flash point : 200.01 °F (93.34 °C)

Ignition temperature : Not applicable

Decomposition temperature : No data available

Lower explosion limit (Vol%) : No data available

Upper explosion limit (Vol%) : No data available

Flammability (solid, gas) : No data available

Oxidizing properties : No data available

pH : Note: Not applicable

Melting point/range /

Freezing point

Boiling point/boiling range : No data available

Vapor pressure : No data available

Density : ca.1.24 g/cm3

No data available

# Safety Data Sheet

# Sikalastic®-391 Part A



### Revision Date 06/01/2016

at 73 °F (23 °C)

Water solubility : Note: insoluble

Partition coefficient: n-

Viscosity, dynamic

octanol/water

No data available

: No data available

Viscosity, kinematic : ca.> 20.5 mm2/s

at 104 °F (40 °C)

Relative vapor density : No data available

Evaporation rate : No data available

Burning rate : No data available

Volatile organic compounds

(VOC) content

: 1 g/l

A+B Combined

## 10. Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous

Conditions to avoid

reactions

: Stable under recommended storage conditions.

: No data available

Incompatible materials : No data available

## 11. Toxicological information

## **Acute toxicity**

Product:

Acute oral toxicity : No data available

Acute inhalation toxicity : No data available

Acute dermal toxicity : No data available

**Ingredients:** 

Carbon black:

Acute oral toxicity : LD50 Oral (Rat): > 8,000 mg/kg

### Skin corrosion/irritation

**Product:** 

Remarks: No data available



Revision Date 06/01/2016

## Serious eye damage/eye irritation

**Product:** 

Remarks: No data available

Respiratory or skin sensitization

**Product:** 

Remarks: No data available

Germ cell mutagenicity

Product:

Germ cell mutagenicity -

: No data available

Assessment

Carcinogenicity

**Product:** 

Carcinogenicity - Assessment

: Suspected of causing cancer.

Assessifieri

IARC Group 2B: Possibly carcinogenic to humans

titanium dioxide

13463-67-7

Carbon black

1333-86-4

NTP Not applicable

Reproductive toxicity

**Product:** 

Reproductive toxicity -

: No data available

Assessment

No data available

STOT-single exposure

**Product:** 

Assessment: No data available

STOT-repeated exposure

**Product:** 

Assessment: No data available

**Aspiration toxicity** 

**Product:** 

No data available



Revision Date 06/01/2016

12. Ecological information

Other information Do not empty into drains; dispose of this material and its

container in a safe way.

Avoid dispersal of spilled material and runoff and contact

with soil, waterways, drains and sewers.

Component:

Carbon black 1333-86-4 Toxicity to fish: LC50

Species: Brachydanio rerio (zebrafish)

Dose: > 1,000 mg/l Exposure time: 96 h

## 13. Disposal considerations

**Disposal methods** 

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

## 14. Transport information

DOT

Not dangerous goods

IATA

Not dangerous goods

**IMDG** 

Not dangerous goods

Special precautions for user

No data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## 15. Regulatory information

**TSCA list** : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

Print Date 06/01/2016

Revision Date 06/01/2016

exemption.

### **EPCRA - Emergency Planning and Community Right-to-Know**

### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

## **SARA304** Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Chronic Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

Ozone-Depletion

**Potential** 

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

### 16. Other information

#### **HMIS Classification**



Caution: HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

## Notes to Reader



Revision Date 06/01/2016

Print Date 06/01/2016

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 06/01/2016

Material number: 471647