

Paraseal® Permanent Seam Tape™

Paraseal Accessory

Product Description

Paraseal® Permanent Seam Tape™ is a 60-mil thick rubberized asphalt membrane laminated to a polyethylene reinforcing film. A removable release paper protects the adhesive membrane face until removed during installation.

Racic Head

Permanent Seam Tape is used primarily for sealing the seams of Paraseal and Deckseal applications when flood testing is desired. It is used on all seams of Paraseal Saltwater Grade applications and with Paraseal LG when installed for vaporproofing. The inherent adhesive and waterproofing properties of the rubberized-asphalt membrane effectively seals the HDPE liner face on Paraseal products to render the bentonite a secondary back-up.

Availability

Immediately available from your local Tremco Sales Representative or Distributor. For Distributor locations, visit www.tremcosealants.com.

Packaging

4" x 75' long rolls (22 m)/ 6 rolls case.

Warranty

Tremco warrants its Products to be free of defects in materials but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of Tremco Products proven to be defective, and Tremco shall not be liable for any loss or damage.

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.



0517/SEAMTAPEDS-BG