



Cordless MULTIMASTER AMM 700 Max AS

Cordless oscillating multi-tool

Our best cordless MultiTool for ultra-rapid work progress with interior construction and renovation in the variant without a storage battery and charger – with a bi-metal saw blade for wood, metal, and plastics.

Product number: 7 129 36 62 09 0

Details

- Anti-vibration system: Permanently safe, pleasant working conditions with minimum vibrations and outstanding noise damping.
- StarlockMax tool mounting: Work faster and with higher precision thanks to 100% no-loss power transmission.
- QuickIN: Tool change in under 3 seconds with a patented, tool-free, FEIN rapid-clamping system.
- With the StarlockMax tool mounting, you have access to around 180 FEIN accessories in the Starlock, StarlockPlus and StarlockMax performance categories.
- 18 V FEIN PowerDrive motor: Especially powerful, virtually wear-free brushless motor with high efficiency, extremely high load handling and long service life.
- Tacho generator: Constant speeds, even under load, and infinitely variable electronic speed control.

- Metal drive head: High load capacity and maximum service life, since all drive head parts are made of metal.
- Mechanical interface: For stationary use in the table or drill jig holders, or to attach depth stops.
- Electronic cell protection (ECP): ECP protects storage batteries against overloading, overheating and deep discharge.
- COOLPACK technology ensures a longer storage battery service life, enabling longer operation times.
- The battery capacity can be read directly on the battery.
- Compatible with AMPShare/Bosch Professional 18 V batteries from 2008 on.
- Perfectly equipped for any job with our L-BOXX system.
- Electronic safety cut-off protection for users if the saw blade blocks, for example.

Price includes

- 1 universal E-Cut saw blade 1-3/4 in (44 mm) (type 152)
- + 1 tool case (L-BOXX 136)

Product feature

+ Mechanical interconnection



Technical data

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES

Battery voltage	18 V	Sound pressure level LpA Measurement uncertainty of the	76,0 dB 3 dB
Battery compatibility	Li-ion / CORE 18 V Li-	measured value KpA	
	ions	Sound power level LWA Measurement uncertainty of the measured value KWA	84,0 dB 3 dB
Battery interface	18 V AMPShare		
Oscillations	10,000 - 19,500 opm	Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	88,4 dB
Tool mount	StarlockMax		3 dB
Tool change	QuickIN		
Range	2 x 2,0°		
Weight without battery	2.43 [1.10] lbs[kg]		

Application examples



Compatible with AMPShare/Bosch Professional 18 V batteries.

Compatible avec les batteries 18 V AMPShare/Bosch Professional. | Compatible con baterías AMPShare/ Bosch Professional de 18 V.









