



FEIN



MULTIMASTER MM 700 Max Top

Oscillating MultiTools - MM 700

Top in its performance class, our MULTIMASTER 700 makes quick work of professional interior construction and renovation jobs. Includes accessories for sawing in wood, metal, plastics, removing tiles, cutting silicone caulking and carpeting, and removing residual adhesive and tile adhesive.

Product number: 7 229 68 64 09 0

Details

- + Anti-vibration system: Permanently safe, pleasant working conditions with minimum vibrations and outstanding noise damping.
- + StarlockMax tool mounting: Work faster and with higher precision thanks to 100% no-loss power transmission.
- + QuickIN: Tool change in under 3 seconds with a patented, tool-free, FEIN rapid-clamping system.
- + With the StarlockMax tool mounting, you have access to around 180 FEIN accessories in the Starlock, StarlockPlus and StarlockMax performance categories.
- + 450 W FEIN high-performance motor: Durable, overload-proof, high-performance motor with high proportion of copper for higher cutting speed and ultra-rapid work progress.
- + Tacho generator: Constant speeds, even under load, and infinitely variable electronic speed control.
- + Metal drive head: High load capacity and maximum service life, since all drive head parts are made of metal.
- + Mechanical interface: For stationary use in the table or drill jig holders, or to attach depth stops.
- + Industrial cable: Large operating radius thanks to the 5 m, fine-stranded rubber-clad cable in industrial quality.
- + Electronic safety cut-off – protection for users if the saw blade blocks, for example.
- + Perfectly equipped for any job with our L-BOXX system.

Price includes

- | | |
|---------------------------------------------------------------|-----------------------------------------------------------|
| + 2 E-Cut standard saw blades, curved (1-3/8 [35] in[mm]) | + 2 E-Cut standard saw blades, curved (2-1/2 [65] in[mm]) |
| + 1 E-Cut Precision BIM saw blade (1-3/8 [35] in[mm]) | + 1 E-Cut Precision BIM saw blade (2-1/4 [65] in[mm]) |
| + 1 E-Cut Long Life saw blade (10 mm) | + 2 E-Cut Long Life saw blades (1-3/8 [35] in[mm]) |
| + 1 E-Cut Long Life saw blade (1-1/4 [32] in[mm]) | + 1 E-Cut Long Life saw blade (1-5/8 [42] in[mm]) |
| + 1 E-Cut Carbide Pro saw blade (1-1/4 [32] in[mm]) | + 1 segmented saw blade (Ø 3-3/8 [85] in[mm]) |
| + 1 HM saw blade (Ø 3 [75] in[mm]) | + 1 carbide rasp (triangular) |
| + 1 rigid scraper blade | + 1 mushroom-shaped cutting blade 6 390 31 28 01 2 |
| + 1 Multi-knife | + 1 perforated sanding pad |
| + 10 sanding sheets, perforated each (grits 60, 80, 120, 180) | + 1 dust extraction device |
| + 1 tool case (L-BOXX 136) | |

Product feature

+ Mechanical interconnection

Technical data

TECHNICAL DATA

Power consumption	450 W
Power output	250 W
Oscillations	10,000 - 19,500 opm
Tool mount	StarlockMax
Tool change	QuickIN
Range	2 x 2,0°
Cable with plug	16.4 [5] ft[m]
Weight	3.53 [1.60] lbs[kg]

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Measurement uncertainty of the measured value KpA	85 dB 3 dB
Sound power level LWA Measurement uncertainty of the measured value KWA	96 dB 3 dB
Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	97 dB 3 dB

Application examples

