




CC500MXL2 Masonry Saw

Features & Benefits:

- Stay level blade guard
- Removable cutting head
- Leg kit standard-folding stand optional
- Side carrying handles
- Replaceable conveyor cart rails
- Includes water pump
- Vulcanized rubber coated material slide cart
- Open throat cutting
- Easy and safe access to depth control lock
- Open back cutting allows longer material to be cut
- Heavy duty frame design help resist damage to saw body
- Reinforced slide rails keep the cart running smoothly
- Simple yet strong design allows easy maintenance
- Sealed drain hole on the bottom of the tray allows quick clean up

Specifications:

Maximum Depth of Cut:	5"
Blade Shaft Diameter:	7/8"
Arbor Diameter:	1"
Blade Shaft Bearings:	Flange block ball bearings
Blade Shaft Drive:	2 belt
Blade Mounting:	Right (electric), Left (gas)
Blade Raise/Lower:	Counterbalanced, spring tensioned head pivots on two 7/8" flange block bearings
Blade Coolant:	Dual spray tubes, pump fed (electric models), pump from tray (gas models)
Air Filter:	3-stage cyclone (gas models)
Fuel Capacity:	1 gallon (gas models)
High Temp Shut-off:	Included (electric models)



Product Details

<https://www.diamondproducts.com/cc500mxl2-masonry-saw>

Size	Part Number	Catalog Number
	5800799	03725
	5800814	08667
	5800801	03726
	5800802	03728
	5801217	23961