

**DOW CORNING(R) 795 SILICONE BUILDING
SEALAN T, LIMESTONE**

Version 3.0 Revision Date: 10/10/2015 SDS Number: 948592-00003 Date of last issue: 03/24/2015
Date of first issue: 12/12/2014

SECTION 1. IDENTIFICATION

Product name : DOW CORNING(R) 795 SILICONE BUILDING SEALAN T,
LIMESTONE

Product code : 000000000003104494

Manufacturer or supplier's details

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road
Midland Michigan 48686

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900
CHEMTREC : (800) 424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Adhesive, binding agents

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Precautionary Statements : **Prevention:**
P271 Use only outdoors or in a well-ventilated area.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Silicone elastomer

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Calcium carbonate	471-34-1	>= 50 - < 70
Amorphous fumed silica	112945-52-5	>= 1 - < 5
Magnesium carbonate	546-93-0	>= 1 - < 5
Quartz	14808-60-7	>= 0.1 - < 1
Titanium dioxide	13463-67-7	>= 0.1 - < 1
Methanol	67-56-1	>= 0.1 - < 1

**DOW CORNING(R) 795 SILICONE BUILDING
SEALAN T, LIMESTONE**

Version 3.0	Revision Date: 10/10/2015	SDS Number: 948592-00003	Date of last issue: 03/24/2015 Date of first issue: 12/12/2014
----------------	------------------------------	-----------------------------	---

Carbon black	1333-86-4	>= 0.1 - < 1
--------------	-----------	--------------

SECTION 4. FIRST AID MEASURES

- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : No special precautions are necessary for first aid responders.
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Metal oxides
Silicon oxides
Formaldehyde
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment : Wear self-contained breathing apparatus for firefighting if nec-

**DOW CORNING(R) 795 SILICONE BUILDING
SEALANT, LIMESTONE**

Version	Revision Date:	SDS Number:	Date of last issue: 03/24/2015
3.0	10/10/2015	948592-00003	Date of first issue: 12/12/2014

for fire-fighters

essary.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Avoid prolonged or repeated contact with skin. Handle in accordance with good industrial hygiene and safety practice. Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers. Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

DOW CORNING(R) 795 SILICONE BUILDING SEALAN T, LIMESTONE

Version
3.0Revision Date:
10/10/2015SDS Number:
948592-00003Date of last issue: 03/24/2015
Date of first issue: 12/12/2014

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium carbonate	471-34-1	TWA (Respirable)	5 mg/m ³	NIOSH REL
		TWA (total)	10 mg/m ³	NIOSH REL
Amorphous fumed silica	112945-52-5	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3
		TWA	6 mg/m ³ (Silica)	NIOSH REL
Magnesium carbonate	546-93-0	TWA (Respirable)	5 mg/m ³	NIOSH REL
		TWA (total)	10 mg/m ³	NIOSH REL
		TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
Quartz	14808-60-7	TWA (total dust)	30 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (Respirable fraction)	0.025 mg/m ³ (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m ³ (Silica)	NIOSH REL
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA	10 mg/m ³ (Titanium dioxide)	ACGIH
		TWA	200 ppm	ACGIH
Methanol	67-56-1	STEL	250 ppm	ACGIH
		TWA	200 ppm	NIOSH REL
		TWA	260 mg/m ³	NIOSH REL
		ST	250 ppm	NIOSH REL
Carbon black	1333-86-4	TWA	325 mg/m ³	NIOSH REL
		TWA	200 ppm	OSHA Z-1
		TWA	260 mg/m ³	OSHA Z-1
Carbon black	1333-86-4	TWA	3.5 mg/m ³	NIOSH REL
		TWA	3.5 mg/m ³	OSHA Z-1
		TWA (Inhal-)	3 mg/m ³	ACGIH

DOW CORNING(R) 795 SILICONE BUILDING
SEALAN T, LIMESTONE

Version 3.0 Revision Date: 10/10/2015 SDS Number: 948592-00003 Date of last issue: 03/24/2015
Date of first issue: 12/12/2014

|| | | able fraction) | | |

Biological occupational exposure limits

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI

Engineering measures : Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : For prolonged or repeated contact use protective gloves.
Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**DOW CORNING(R) 795 SILICONE BUILDING
SEALAN T, LIMESTONE**

Version	Revision Date:	SDS Number:	Date of last issue: 03/24/2015
3.0	10/10/2015	948592-00003	Date of first issue: 12/12/2014

Appearance	: paste
Color	: Limestone
Odor	: slight
Odor Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: Not applicable
Flash point	: Not applicable
Evaporation rate	: Not applicable
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapor pressure	: Not applicable
Relative vapor density	: No data available
Relative density	: 1.52
Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: Not applicable
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: No data available

SECTION 10. STABILITY AND REACTIVITY

DOW CORNING(R) 795 SILICONE BUILDING SEALAN T, LIMESTONE

Version	Revision Date:	SDS Number:	Date of last issue: 03/24/2015
3.0	10/10/2015	948592-00003	Date of first issue: 12/12/2014

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Use at elevated temperatures may form highly hazardous compounds. Can react with strong oxidizing agents. Methyl alcohol is formed upon contact with water or humid air. Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	:	None known.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products		
Thermal decomposition	:	Benzene Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Ingredients:

Calcium carbonate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

DOW CORNING(R) 795 SILICONE BUILDING SEALAN T, LIMESTONE

Version 3.0 Revision Date: 10/10/2015 SDS Number: 948592-00003 Date of last issue: 03/24/2015
 Date of first issue: 12/12/2014

Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
 Method: OECD Test Guideline 402
 Assessment: The substance or mixture has no acute dermal toxicity

Amorphous fumed silica:

Acute oral toxicity : LD50 (Rat): > 20,000 mg/kg
 Assessment: The substance or mixture has no acute oral toxicity
 Remarks: Information taken from reference works and the literature.

Magnesium carbonate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: OECD Test Guideline 420
 Assessment: The substance or mixture has no acute oral toxicity

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
 Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Assessment: The substance or mixture has no acute inhalation toxicity

Methanol:

Acute oral toxicity : Acute toxicity estimate (Humans): 300 mg/kg
 Method: Expert judgment
 Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l
 Exposure time: 4 h
 Test atmosphere: vapor
 Method: Expert judgment
 Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI
 Acute dermal toxicity : Acute toxicity estimate (Humans): 300 mg/kg
 Method: Expert judgment

Carbon black:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
 Acute inhalation toxicity : LC50 (Rat): > 0.0046 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist

**DOW CORNING(R) 795 SILICONE BUILDING
SEALAN T, LIMESTONE**

Version 3.0 Revision Date: 10/10/2015 SDS Number: 948592-00003 Date of last issue: 03/24/2015
Date of first issue: 12/12/2014

Skin corrosion/irritation

Not classified based on available information.

Ingredients:**Calcium carbonate:**

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Magnesium carbonate:

Method: EPISKIN Human Skin Model Test
Result: No skin irritation

Titanium dioxide:

Species: Rabbit
Result: No skin irritation

Methanol:

Species: Rabbit
Result: No skin irritation

Carbon black:

Species: Rabbit
Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Ingredients:**Calcium carbonate:**

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405

Magnesium carbonate:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405

Titanium dioxide:

Species: Rabbit
Result: No eye irritation

Methanol:

Species: Rabbit
Result: No eye irritation

Carbon black:

Species: Rabbit
Result: No eye irritation

**DOW CORNING(R) 795 SILICONE BUILDING
SEALAN T, LIMESTONE**

Version 3.0 Revision Date: 10/10/2015 SDS Number: 948592-00003 Date of last issue: 03/24/2015
Date of first issue: 12/12/2014

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.

Respiratory sensitization: Not classified based on available information.

Ingredients:**Calcium carbonate:**

Test Type: Local lymph node assay (LLNA)

Routes of exposure: Skin contact

Species: Mouse

Method: OECD Test Guideline 429

Result: negative

Titanium dioxide:

Test Type: Local lymph node assay (LLNA)

Routes of exposure: Skin contact

Species: Mouse

Result: negative

Methanol:

Test Type: Maximization Test

Routes of exposure: Skin contact

Species: Guinea pig

Result: negative

Carbon black:

Test Type: Buehler Test

Routes of exposure: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:**Calcium carbonate:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Magnesium carbonate:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Titanium dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Result: negative

DOW CORNING(R) 795 SILICONE BUILDING SEALAN T, LIMESTONE

Version 3.0 Revision Date: 10/10/2015 SDS Number: 948592-00003 Date of last issue: 03/24/2015
 Date of first issue: 12/12/2014

Methanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Method: OECD Test Guideline 471
 Result: negative

Genotoxicity in vivo : Test Type: In vitro mammalian cell gene mutation test
 Method: OECD Test Guideline 476
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
 Species: Mouse
 Application Route: Intraperitoneal injection
 Result: negative

Carbon black:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
 Result: negative

Carcinogenicity

Not classified based on available information.

Ingredients:

Magnesium carbonate:

Species: Mouse
 Application Route: Ingestion
 Exposure time: 18 Months
 Result: negative
 Remarks: Based on data from similar materials

Quartz:

Species: Humans
 Application Route: inhalation (dust/mist/fume)
 Result: positive
 Remarks: IARC (International Agency for Research on Cancer)
 The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

Titanium dioxide:

Species: Rat
 Application Route: inhalation (dust/mist/fume)
 Exposure time: 24 Months
 Method: OECD Test Guideline 453
 Result: positive
 Remarks: The mechanism or mode of action may not be relevant in humans.
 The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

DOW CORNING(R) 795 SILICONE BUILDING SEALAN T, LIMESTONE

Version 3.0 Revision Date: 10/10/2015 SDS Number: 948592-00003 Date of last issue: 03/24/2015
 Date of first issue: 12/12/2014

||

Methanol:

Species: Mouse
 Application Route: inhalation (vapor)
 Exposure time: 18 Months
 Method: OECD Test Guideline 453
 Result: negative

IARC

Group 1: Carcinogenic to humans

Quartz 14808-60-7

Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

Carbon black 1333-86-4

OSHA

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

Known to be human carcinogen

Quartz 14808-60-7

Reproductive toxicity

Not classified based on available information.

Ingredients:**Calcium carbonate:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 422
 Result: negative

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 422
 Result: negative

Magnesium carbonate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 422
 Result: negative
 Remarks: Based on data from similar materials

**DOW CORNING(R) 795 SILICONE BUILDING
SEALAN T, LIMESTONE**

Version 3.0 Revision Date: 10/10/2015 SDS Number: 948592-00003 Date of last issue: 03/24/2015
Date of first issue: 12/12/2014

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Methanol:

Effects on fertility : Test Type: Fertility/early embryonic development
Species: Mouse
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: positive
Remarks: The effects were seen only at maternally toxic doses.

STOT-single exposure

Not classified based on available information.

Ingredients:**Methanol:**

Target Organs: Eyes, Central nervous system
Assessment: Causes damage to organs.

STOT-repeated exposure

Not classified based on available information.

Ingredients:**Quartz:**

Routes of exposure: inhalation (dust/mist/fume)
Target Organs: Lungs
Assessment: Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Carbon black:

Routes of exposure: inhalation (dust/mist/fume)
Assessment: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

Repeated dose toxicity**Ingredients:****Calcium carbonate:**

Species: Rat
NOAEL: 1,000 mg/kg

**DOW CORNING(R) 795 SILICONE BUILDING
SEALAN T, LIMESTONE**

Version 3.0 Revision Date: 10/10/2015 SDS Number: 948592-00003 Date of last issue: 03/24/2015
Date of first issue: 12/12/2014

Application Route: Ingestion
Exposure time: 6 Weeks
Method: OECD Test Guideline 422

Magnesium carbonate:

Species: Rat
NOAEL: 124 - 127 mg/kg
Application Route: Ingestion
Exposure time: 90 Days

Quartz:

Species: Humans
LOAEL: 0.053 mg/m³
Application Route: Inhalation
Remarks: OECD SIDS
The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Titanium dioxide:

Species: Rat
NOAEL: 24,000 mg/kg
Application Route: Ingestion
Exposure time: 28 d

Species: Rat
NOAEL: 10 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 2 y
Remarks: The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Methanol:

Species: Rat
NOAEL: 1.06 mg/l
Application Route: inhalation (vapor)
Exposure time: 90 Days

Carbon black:

Species: Rat
NOAEL: 1 mg/m³
LOAEL: 7 mg/m³
Application Route: Inhalation
Test atmosphere: dust/mist
Exposure time: 90 d
Remarks: The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Aspiration toxicity

Not classified based on available information.

DOW CORNING(R) 795 SILICONE BUILDING SEALAN T, LIMESTONE

Version	Revision Date:	SDS Number:	Date of last issue: 03/24/2015
3.0	10/10/2015	948592-00003	Date of first issue: 12/12/2014

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Ingredients:

Calcium carbonate:

- | | | |
|---|---|--|
| Toxicity to fish | : | LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202 |
| Toxicity to algae | : | ErC50 (Desmodesmus subspicatus (green algae)): > 14 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201 |

Magnesium carbonate:

- | | | |
|---|---|--|
| Toxicity to fish | : | LC50 (Pimephales promelas (fathead minnow)): 2,120 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): 490 - 1,127 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials |
| Toxicity to algae | : | ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials |
| Toxicity to bacteria | : | EC50: > 900 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials |

Quartz:

Ecotoxicology Assessment

- | | | |
|--------------------------|---|---|
| Acute aquatic toxicity | : | No toxicity at the limit of solubility. |
| Chronic aquatic toxicity | : | No toxicity at the limit of solubility. |

Titanium dioxide:

- | | | |
|---|---|--|
| Toxicity to fish | : | LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h |
| Toxicity to algae | : | EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l |

DOW CORNING(R) 795 SILICONE BUILDING SEALAN T, LIMESTONE

Version 3.0 Revision Date: 10/10/2015 SDS Number: 948592-00003 Date of last issue: 03/24/2015
 Date of first issue: 12/12/2014

	Exposure time: 72 h
Toxicity to bacteria	: EC50: > 1,000 mg/l Exposure time: 3 h Method: OECD Test Guideline 209
Methanol:	
Toxicity to fish	: LC50 (Lepomis macrochirus (Bluegill sunfish)): 15,400 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (green algae)): 22,000 mg/l Exposure time: 96 h Method: OPPTS 850.5400
Toxicity to fish (Chronic toxicity)	: NOEC (Oryzias latipes (Orange-red killifish)): 15,800 mg/l Exposure time: 200 h
Toxicity to bacteria	: EC50: 20,000 mg/l Exposure time: 15 h

Carbon black:

Toxicity to fish	: LC0 (Danio rerio (zebra fish)): 1,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 5,600 mg/l Exposure time: 24 h Method: OECD Test Guideline 202
Toxicity to algae	: NOEC (Desmodesmus subspicatus (green algae)): 10,000 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

Persistence and degradability**Ingredients:****Methanol:**

Biodegradability	: Result: Readily biodegradable. Biodegradation: 95 % Exposure time: 20 d
------------------	---

Bioaccumulative potential**Ingredients:****Methanol:**

Bioaccumulation	: Species: Leuciscus idus (Golden orfe) Bioconcentration factor (BCF): < 10
-----------------	--

**DOW CORNING(R) 795 SILICONE BUILDING
SEALAN T, LIMESTONE**

Version 3.0	Revision Date: 10/10/2015	SDS Number: 948592-00003	Date of last issue: 03/24/2015 Date of first issue: 12/12/2014
----------------	------------------------------	-----------------------------	---

Partition coefficient: n-octanol/water : log Pow: -0.77

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Resource Conservation and Recovery Act (RCRA) : This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulation****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)

DOW CORNING(R) 795 SILICONE BUILDING
SEALAN T, LIMESTONE

Version 3.0 Revision Date: 10/10/2015 SDS Number: 948592-00003 Date of last issue: 03/24/2015
Date of first issue: 12/12/2014

Methanol	67-56-1	5000	*
Toluene	108-88-3	1000	*
Ethylenediamine	107-15-3	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Ethylenediamine	107-15-3	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : No SARA Hazards

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations**Pennsylvania Right To Know**

Calcium carbonate	471-34-1	50 - 70 %
Dimethyl siloxane, hydroxy-terminated	70131-67-8	30 - 50 %
Dimethyl siloxane, trimethylsiloxy-terminated	63148-62-9	5 - 10 %
Amorphous fumed silica	112945-52-5	1 - 5 %
Methanol	67-56-1	0.1 - 1 %
Aluminium	7429-90-5	0 - 0.1 %
Toluene	108-88-3	0 - 0.1 %

New Jersey Right To Know

Calcium carbonate	471-34-1	50 - 70 %
Dimethyl siloxane, hydroxy-terminated	70131-67-8	30 - 50 %
Dimethyl siloxane, trimethylsiloxy-terminated	63148-62-9	5 - 10 %
Amorphous fumed silica	112945-52-5	1 - 5 %
Phenylmethyl siloxane, hydroxy-terminated	80801-30-5	1 - 5 %
Magnesium carbonate	546-93-0	1 - 5 %
Quartz	14808-60-7	0.1 - 1 %
Methanol	67-56-1	0.1 - 1 %
Carbon black	1333-86-4	0.1 - 1 %

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

Cobalt titanite green spinel 68186-85-6

WARNING: This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

Methanol 67-56-1

DOW CORNING(R) 795 SILICONE BUILDING SEALAN T, LIMESTONE

Version 3.0 Revision Date: 10/10/2015 SDS Number: 948592-00003 Date of last issue: 03/24/2015
 Date of first issue: 12/12/2014

Toluene

108-88-3

The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

AICS : All ingredients listed or exempt.


IECSC : All ingredients listed or exempt.

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
 ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
 NIOSH REL : USA. NIOSH Recommended Exposure Limits
 OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
 OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
 ACGIH / TWA : 8-hour, time-weighted average
 ACGIH / STEL : Short-term exposure limit
 NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
 NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
 OSHA Z-1 / TWA : 8-hour time weighted average
 OSHA Z-3 / TWA : 8-hour time weighted average

**DOW CORNING(R) 795 SILICONE BUILDING
SEALAN T, LIMESTONE**

Version	Revision Date:	SDS Number:	Date of last issue: 03/24/2015
3.0	10/10/2015	948592-00003	Date of first issue: 12/12/2014

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/10/2015

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

**DOW CORNING(R) 795 SILICONE BUILDING
SEALANT, LIMESTONE**

Version	Revision Date:	SDS Number:	Date of last issue: 03/24/2015
3.0	10/10/2015	948592-00003	Date of first issue: 12/12/2014

US / Z8