

DuPont™ StraightFlash™

Flashing Protection for Straight Jambs and Heads of Windows and Doors



FEATURES/BENEFITS

Description

DuPont™ StraightFlash™ is an innovative, single-sided, self-adhered flashing solution that bridges the gap between the rough opening and building envelope to protect against water intrusion around heads and jambs of rectangular doors, windows and other gaps. By sealing vulnerable areas around openings, DuPont™ StraightFlash™ can help improve the durability and energy efficiency of both homes and commercial structures.

DuPont™ StraightFlash™ flashing combines a DuPont™ Tyvek® topsheet with a 100% butyl-based adhesive layer, merging the strength, durability and water resistance of Tyvek® material with the convenience and flexibility of a self-adhered flashing. The result: premium door and window flashing protection that keeps rain out and integrates seamlessly with other DuPont™ air and water barriers in a complete building envelope system.

Available Sizes

DuPont™ StraightFlash™ is packaged in ready-to-use 4" x 150' or 9" x 125' rolls in an easy dispensing carton

Ease of Use

- 100% butyl sealant provides excellent adhesion to most common building materials
- Constructed with a tear-resistant, micro-creped DuPont™ Tyvek® top-sheet and specially-designed, quick-release, scored release liner
- Forgiving initial tack provides ability to correct installation mistakes
- Can be installed at external temperatures as low as -4°C (25°F) as long as the surface is clean and free from frost and ice
- Qualified to several key industry-approved standards, including AAMA 711-07 Voluntary Specification for Self-Adhering Flashing Used for Installation of Exterior Wall Fenestration Products
- Does not contain asphaltic / bitumen adhesive materials which many window manufacturers prohibit due to adverse material reactions.
- Withstands up to nine (9) months (270 days) of UV exposure
- Backed by a limited product warranty from DuPont

High Performance Durability

The gap between rough openings for doors and windows is a vulnerable weak point for water penetration into walls. Sealing it with DuPont™ StraightFlash™ helps prevent water intrusion by stopping potential water damage – from rot and corrosion to mold – before it starts, resulting in a more durable wall assembly. And by helping to prevent air and water leakage, DuPont™ StraightFlash™ can also preserve the installed R-Value of insulation, making buildings more energy efficient.

Complete System

DuPont™ StraightFlash™ is compatible with all DuPont™ Tyvek® air and water barriers and other building envelope products.

Sustainable Solutions

When used as part of a DuPont™ Building Envelope system, DuPont™ StraightFlash™ door and window flashing can also help contribute towards U.S. Green Building Council LEED® points.

PROPERTIES

DuPont™ StraightFlash™ exhibits physical properties as indicated in Table 1 when tested as represented. Review all instructions and (Material) Safety Data Sheet ((M)SDS) before use. Please contact DuPont at 1-800-448-9835 when additional guidance is required for writing specifications that include this product.

TABLE 1: Performance Testing for DuPont™ StraightFlash™

| Property | Test Method | Typical Value |
|---|---|--|
| Installed System Water Intrusion Testing | ASTM E-331 | NO leakage at 300 Pa |
| | ASTM-E331 (after thermal aging (0-120°F)) | |
| Water Vapor Permeability | ASTM E-96 | <1 Perm (<60 ng/Pa.sec.m2) |
| Application Temperature | --- | Best when installed above 25°F* |
| Material Standard for Self-Adhering Flashing Surrounding Exterior Wall Fenestration | AAMA 711-13 | Class A (no primer) |
| | | Level 3 Thermal Exposure (80°C/176°F for 7 days) |

* Consult DuPont for primer recommendations



**For more information visit
building.dupont.com
or call 1-866-583-2583**

NOTICE: No freedom from any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries or regions. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DUPONT. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont Specialty Products USA, LLC or its affiliates, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.

CAUTION: This product is combustible. Protect from high heat sources. A protective barrier or thermal barrier may be required as specified in the appropriate building code. For more information, consult (Material) Safety Data Sheet ((M)SDS), call DuPont at 1-866-583-2583 or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada.

WARNING: Rigid foam insulation does not constitute a working walkable surface or qualify as a fall protection product.

Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including DuPont can give assurance that mold will not develop in any specific system.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2019 DuPont.