

Revision Date: 06/29/2016

## SAFETY DATA SHEET

#### 1. Identification

Material name: DIAMOND CLEAR 350 - 5 GAL PAIL

Material: 359DC 05

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

EUCLID CHEMICAL COMPANY 19218 REDWOOD ROAD CLEVELAND OH 44110

US

Contact person:EH&S DepartmentTelephone:216-531-9222

**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

## **Hazard Classification**

## **Physical Hazards**

Flammable liquids Category 2

**Health Hazards** 

Carcinogenicity Category 1B

**Unknown toxicity - Health** 

Acute toxicity, oral 0.15 %
Acute toxicity, dermal 0.15 %
Acute toxicity, inhalation, vapor 99.93 %
Acute toxicity, inhalation, dust or mist 99.15 %

**Environmental Hazards** 

Acute hazards to the aquatic Category 3

environment

**Unknown toxicity - Environment** 

Acute hazards to the aquatic 96.67 %

environment

Chronic hazards to the aquatic 100 %

environment

#### **Label Elements**

#### **Hazard Symbol:**



Revision Date: 06/29/2016



Signal Word: Danger

**Hazard Statement:** Highly flammable liquid and vapor.

May cause cancer. Harmful to aquatic life.

Precautionary Statement: Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Keep container tightly closed. Ground and bond

container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take

precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid

release to the environment.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower. If exposed or concerned: Get medical

advice/attention. In case of fire: Use ... to extinguish.

**Storage:** Store in well-ventilated place. Keep cool. Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and

vapor. May cause flash fire or explosion.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical Identity	CAS number	Content in percent (%)*
One mean reconstruction	OAO Hallibol	Contone in persone (70)
Aromatic petroleum distillates	64742-95-6	3 - 7%
1,2,4-Trimethylbenzene	95-63-6	1 - 5%
Tert-Butyl Acetate	540-88-5	0.1 - 1%
Acetone	67-64-1	0.1 - 1%
Xylene	1330-20-7	0.1 - 1%
Cumene	98-82-8	0.1 - 1%

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Revision Date: 06/29/2016

#### 4. First-aid measures

Ingestion: Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.

**Inhalation:** Move to fresh air.

Skin Contact: Wash skin thoroughly with soap and water. Take off immediately all

contaminated clothing. If skin irritation occurs: Get medical advice/attention.

Eye contact: Any material that contacts the eye should be washed out immediately with

water. If easy to do, remove contact lenses. If eye irritation persists: Get

medical advice/attention.

Most important symptoms/effects, acute and delayed

**Symptoms:** Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

**Treatment:** Symptoms may be delayed.

## 5. Fire-fighting measures

**General Fire Hazards:** Use water spray to keep fire-exposed containers cool. Water may be

ineffective in fighting the fire. Fight fire from a protected location. Move

containers from fire area if you can do so without risk.

#### Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of

vapors or gases to explosive concentrations.

## Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

#### 6. Accidental release measures



Revision Date: 06/29/2016

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.

Methods and material for containment and cleaning

Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

**Notification Procedures:** 

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

**Environmental Precautions:** 

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

## 7. Handling and storage

Precautions for safe handling:

Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities:

Store locked up. Store in a well-ventilated place. Store in a cool place.

#### 8. Exposure controls/personal protection

#### **Control Parameters**

**Occupational Exposure Limits** 

Chemical Identity	type	Exposure Limi	t Values	Source
1,2,4-Trimethylbenzene	TWA	25 ppm		US. ACGIH Threshold Limit Values (2011)
Tert-Butyl Acetate	TWA	200 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	200 ppm	950 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Acetone	TWA	250 ppm		US. ACGIH Threshold Limit Values (03 2015)
	STEL	500 ppm		US. ACGIH Threshold Limit Values (03 2015)
	PEL	1,000 ppm	2,400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)



Revision Date: 06/29/2016

	OTF!	150 ppm	655	US. NIOSH: Pocket Guide to
	STEL	тоо ррпп	mg/m3	Chemical Hazards (2010)
	DEL	100 ppm	435	US. NIOSH: Pocket Guide to
	REL	100 ppili	mg/m3	Chemical Hazards (2010)
	QTE!	150 ppm	655	US. NIOSH: Pocket Guide to
	STEL	. 50 pp///	mg/m3	Chemical Hazards (2010)
	REL	100 ppm	435	US. NIOSH: Pocket Guide to
	NEL	F	mg/m3	Chemical Hazards (2010)
	STEL	150 ppm	655	US. OSHA Table Z-1-A (29 CFR
	SILL		mg/m3	1910.1000) (1989)
	TWA	100 ppm	435	US. OSHA Table Z-1-A (29 CFR
			mg/m3	1910.1000) (1989)
	TWA	100 ppm	435	US. Tennessee. OELs. Occupational
	10070		mg/m3	Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm	655	US. Tennessee. OELs. Occupational
	J. LL		mg/m3	Exposure Limits, Table Z1A (06 2008)
	ST ESL		350 µg/m3	US. Texas. Effects Screening Levels
				(Texas Commission on
				Environmental Quality) (07 2011)
	ST ESL		80 ppb	US. Texas. Effects Screening Levels
				(Texas Commission on
				Environmental Quality) (07 2011)
	AN ESL		42 ppb	US. Texas. Effects Screening Levels
				(Texas Commission on
				Environmental Quality) (07 2011)
	AN ESL		180 µg/m3	US. Texas. Effects Screening Levels
				(Texas Commission on
				Environmental Quality) (07 2011)
	STEL	150 ppm	655	US. California Code of Regulations,
			mg/m3	Title 8, Section 5155. Airborne
		000		Contaminants (08 2010)
	Ceiling	300 ppm		US. California Code of Regulations,
				Title 8, Section 5155. Airborne
		100	425	Contaminants (08 2010)
	TWA	100 ppm	435	US. California Code of Regulations,
	PEL		mg/m3	Title 8, Section 5155. Airborne Contaminants (08 2010)
		100 ppm		US. ACGIH Threshold Limit Values
	TWA	του ρριτι		(2011)
	OTE	150 ppm		US. ACGIH Threshold Limit Values
	STEL	100 ppm		(2011)
	PEL	100 ppm	435	US. OSHA Table Z-1 Limits for Air
	FEL	PP-11	mg/m3	Contaminants (29 CFR 1910.1000)
				(02 2006)
Cumene	TWA	50 ppm		US. ACGIH Threshold Limit Values
		- 1-1		(2011)
	PEL	50 ppm	245	US. OSHA Table Z-1 Limits for Air
			mg/m3	Contaminants (29 CFR 1910.1000)
			Ü	(02 2006)
				1 \/



Revision Date: 06/29/2016

Chemical name	type	Exposure Limit	t Values	Source
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWAEV	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Cumene	STEL	75 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cumene	TWAEV	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Cumene	TWA	50 ppm	246 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

**Biological Limit Values** 

Chemical Identity	Exposure Limit Values	Source
Acetone (acetone: Sampling time: End of shift.)	25 mg/l (Urine)	ACGIH BEI (03 2015)
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)

# Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.



Revision Date: 06/29/2016

#### Individual protection measures, such as personal protective equipment

**General information:** Use explosion-proof ventilation equipment. Good general ventilation

(typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been

established, maintain airborne levels to an acceptable level.

**Eye/face protection:** Wear safety glasses with side shields (or goggles).

**Skin Protection** 

**Hand Protection:** Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing.

**Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. When using do not smoke.

## 9. Physical and chemical properties

**Appearance** 

Physical state: liquid
Form: liquid
Color: Colorless

Odor: Mild petroleum/solvent
Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: > 35 °C > 95 °F

Flash Point: 17 °C 63 °F(Setaflash Closed Cup)

**Evaporation rate:** Slower than Ether

Flammability (solid, gas): No Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

Explosive limit - lower (%):

No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 1.05

Solubility(ies)

Solubility in water: Practically Insoluble
Solubility (other): No data available.



Revision Date: 06/29/2016

Partition coefficient (n-octanol/water):

Auto-ignition temperature:

No data available.

No data available.

No data available.

Viscosity:

No data available.

No data available.

## 10. Stability and reactivity

**Reactivity:** No data available.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

**Conditions to avoid:** Heat, sparks, flames.

Incompatible Materials: Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides

and chromates). Strong bases.

**Hazardous Decomposition** 

**Products:** 

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

## 11. Toxicological information

#### Information on likely routes of exposure

**Ingestion:** May be ingested by accident. Ingestion may cause irritation and malaise.

**Inhalation:** In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

**Skin Contact:** May be harmful in contact with skin. Causes mild skin irritation.

**Eye contact:** Eye contact is possible and should be avoided.

#### Information on toxicological effects

## Acute toxicity (list all possible routes of exposure)

Oral

**Product:** No data available.

Dermal

**Product:** ATEmix: 2,409.54 mg/kg

Inhalation

**Product:** No data available.

Repeated dose toxicity

**Product:** No data available.



Revision Date: 06/29/2016

Skin Corrosion/Irritation

**Product:** No data available.

Specified substance(s):

Aromatic petroleum

distillates

in vivo (Rabbit): Experimental result, Key study

1,2,4-Trimethylbenzene in vivo (Rabbit): Read-across from supporting substance (structural

analogue or surrogate), Key study

Tert-Butyl Acetate in vivo (Rabbit): Experimental result, Key study

Acetone in vivo (Rabbit): Experimental result, Supporting study

Xylene in vivo (Rabbit): Experimental result, Weight of Evidence study

Cumene in vivo (Rabbit): Experimental result, Key study

Serious Eye Damage/Eye Irritation

**Product:** No data available.

Specified substance(s):

Aromatic petroleum

distillates

in vivo (Rabbit, 24 - 72 hrs): Not irritating

1,2,4-Trimethylbenzene in vivo (Rabbit, 30 min): Not irritating

Tert-Butyl Acetate in vivo (Rabbit, 24 hrs): Not irritating

Acetone in vivo (Rabbit, 24 hrs): Minimum grade of severe eye irritant

Xylene in vivo (Rabbit, 24 hrs): Moderately irritating

Cumene in vivo (Rabbit, 24 hrs): Not irritating

Respiratory or Skin Sensitization

**Product:** No data available.

Carcinogenicity

**Product:** May cause cancer. Suspected of causing cancer.



Revision Date: 06/29/2016

## IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Cumene Overall evaluation: Possibly carcinogenic to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens:** 

Cumene Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

**Germ Cell Mutagenicity** 

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** No data available.

**Specific Target Organ Toxicity - Single Exposure** 

**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure** 

**Product:** No data available.

**Aspiration Hazard** 

**Product:** No data available.

Other effects: No data available.

## 12. Ecological information

## **Ecotoxicity:**

## Acute hazards to the aquatic environment:

Fish

**Product:** No data available.

Specified substance(s):

1,2,4-Trimethylbenzene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.19 - 8.28 mg/l

Mortality

Tert-Butyl Acetate LC 50 (Fathead minnow (Pimephales promelas), 96 h): 296 - 362 mg/l

Mortality



Revision Date: 06/29/2016

Acetone LC 50 (Fathead minnow (Pimephales promelas), 96 h): 5,490 - 7,030 mg/l

Mortality

Xylene LC 50 (Bryconamericus iheringii, 96 h): 9.94 mg/l Read-across from

supporting substance (structural analogue or surrogate), Supporting study LC 50 (Oncorhynchus mykiss, 96 h): 8.05 mg/l Read-across from supporting

substance (structural analogue or surrogate), Supporting study LC 50 (Bryconamericus iheringii, 96 h): 6.9 mg/l Read-across from

supporting substance (structural analogue or surrogate), Supporting study LC 50 (Oncorhynchus mykiss, 96 h): 7.6 mg/l Read-across from supporting

substance (structural analogue or surrogate), Supporting study

LC 50 (Oncorhynchus mykiss, 96 h): 2.6 mg/l Read-across from supporting

substance (structural analogue or surrogate), Key study

Cumene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 6.04 - 6.61 mg/l

Mortality

**Aquatic Invertebrates** 

**Product:** No data available.

Specified substance(s):

1,2,4-Trimethylbenzene LC 50 (Scud (Elasmopus pectinicrus), 24 h): 4.89 - 5.62 mg/l Mortality

Tert-Butyl Acetate LC 50 (Water flea (Daphnia magna), 24 h): 4,730 mg/l Mortality

Acetone LC 50 (Water flea (Daphnia magna), 24 h): 10 mg/l Mortality

EC 50 (Water flea (Daphnia magna), 48 h): 21,600 - 23,900 mg/l Intoxication

LC 50 (Scud (Gammarus fasciatus), 96 h): > 100 mg/l Mortality

LC 50 (Asiatic clam (Corbicula manilensis), 96 h): > 20,000 mg/l Mortality

LC 50 (Water flea (Daphnia magna), 96 h): > 100 mg/l Mortality

Xylene EC 50 (Daphnia magna, 48 h): 3.82 mg/l Read-across from supporting

substance (structural analogue or surrogate), Supporting study

EC 50 (Ceriodaphnia dubia, 48 h): > 3.4 mg/l Read-across from supporting

substance (structural analogue or surrogate), Supporting study IC 50 (Daphnia magna, 24 h): 4.7 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study IC 50 (Daphnia magna, 24 h): 3.6 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study IC 50 (Daphnia magna, 24 h): 2.2 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study

Cumene LC 50 (Water flea (Daphnia magna), 24 h): 95 mg/l Mortality

#### Chronic hazards to the aquatic environment:

**Fish** 

**Product:** No data available.

Specified substance(s):

Aromatic petroleum

distillates

EC 50 (Daphnia magna, 21 d): 10 mg/l Other, Key study

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l Experimental result, Key

11/16



Revision Date: 06/29/2016

study

Cumene NOAEL (Danio rerio; Pimephales promelas, 28 d): 0.38 mg/l QSAR QSAR,

Key study

**Aquatic Invertebrates** 

**Product:** No data available.

Specified substance(s):

Xylene NOAEL (Ceriodaphnia dubia, 7 d): 1.17 mg/l Read-across from supporting

substance (structural analogue or surrogate), Key study

NOAEL (Daphnia magna, 21 d): 1.57 mg/l Read-across from supporting

substance (structural analogue or surrogate), Supporting study

LOAEL (Daphnia magna, 21 d): 3.16 mg/l Read-across from supporting

substance (structural analogue or surrogate), Supporting study

EC 10 (Daphnia magna, 21 d): 1.91 mg/l Read-across from supporting

substance (structural analogue or surrogate), Supporting study EC 50 (Daphnia magna, 21 d): 2.9 mg/l Read-across from supporting substance (structural analogue or surrogate), Supporting study

Toxicity to Aquatic Plants

**Product:** No data available.

**Persistence and Degradability** 

Biodegradation

**Product:** No data available.

**BOD/COD Ratio** 

**Product:** No data available.

**Bioaccumulative Potential** 

**Bioconcentration Factor (BCF)** 

**Product:** No data available.

Specified substance(s):

Xylene Oncorhynchus mykiss, Bioconcentration Factor (BCF); > 5.5 - < 12.2 Aguatic

sediment Experimental result, Key study

Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 8.1 - < 25.9 Aquatic

sediment Experimental result, Key study

Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 7.2 - < 24.2 Aquatic

sediment Experimental result, Key study

Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 7.4 - < 18.5 Aquatic

sediment Experimental result, Key study

Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 7.7 - < 21.2 Aquatic

sediment Experimental result, Key study

Partition Coefficient n-octanol / water (log Kow)
Product:
No data available.

Specified substance(s):



Revision Date: 06/29/2016

Tert-Butyl Acetate Log Kow: 1.76

Acetone Log Kow: -0.24

Xylene Log Kow: 3.12 - 3.20

Cumene Log Kow: 3.66

Mobility in Soil: No data available.

Other Adverse Effects: Harmful to aquatic organisms.

## 13. Disposal considerations

**Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

## 14. Transport information

#### TDG:

UN1866, RESIN SOLUTION, 3, PG II

#### CFR / DOT:

UN1866, Resin solution, 3, PG II

#### IMDG:

UN1866, RESIN SOLUTION, 3, PG II

#### **Further Information:**

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

## 15. Regulatory information

## **US Federal Regulations**

## TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.



Revision Date: 06/29/2016

#### CERCLA Hazardous Substance List (40 CFR 302.4):

<b>Chemical Identity</b>	Reportable quantity
Dimethyl carbonate	100 lbs.
Tert-Butyl Acetate	5000 lbs.
Acetone	5000 lbs.
Xylene	100 lbs.
Cumene	5000 lbs.
Methanol	5000 lbs.
Ethylbenzene	1000 lbs.
Tert-Butyl Alcohol	100 lbs.

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

## **Hazard categories**

Fire Hazard

Delayed (Chronic) Health Hazard

## **SARA 302 Extremely Hazardous Substance**

None present or none present in regulated quantities.

## **SARA 304 Emergency Release Notification**

Chemical Identity		l Identity	Reportable quantity	
Dimethyl carbonate		carbonate	100 lbs.	
	Bis	(2-propylheptyl)		
	phthalate	!		
	Tert-Buty	l Acetate	5000 lbs.	
	Acetone		5000 lbs.	
	Vylono		100 lbc	

 Acetone
 5000 lbs.

 Xylene
 100 lbs.

 Cumene
 5000 lbs.

 Methanol
 5000 lbs.

 Ethylbenzene
 1000 lbs.

 Tert-Butyl Alcohol
 100 lbs.

#### SARA 311/312 Hazardous Chemical

Chemical Identity	<b>Threshold Planning Quantity</b>
Aromatic petroleum	500 lbs
distillates	
1,2,4-Trimethylbenzene	500 lbs
Tert-Butyl Acetate	500 lbs
Acetone	500 lbs
Xylene	500 lbs
Cumene	500 lbs

## SARA 313 (TRI Reporting)

## **Chemical Identity**

1,2,4-Trimethylbenzene

## Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

Chemical Identity	Reportable quantity
Xylene	100 lbs.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.



Revision Date: 06/29/2016

## **US State Regulations**

#### **US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

#### US. New Jersey Worker and Community Right-to-Know Act

## **Chemical Identity**

Dimethyl carbonate 1,2,4-Trimethylbenzene

#### **US. Massachusetts RTK - Substance List**

## **Chemical Identity**

Dimethyl carbonate 1,2,4-Trimethylbenzene

## US. Pennsylvania RTK - Hazardous Substances

#### **Chemical Identity**

Dimethyl carbonate 1,2,4-Trimethylbenzene

#### **US. Rhode Island RTK**

## **Chemical Identity**

1,2,4-Trimethylbenzene

## Other Regulations:

Regulatory VOC (less water 320 g/l

and exempt solvent):

**VOC Method 310:** 7.11 %

## **Inventory Status:**

Australia AICS: One or more components in this product are

not listed on or exempt from the Inventory.

Canada DSL Inventory List: All components in this product are listed on or

exempt from the Inventory.

EINECS, ELINCS or NLP:

One or more components in this product are

not listed on or exempt from the Inventory.

Japan (ENCS) List: One or more components in this product are

not listed on or exempt from the Inventory.

China Inv. Existing Chemical Substances:

One or more components in this product are

not listed on or exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI): One or more components in this product are

not listed on or exempt from the Inventory.



Revision Date: 06/29/2016

Canada NDSL Inventory: One or more components in this product are

not listed on or exempt from the Inventory.

Philippines PICCS: One or more components in this product are

not listed on or exempt from the Inventory.

US TSCA Inventory:

All components in this product are listed on or

exempt from the Inventory.

New Zealand Inventory of Chemicals:

One or more components in this product are

not listed on or exempt from the Inventory.

Japan ISHL Listing:

One or more components in this product are

not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are

not listed on or exempt from the Inventory.

## 16.Other information, including date of preparation or last revision

**Revision Date:** 06/29/2016

Version #: 2.0

Further Information: No data available.

**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.