

# Cordless MULTIMASTER AMM 300 Plus Start

## Cordless oscillating multi-tool

The entry-level cordless MultiTool for interior construction and renovation with the basic equipment for sawing in wood, metal, dry wall, and plastics.

Product number: 7 129 32 61 09 0



## Details

- > Anti-vibration: Minimal vibration and outstanding noise dampening means you can work comfortably, for longer.
- > StarlockPlus tool mounting: Work faster and with higher precision thanks to 100% no-loss power transmission.
- > QuickIN: Change accessories in under 3 seconds with a patented, tool-free, FEIN rapid-clamping system.
- > With the StarlockPlus tool mounting, you have access to around 100 FEIN accessories in the Starlock and StarlockPlus performance categories.
- > DC motor: Effective, high-torque motor technology for output that is virtually identical to that of the model with a cord.
- > Variable electronic speed control.
- > Metal drive head: 100% of gearbox components are made from metal providing high load capacity and long service life.
- > SafetyCell technology: Perfect protection from overload, overheating and deep discharge thanks to Li-ion batteries with individual cell monitoring.
- > The battery capacity can be read directly on the battery.

## Price includes

- ✓ 1 E-Cut Long-Life saw blade 1-3/8 in (35 mm) (type 160)
- ✓ 1 universal E-Cut saw blade 1-3/4 in (44 mm) (type 152)
- ✓ 2 Li-ion battery packs (12 V / 3 Ah)
- ✓ 1 E-Cut Long-Life saw blade 2-9/16 in (65 mm) (type 161)
- ✓ 1 rapid charger ALG 80
- ✓ 1 tool case



## Technical data

### TECHNICAL DATA

Battery voltage	12 V
Battery capacity	3 Ah
Battery compatibility	Li-ion
Battery interface	12 V
Oscillations	11,500 - 18,000 opm
Tool mount	StarlockPlus
Tool change	QuickIN
Range	2 x 1,6°
Weight incl. battery	3.31 [1.50] lbs[kg]
Weight without battery	2.65 [1.20] lbs[kg]

### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA  
Measurement uncertainty of the measured value KpA

70 dB  
3 dB

Sound power level LWA  
Measurement uncertainty of the measured value KWA

81 dB  
3 dB

Peak sound value  
LpCpeak  
Measurement uncertainty of the measured value KpCpeak

83 dB  
3 dB

# Application examples

