



Cordless MULTIMASTER AMM 500 Plus Select

Cordless oscillating multi-tool

The high-performance cordless MultiTool for rapid work progress (both interior construction and renovation) in the variant without a battery and charger – with a bi-metal saw blade for wood, metal, and plastics.

Product number: 7 129 33 62 09 0

Details

- > Anti-vibration: Minimal vibration and outstanding noise dampening means you can work comfortably, for longer.
- > StarlockPlus tool mounting: Work faster and with higher precision thanks to 100% no-loss power transmission.
- > QuickIN: Change accessories in under 3 seconds with a patented, tool-free, FEIN rapid-clamping system.
- > With the StarlockPlus tool mounting, you have access to around 100 FEIN accessories in the Starlock and StarlockPlus performance categories.
- > DC motor: Effective, high-torque motor technology for output that is virtually identical to that of the model with a cord.
- > Variable Speed: Constant speed even under load and variable electronic speed control.
- > Metal drive head: 100% of gearbox components are made from metal providing high load capacity and long service life.
- > Mechanical interface: For stationary use in the table or drill jig holders, or to attach depth stops.
- > SafetyCell technology: Perfect protection from overload, overheating and deep discharge thanks to Li-ion batteries with individual cell monitoring.
- > The battery capacity can be read directly on the battery.

Price includes

- ✓ 1 universal E-Cut saw blade 1-3/4 in (44 mm) (type 152)
- ✓ 1 tool case

Product feature

- ✓ Mechanical interconnection

Technical data

TECHNICAL DATA

Battery voltage	18 V
Battery compatibility	Li-ion / HighPower Li-ions
Battery interface	18 V
Oscillations	11,000 - 18,500 opm
Tool mount	StarlockPlus
Tool change	QuickIN
Range	2 x 1,7°
Weight without battery	2.87 [1.30] lbs[kg]

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Measurement uncertainty of the measured value KpA	74 dB 3 dB
Sound power level LWA Measurement uncertainty of the measured value KWA	85 dB 3 dB
Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	87 dB 3 dB

Application examples

