



Cordless MULTIMASTER AMM 500 Plus Top

Cordless oscillating multi-tool

The high-performance cordless MultiTool for rapid work progress (both interior construction and renovation) with over 30 accessories – for sawing in wood and metal, sanding, removing tiles, and more.

Product number: 7 129 33 61 09 0

Details

- > Anti-vibration: Minimal vibration and outstanding noise dampening means you can work comfortably, for longer.
- > StarlockPlus tool mounting: Work faster and with higher precision thanks to 100% no-loss power transmission.
- > QuickIN: Change accessories in under 3 seconds with a patented, tool-free, FEIN rapid-clamping system.
- > With the StarlockPlus tool mounting, you have access to around 100 FEIN accessories in the Starlock and StarlockPlus performance categories.
- > DC motor: Effective, high-torque motor technology for output that is virtually identical to that of the model with a cord.
- > Variable Speed: Constant speed even under load and variable electronic speed control.
- > Metal drive head: 100% of gearbox components are made from metal providing high load capacity and long service life.
- > Mechanical interface: For stationary use in the table or drill jig holders, or to attach depth stops.
- > SafetyCell technology: Perfect protection from overload, overheating and deep discharge thanks to Li-ion batteries with individual cell monitoring.
- > The battery capacity can be read directly on the battery.

Price includes

- ✓ 1 E-Cut Long Life saw blade (10 mm)
- ✓ 2 E-Cut Long Life saw blades (2-9/16 [65] in[mm])
- ✓ 1 HM saw blade (Ø 3 [75] in[mm])
- ✓ 1 rigid scraper blade
- ✓ 20 perforated sanding sheets (5 each of grits 60, 80, 120, 180)
- ✓ 1 rapid charger ALG 80
- ✓ 1 tool case
- ✓ 2 E-Cut Long Life saw blades (1-3/8 [35] in[mm])
- ✓ 1 E-Cut Carbide Pro saw blade (1-1/4 [32] in[mm])
- ✓ 1 carbide rasp (triangular)
- ✓ 1 perforated sanding pad
- ✓ 1 dust extraction device
- ✓ 2 Li-ion battery packs (18 V / 3 Ah)

Product feature

- ✓ Mechanical interconnection



Technical data

TECHNICAL DATA

Battery voltage	18 V
Battery capacity	3 Ah
Battery compatibility	Li-ion / HighPower Li-ions
Battery interface	18 V
Oscillations	11,000 - 18,500 opm
Tool mount	StarlockPlus
Tool change	QuickIN
Range	2 x 1,7°
Weight incl. battery	3.97 [1.80] lbs[kg]
Weight without battery	2.87 [1.30] lbs[kg]

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA
Measurement uncertainty of the measured value KpA

74 dB
3 dB

Sound power level LWA
Measurement uncertainty of the measured value KWA

85 dB
3 dB

Peak sound value
LpCpeak
Measurement uncertainty of the measured value KpCpeak

87 dB
3 dB

Application examples

