



# Cordless MULTIMASTER AMM 700 Max Top

#### Cordless oscillating multi-tool

Our best MultiTool for ultra-rapid work progress for interior construction and renovation with 60 accessories – for sawing in wood, metal, plastics, for removing tiles, cutting silicone caulking and carpeting, and removing residual and tile adhesive.

Product number: 7 129 34 61 09 0

#### Details

- Anti-vibration: Minimal vibration and outstanding noise dampening means you can work comfortably, for longer.
- StarlockMax tool mounting: Work faster and with higher precision thanks to 100% no-loss power transmission.
- > QuickIN: Change accessories in under 3 seconds with a patented, tool-free, FEIN rapidclamping system.
- With the StarlockMax tool mounting, you have access to around 180 FEIN accessories in the Starlock, StarlockPlus and StarlockMax performance categories.
- > 18 V FEIN PowerDrive motor: Especially powerful, virtually wear-free brushless motor

with high efficiency, extremely high load handling and long service life.

- Metal drive head: 100% of gearbox components are made from metal providing high load capacity and long service life.
- > Mechanical interface: For stationary use in the table or drill jig holders, or to attach depth stops.
- SafetyCell technology: Perfect protection from overload, overheating and deep discharge thanks to Li-ion batteries with individual cell monitoring.
- > The battery capacity can be read directly on the battery.



#### Price includes

- 2 E-Cut standard saw blades, curved (1-3/8 [35] in[mm])
- 1 E-Cut Precision saw blade (1-3/8 [35] in[mm])
- 1 E-Cut Long Life saw blade (10 mm)
- 1 E-Cut Long Life saw blade (1-1/4 [32] in[mm])
- 1 E-Cut Carbide Pro saw blade (1-1/4 [32] in[mm])
- 1 carbide segment saw blade
- 1 rigid scraper blade
- 🧹 1 Multi-knife
- ✓ 40 perforated sanding sheets (10 each of grits 60, 80, 120, 180)
- 1 rapid charger ALG 80
- 1 tool case

### Product feature

Mechanical interconnection

- 2 E-Cut standard saw blades, curved (2-1/2 [65] in[mm])
- 1 E-Cut Precision saw blade (2-9/16 [65] in[mm])
- 2 E-Cut Long Life saw blades (1-3/8 [35] in[mm])
- 1 E-Cut Long Life saw blade (1-5/8 [42] in[mm])
- 1 segmented saw blade (Ø 3-3/8
  [85] in[mm])
- 1 carbide rasp (triangular)
- 1 mushroom-shaped cutting blade
- 1 perforated sanding pad
- 1 dust extraction device
- 2 Li-ion battery packs (18 V / 3 Ah)



## Technical data

## TECHNICAL DATA

# VIBRATION AND SOUND EMISSION VALUES

Battery voltage	18 V	Sound pressure level LpA Measurement uncertainty of the measured value KpA	83 dB 3 dB
Battery capacity	3 Ah		
Battery compatibility	Li-ion / HighPower Li- ions	Sound power level LWA Measurement uncertainty of the measured value KWA	94 dB 3 dB
Battery interface	MultiVolt	Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	97 dB
Oscillations	10,000 - 19,500 opm		3 dB
Tool mount	StarlockMax		
Tool change	QuickIN		
Range	2 x 2,0°		
Weight incl. battery	3.53 [1.60] lbs[kg]		
Weight without battery	2.43 [1.10] lbs[kg]		



# Application examples

















