



FEIN



JHM ShortSlugger

Endurance magnetic base drill up to 1-3/16 in [30 mm]

Extremely compact for drilling on the construction site.

Product number: 7 272 51 61 12 4

Details

- > Extremely compact with ideal power to weight ratio for work at heights and in confined spaces.
- > Hand feed wheel mounts on either side for use in special situations.
- > Internal motor cable routing prevents unintended threading or hanging up on the workpiece.
- > Internal cooling.
- > Easy guide readjustment.
- > Smart magnet circuitry will not allow motor to start without sufficient magnetic force.

Price includes

- ✓ 1 case
- ✓ 1 coolant tank
- ✓ 1 safety strap
- ✓ 1 chip hook
- ✓ 4 pilot pins
- ✓ 1 allen key 5 mm
- ✓ 1 chip guard

Product feature

- ✓ Hand feed wheel can be mounted on either side



Application

Use of HSS cutters



Carbide-tipped cutter use



Mag base drilling metal up to 1-3/8 in dia.



Performing overhead work



Installation work



Workshop jobs



- ★ suitable
- ★★ well suitable



Technical data

TECHNICAL DATA

Power consumption	750 W
Power output	430 W
Full load speed	430 rpm
No load speed	680 rpm
HSS cutter max. dia.	1-1/8 [30] in[mm]
Cutter max. drilling depth	2 [50] in[mm]
Cutter holder	3/4 in straight shank
Stroke	2-9/16 [65] in[mm]
Magnetic holding force	1798 [8,000] lbs[N]
Magnetic base dimensions	7 [178] x 3 [76] in[mm]
Cable with plug	12.5 [3.8] ft[m]
Weight	22.05 [10.00] lbs[kg]