



MULTIMASTER MM 500 Plus Top

Oscillating MultiTools - MM 500

The high-performance MultiTool for quick work progress (both interior construction and renovation) with over 30 accessories for sawing in wood and metal, sanding, removing tiles, and more.

Product number: 7 229 67 61 09 0

Details

- > Anti-vibration: Minimal vibration and outstanding noise dampening means you can work comfortably, for longer.
- > StarlockPlus tool mounting: Work faster and with higher precision thanks to 100% no-loss power transmission.
- > QuickIN: Change accessories in under 3 seconds with a patented, tool-free, FEIN rapid-clamping system.
- > With the StarlockPlus tool mounting, you have access to around 100 FEIN accessories in the Starlock and StarlockPlus performance categories.
- > 350 W FEIN motor: Overload-protected, high-performance motor with high proportion of copper for higher cutting speed and rapid work progress.
- > Variable Speed: Constant speed even under load and variable electronic speed control.
- > Metal drive head: 100% of gearbox components are made from metal providing high load capacity and long service life.
- > Mechanical interface: For stationary use in the table or drill jig holders, or to attach depth stops.
- > Industrial-strength cable: The 16 ft (5m) rubber-clad, industrial-quality cord gives you room to work.

Price includes

- ✓ 1 E-Cut Long Life saw blade (10 mm)
- ✓ 2 E-Cut Long Life saw blades (2-9/16 [65] in[mm])
- ✓ 1 HM saw blade (Ø 3 [75] in[mm])
- ✓ 1 rigid scraper blade
- ✓ 20 perforated sanding sheets (5 each of grits 60, 80, 120, 180)
- ✓ 1 tool case
- ✓ 2 E-Cut Long Life saw blades (1-3/8 [35] in[mm])
- ✓ 1 E-Cut Carbide Pro saw blade (1-1/4 [32] in[mm])
- ✓ 1 carbide rasp (triangular)
- ✓ 1 perforated sanding pad
- ✓ 1 dust extraction device

Product feature

- ✓ Mechanical interconnection

Technical data

TECHNICAL DATA

Power consumption	350 W
Oscillations	10,000 - 19,500 opm
Tool mount	StarlockPlus
Tool change	QuickIN
Range	2 x 1,7°
Cable with plug	16.4 [5] ft[m]
Weight	3.09 [1.40] lbs[kg]

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Measurement uncertainty of the measured value KpA	72 dB 3 dB
Sound power level LWA Measurement uncertainty of the measured value KWA	83 dB 3 dB
Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	84 dB 3 dB

Application examples

