



# MULTIMASTER MM 700 1.7 Q Autoglas

## Oscillating MultiTools - MM 700

Our best oscillating MultiMaster for the automotive sector incl. extensive accessories for removing windshields and working on car bodies.

Product number: 7 229 70 62 09 0

### Details

- Anti-vibration: Minimal vibration and outstanding noise dampening means you can work comfortably, for longer.
- QuickIN: Change accessories in under 3 seconds with a patented, tool-free, FEIN rapid-clamping system.
- Hexagonal accessory mount for optimal torque transfer.
- 450 W FEIN high-performance motor: Durable, overload-protected, high-performance motor
- with high proportion of copper for higher cutting speed and ultra-rapid work progress.
- Variable Speed: Constant speed even under load and variable electronic speed control.
- Metal drive head: 100% of gearbox components are made from metal providing high load capacity and long service life.
- Industrial-strength cable: The 16 ft (5m) rubber-clad, industrial-quality cord gives you room to work.

### Price includes

- ✓ 3 L-shaped cutting blades, serrated (type 207)
- ✓ 1 L-shaped cutting blade, serrated (type 209)
- ✓ 2 U-shaped cutting blades, reinforced model, serrated (type 212)
- ✓ 1 straight cutting blade, offset, serrated (type 081)
- ✓ 1 whetstone (6 37 19 010 01 4)
- ✓ 2 L-shaped cutting blades, toothed (type 208)
- ✓ 2 U-shaped cutting blades, reinforced model (types 157 and 111)
- ✓ 1 straight cutting blade, offset, with adjustable roller stop (type 143)
- ✓ 1 protective cover for accessory changes
- ✓ 1 tool case

## Technical data

### TECHNICAL DATA

Power consumption	450 W
Power output	250 W
Oscillations	10,000 - 19,500 opm
Tool mount	Hexagon
Tool change	QuickIN
Range	2 x 1,7°
Cable with plug	16.4 [5] ft[m]
Weight	3.64 [1.65] lbs[kg]

### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA  
Measurement uncertainty of the measured value KpA

85 dB  
3 dB

Sound power level LWA  
Measurement uncertainty of the measured value KWA

96 dB  
3 dB

Peak sound value  
LpCpeak  
Measurement uncertainty of the measured value KpCpeak

97 dB  
3 dB

## Application examples

