



Turbo X

Wet/Dry Dust Extractor

Powerful, dust class L, professional wet / dry vacuum cleaner, for attachment of various case systems, includes extensive accessories.

Product number: 9 20 29 060 09 0

Details

- › Tool cases from various systems can be placed on the vacuum lid and secured.
- › Ergonomic transport of the complete unit, consisting of part tool and vacuum, thanks to push handle, case and accessory fastening.
- › Reliable vacuuming of all types of dirt from liquids to fine dusts.
- › Approval for dust class L.
- › With PES flat pleated filter and electronic shutdown for outstanding wet vacuuming performance.
- › Autostart outlet with power-on delay to prevent current spikes.
- › Infinitely variable suction regulation at vacuum.
- › 25 ft [7.5 m] power cable and 13 ft [4 m] suction hose provide a large operating radius.
- › Anti-static function against electrostatic charging during work – electrostatically conductive with optionally available suction hose 3 13 45 120 01 0.

Price includes

- ✓ 1 push handle
- ✓ 1 non-woven filter bag, premium
- ✓ 1 tool coupling with suction control
- ✓ 2 metal extension tubes, 1 combination tool with interchangeable inserts, , 1 crevice nozzle, 1 dusting brush, 1 elbow
- ✓ 1 flat pleated filter PES
- ✓ 1 suction hose 13 ft [4 m], 1-3/8 in [35 mm] dia.
- ✓ 1 step adapter

Product feature

- ✓ Automatic on/off
- ✓ Anti-static preparation
- ✓ Case storage
- ✓ Soft-start
- ✓ Anti-static function
- ✓ Dust class

Technical data

TECHNICAL DATA

Maximum power input	1,100 W
Suction capacity	153 [4,320] cfm[l/min]
Static water lift	98 [245] psi[bar]
Capacity	9.2 [35] gal[l]
Cable with plug	24.6 [7.5] ft[m]
Sound pressure level	70 dB
Weight	29.76 [13.50] lbs[kg]

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Measurement uncertainty of the measured value KpA	67,0 dB 3 dB
Sound power level LWA Measurement uncertainty of the measured value KWA	81,0 dB 3 dB
Vibration value 1 α_{hv} 3-way	<2,5 m/s ²
Vibration value 2 α_{hv} 3-way	1,5 m/s ²

Application examples

