



Printing date 10/28/2016 Version Number 1.0 Reviewed on 10/28/2016

1 Identification

Product identifier

Trade name: Bituthene Liquid Membrane Part A

SDS ID Number: 60025

Relevant identified uses of the substance or mixture, and uses advised against

Specialty construction product. Not intended for other uses

Details of the supplier of the safety data sheet

Manufacturer/Supplier: GCP Applied Technologies

62 Whittemore Avenue Cambridge, MA 02140 USA

GCP Canada, Inc. 294 Clements Road W. Ajax, Ontario L1S 3C6 Canada

Information department:

Environmental Health & Safety USA: +1-617-876-1400 (24 hours)

+1-800-354-5414 (8AM - 5PM) Not functional within Massachusetts

CAN: 1-905-683-8561 (24 hours) Email address: msds.gcp@gcpat.com

Transport Emergency: Chemtrec +1-800-424-9300 (24 hours)

2 Hazard(s) identification

Classification of the substance or mixture

May cause cancer.

Label elements: The product is classified and labeled according to the Globally Harmonized System (GHS)

Hazard pictograms



Danger

Hazard statements

May cause cancer.

Precautionary statements

Wear protective gloves/protective clothing/eye protection/face protection.

Do not handle until all safety precautions have been read and understood.

Obtain special instructions before use.

IF exposed or concerned: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

NFPA ratings (scale 0 - 4)



Health = 2 Fire = 1 Reactivity = 1

(Cont. on page 2)

(Cont. from page 1)

Printing date 10/28/2016 Version Number 1.0 Reviewed on 10/28/2016

Trade name: Bituthene Liquid Membrane Part A

HMIS-ratings (scale 0 - 4)

HEALTH *2
FIRE 1 Health = *2
Flammability = 1
REACTIVITY 1 Reactivity = 1

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixture

Description: Mixture of the hazardous substance(s) listed below with additional nonhazardous ingredients.

	Hazardous components:			
ſ	8052-42-4	Asphalt	20-25%	
	64742-04-7	Extracts (petroleum), heavy paraffinic distillate solvent	10-20%	
Ī	130498-29-2	Polycyclic Aromatic Hydrocarbons	0.1-0.3%	

Additional information: Non-hazardous ingredients may be listed in Section 15; Right-To-Know disclosure.

4 First-aid measures

Description of first aid measures

General information:

Get medical advice/attention if you feel unwell.

After inhalation:

If symptoms develop, supply fresh air. If required, provide artificial respiration and seek immediate medical treatment.

After skin contact:

Immediately wash contaminated skin with soap or mild detergent and water. If this chemical soaks clothing, immediately remove clothing and wash skin.

If residue remains, clean with waterless handcream or abrasive soap. Never use solvents.

After eve contact:

If contact with residue causes eye irritation, flush eyes with water for at least 15 minutes while holding eyelids open.

After swallowing: Do not induce vomiting; immediately call for medical help.

Information for doctor:

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.

Special hazards arising from the substance or mixture No further relevant information available.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

USGHS =

Printing date 10/28/2016 Version Number 1.0 Reviewed on 10/28/2016

Trade name: Bituthene Liquid Membrane Part A

(Cont. from page 2)

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Do not allow product to reach sewage system or any water course.

Methods and material for containment and cleaning up:

Contain and/or absorb spill with inert material (i.e. sand, vermiculite) then place in a suitable container.

Sweep up spilled product into receptacles.

Pick up mechanically.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling

Open and handle receptacle with care.

Prevent formation of aerosols.

Avoid contact with skin and eyes.

Information about protection against explosions and fires: No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Information about storage in one common storage facility: No special measures required.

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Components with limit values that require monitoring at the workplace:

8052-42-4 Asphalt

REL (USA) Ceiling limit value: 5* mg/m³

*15-min; See Pocket Guide App. A

TLV (USA) Long-term value: 0.5* mg/m³

*inh. fraction; as benzene-soluble aerosol; BEIp

Ingredients with biological limit values:

8052-42-4 Asphalt

BEI (USA)

Medium: urine

Time: end of shift at end of workweek

Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)

130498-29-2 Polycyclic Aromatic Hydrocarbons

BEI (USA) Medium: urine

Time: end of shift at end of workweek

Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)

Additional information: The lists that were valid during the creation were used as basis.

(Cont. on page 4)

Printing date 10/28/2016 Version Number 1.0 Reviewed on 10/28/2016

Trade name: Bituthene Liquid Membrane Part A

(Cont. from page 3)

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Store protective clothing separately.

Breathing equipment:

Control exposure to ingredients with workplace control parameters if mentioned above. If no ingredients are listed, respiratory protection is generally not required.

If exposure limits are listed and may be exceeded, use approved respiratory protective equipment and filter type appropriate for the listed ingredients. (NIOSH, CEN, etc.).

Protection of hands: Gloves should be worn to prevent skin contact and should be impermeable and resistant to the product.

Material of gloves Gloves should be worn to prevent skin contact and should be impermeable and resistant to the product.

Eye protection:



Safety glasses with side shield protection.



A face shield should also be worn if there is potential exposure to splash or spray.

Body protection:

Use personal protective equipment as required.

Take off contaminated clothing.

9 Physica	I and chemica	i properties

9 Fifysical and chemical proper	tysical and chemical properties	
Information on basic physical	l and chemical properties	
General Information Appearance: Form: Color: Odor: Odor threshold:	Liquid According to product specification Characteristic Not determined.	
pH-value (~):	Not determined.	
Change in condition Melting point/Melting range: Boiling point/Boiling range: Flash point:	Undetermined. Undetermined. 200 °C (392 °F)	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature: Auto igniting: Danger of explosion:	Not determined. Product is not selfigniting. Product does not present an explosion hazard.	
Explosion limits: Lower: Upper: VOC Content (max):	Not determined. Not determined. Not determined.	
Vapor pressure: Density: (~) at 20 °C (68 °F) Relative density Vapor density Evaporation rate	Not determined. 1.1 g/cm³ (9.18 lbs/gal) Not determined. Not determined. Not determined. Not determined.	

(Cont. on page 5) - USGHS

Version Number 1.0 Printing date 10/28/2016 Reviewed on 10/28/2016

Trade name: Bituthene Liquid Membrane Part A

		(Cont. from page 4)
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wate	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Molecular weight	Not applicable.	
Other information	No further relevant information available.	

10 Stability and reactivity

Reactivity Stable under normal conditions.

Chemical stability

Thermal decomposition: No decomposition if used according to specifications.

Possibility of hazardous reactions No further relevant information available.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Other potentially hazardous products may also be formed.

Additional information: See section 7 for information on handling, storage and conditions to be avoided.

11 Toxicological information

Information on toxicological effects

Acute toxicity:

Primary irritant effect:

on the skin: No irritating effect expected on the eye: No irritating effect expected inhalation: No irritating effect expected

Additional toxicological information: May cause cancer.

Carcinogenic categories

IARC (International Agency for Research on Cancer) Human Carcinogenicity: Group 1- Positive, Group 2A- Probable, Group 2B- Possible, Group 3- Not Classifiable			
69012-64-2	Silica, fume	3	
8052-42-4	Asphalt	2B	
64742-04-7	Extracts (petroleum), heavy paraffinic distillate solvent	1	
130498-29-2	Polycyclic Aromatic Hydrocarbons	2A	
NTP (Nation	nal Toxicology Program)		

K-Known to be carcinogenic, R-May reasonably be anticipated to be carcinogenic

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

USGHS •

Printing date 10/28/2016 Version Number 1.0 Reviewed on 10/28/2016

Trade name: Bituthene Liquid Membrane Part A

(Cont. from page 5)

12 Ecological information

Toxicity

Aquatic toxicity:

64742-04-7 Extracts (petroleum), heavy paraffinic distillate solvent

LC/EC/IC50 (static) 18.8 mg/l (algae) (OECD guideline 201)

Persistence and degradability No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Not known to be hazardous to water.

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods Comply with Federal, State and local regulations.

Recommendation:



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

*	14 Transport information		
	UN-Number	-	<u> </u>
	DOT, IMDG, IATA	Not applicable.	

Not applicable.

UN proper shipping name DOT, IMDG, IATA Transport hazard class(es)

DOT, IMDG, IATA

Class Not applicable.

Packing group

DOT, IMDG, IATA Not applicable.

Environmental hazards:

Marine pollutant: No

Special precautions for user Not applicable.

Transport/Additional information: Not classified as a dangerous good for transport by road, rail or air.

DOT

Remarks: Not Regulated.

(Cont. on page 7)

Printing date 10/28/2016 Version Number 1.0 Reviewed on 10/28/2016

Trade name: Bituthene Liquid Membrane Part A

(Cont. from page 6)

UN "Model Regulation": Not applicable.

15 Regulatory information

SARA (Superfund Amendments and Reauthorization Act)

Section 302/304 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 Reportable Ingredients (Chemicals present below reporting threshold are exempt):

None of the ingredients is listed.

SARA Section 312/Tier I & II Hazard Categories: Health Hazard - Carcinogenicity

North America Chemical Inventory Status

TSCA (Toxic Substances Control Act - United States):

All ingredients are listed or exempt from listing unless otherwise noted below.

CEPA (Canadian DSL):

All ingredients are listed or exempt from listing unless otherwise noted below.

Right to Know Ingredient Disclosure:

69012-64-2 Silica, fume

69102-90-5 1,3-Butadiene, homopolymer, hydroxy-terminated

25791-96-2 Glycerol, propylene oxide polymer

8001-78-3 Castor oil, hydrogenated

1332-58-7 Natural aluminosilicate (Kaolin)

California Proposition 65

Chemicals known to cause cancer:

Extracts (petroleum), heavy paraffinic distillate solvent

Polycyclic Aromatic Hydrocarbons

Quartz (SiO2)

4-vinylcyclohexene

1,3-Butadiene

Chemicals known to cause reproductive toxicity for females:

100-40-3 4-vinylcyclohexene

106-99-0 1,3-Butadiene

Chemicals known to cause reproductive toxicity for males:

106-99-0 1,3-Butadiene

Chemicals known to cause developmental toxicity:

106-99-0 1,3-Butadiene

Carcinogenicity Categories

EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV-ACGIH (THE American Conference of Governmental Industrial Hygienists)

Human Carcinogen - A1 Confirmed, A2 Suspected, A3 Unknown Relevance, A4 Not Classifiable

Asphalt A4
Natural aluminosilicate (Kaolin) A4

NIOSH-Cancer (National Institute for Occupational Safety and Health)

8052-42-4 Asphalt

Volatile Organic Compounds (VOC) reported per the Emission Standards. (gr/L) 10 gr/L (as applied)

16 Other information

The data included herein are presented in accordance with various environment, health and safety regulations. It is the responsibility of a recipient of the data to remain currently informed on chemical hazard information, to design and update its own program and to comply with all national, federal, state and local laws and regulations applicable to safety, occupational health, right-to-know and environmental protection.

(Cont. on page 8)

Printing date 10/28/2016 Version Number 1.0 Reviewed on 10/28/2016

Trade name: Bituthene Liquid Membrane Part A

(Cont. from page 7)

Department issuing SDS: GCP Applied Technologies

GCP Applied Technologies 62 Whittemore Avenue Cambridge, MA 02140 USA USA: +1-617-876-1400 (24 hours) +1-800-354-5414

Other Information:

There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis. Therefore preventing the onset of silicosis will also reduce the cancer risk.

Date of preparation / last revision 10/28/2016 / -

The first date of preparation 03/03/2015

Number of revision times and the latest revision date 1.0 / 10/28/2016

USGHS •





Printing date 10/31/2016 Version Number 1.2 Reviewed on 10/31/2016

1 Identification

Product identifier

Trade name: Bituthene Liquid Membrane & Deck Prep Part B

SDS ID Number: 583

Relevant identified uses of the substance or mixture, and uses advised against

Specialty construction product. Not intended for other uses

Details of the supplier of the safety data sheet

Manufacturer/Supplier:GCP Applied Technologies
62 Whittemore Avenue

Cambridge, MA 02140 USA

GCP Canada, Inc. 294 Clements Road W. Ajax, Ontario L1S 3C6 Canada

Information department:

Environmental Health & Safety USA: +1-617-876-1400 (24 hours)

+1-800-354-5414 (8AM - 5PM) Not functional within Massachusetts

CAN: 1-905-683-8561 (24 hours) Email address: msds.gcp@gcpat.com

Transport Emergency: Chemtrec +1-800-424-9300 (24 hours)

2 Hazard(s) identification

Classification of the substance or mixture

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties

if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

Label elements: The product is classified and labeled according to the Globally Harmonized System (GHS)

Hazard pictograms





GHS07 GHS08

Danger

Hazard statements

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause respiratory irritation.

(Cont. on page 2)

Version Number 1.2 Printing date 10/31/2016 Reviewed on 10/31/2016

Trade name: Bituthene Liquid Membrane & Deck Prep Part B

(Cont. from page 1)

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

[In case of inadequate ventilation] wear respiratory protection.

Wear eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

IF ON SKIN: Wash with plenty of water.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

NFPA ratings (scale 0 - 4)



Health = 2Fire = 1Reactivity = 1

HMIS-ratings (scale 0 - 4)



Health = *2Flammability = 1

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixture

Description: Mixture of the hazardous substance(s) listed below with additional nonhazardous ingredients.

Hazardous components:			
26447-40-5	Methylenediphenyl diisocyanate, mixture of isomers	30-50%	
101-68-8	Diphenylmethane-4,4'-di-isocyanate	30-50%	
61788-32-7	Terphenyl plasticiser, hydrogenated	10-20%	
78-40-0	Triethylphosphate	1.0-3.0%	

Additional information: Non-hazardous ingredients may be listed in Section 15; Right-To-Know disclosure.

4 First-aid measures

Description of first aid measures

General information: Get medical advice/attention if you feel unwell.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Immediately wash contaminated skin with soap or mild detergent and water. If this chemical soaks clothing, immediately remove clothing and wash skin.

After eye contact:

Rinse opened eye for several minutes under running water.

Seek immediate medical advice.

After swallowing:

Rinse mouth.

Never give anything by mouth to an unconscious person.

Do not induce vomiting; immediately call for medical help.

(Cont. on page 3)

Version Number 1.2 Printing date 10/31/2016 Reviewed on 10/31/2016

Trade name: Bituthene Liquid Membrane & Deck Prep Part B

(Cont. from page 2)

Information for doctor:

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

Special hazards arising from the substance or mixture No further relevant information available.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Methods and material for containment and cleaning up:

Contain and/or absorb spill with inert material (i.e. sand, vermiculite) then place in a suitable container.

Sweep up spilled product into receptacles.

Dispose contaminated material as waste according to section 13 of the SDS.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling

Open and handle receptacle with care.

Prevent formation of aerosols.

Avoid contact with skin.

Avoid contact with eyes.

Information about protection against explosions and fires: No special measures required.

Conditions for safe storage, including any incompatibilities

Information about storage in one common storage facility: No special measures required.

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

(Cont. on page 4)

Version Number 1.2 Printing date 10/31/2016 Reviewed on 10/31/2016

Trade name: Bituthene Liquid Membrane & Deck Prep Part B

(Cont. from page 3)

Control pai	rameters
Components	with limit values that require monitoring at the workplace:
101-68-8 Dipl	nenylmethane-4,4'-di-isocyanate
PEL (USA)	Ceiling limit value: 0.2 mg/m³, 0.02 ppm
REL (USA)	Long-term value: 0.05 mg/m³, 0.005 ppm Ceiling limit value: 0.2* mg/m³, 0.02* ppm *10-min
TLV (USA)	Long-term value: 0.051 mg/m³, 0.005 ppm
61788-32-7 To	erphenyl plasticiser, hydrogenated
REL (USA)	Long-term value: 5 mg/m³, 0.5 ppm
TLV (USA)	Long-term value: 4.9 mg/m³, 0.5 ppm nonirradiated
78-40-0 Trietl	hylphosphate
WEEL (USA)	Long-term value: 7.45 mg/m ³

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Avoid contact with the eyes and skin.

The usual precautionary measures for handling chemicals should be followed.

Breathing equipment:

Control exposure to ingredients with workplace control parameters if mentioned above. If no ingredients are listed, respiratory protection is generally not required.

If exposure limits are listed and may be exceeded, use approved respiratory protective equipment and filter type appropriate for the listed ingredients. (NIOSH, CEN, etc.).

Protection of hands: Gloves should be worn to prevent skin contact and should be impermeable and resistant to the product.

Material of gloves Gloves should be worn to prevent skin contact and should be impermeable and resistant to the product.

Eye protection:



Safety glasses with side shield protection.

Safety glasses with side shields should be worn to prevent contact due to splashing. Under high vapor mist concentrations, tightly sealed goggles should be worn.



A face shield should also be worn if there is potential exposure to splash or spray.

Body protection:

Protective work clothing

Use personal protective equipment as required.

Take off contaminated clothing.

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form: Liquid

Color: According to product specification

Odor: Characteristic

(Cont. on page 5)

Printing date 10/31/2016 Version Number 1.2 Reviewed on 10/31/2016

Trade name: Bituthene Liquid Membrane & Deck Prep Part B

	(Cont. from page 4)
Odor threshold:	Not determined.
pH-value (~):	Not determined.
Change in condition Melting point/Melting range: Boiling point/Boiling range: Flash point:	Undetermined. 208 °C (406 °F) 212 °C (414 °F)
Flammability (solid, gaseous):	Not applicable.
Decomposition temperature: Auto igniting: Danger of explosion:	Not determined. Product is not selfigniting. Product does not present an explosion hazard.
Explosion limits: Lower: Upper: VOC Content (max):	Not determined. Not determined. Not determined.
Vapor pressure: Density: (~) Relative density Vapor density Evaporation rate	Not determined. Not determined. Not determined. Not determined. Not determined. Not determined.
Solubility in / Miscibility with Water:	Not miscible or difficult to mix. Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	r): Not determined.
Viscosity: Dynamic: Kinematic: Molecular weight	Not determined. Not determined. Not applicable.
Other information	These are typical values and do not constitute a specification.

10 Stability and reactivity

Reactivity Stable under normal conditions.

Chemical stability

Thermal decomposition: No decomposition if used according to specifications.

Possibility of hazardous reactions No further relevant information available.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products:

Carbon monoxide and carbon dioxide

(possible HCN)

Other potentially hazardous products may also be formed.

Additional information: See section 7 for information on handling, storage and conditions to be avoided.

11 Toxicological information

Delayed and immediate effects and chronic effects from short or long term exposure

May cause damage to organs through prolonged or repeated exposure.

(Cont. on page 6)

Printing date 10/31/2016 Version Number 1.2 Reviewed on 10/31/2016

Trade name: Bituthene Liquid Membrane & Deck Prep Part B

(Cont. from page 5)

Information on toxicological effects

Acute toxicity:

LI	D/LC50	values rele	evant for classification:
10	1-68-8 D	Diphenylm	ethane-4,4'-di-isocyanate
Or	ral	LD50	> 10000 mg/kg (rat)
De	ermal	LD50	> 9400 mg/kg (rabbit)
Inh	halation	LC50, 4h	0.49 mg/l (rat)

Primary irritant effect:

on the skin: Causes skin irritation.

on the eye: Causes serious eye irritation.

inhalation:

Harmful if inhaled.
Causes damage to organs.
May cause respiratory irritation.

Ingestion: May cause damage to organs through prolonged or repeated exposure.

Sensitization:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Additional toxicological information: Suspected of causing cancer.

Carcinogenic categories

IARC (International Agency for Research on Cancer) Human Carcinogenicity:

Group 1- Positive, Group 2A- Probable, Group 2B- Possible, Group 3- Not Classifiable

101-68-8 Diphenylmethane-4,4'-di-isocyanate

3

NTP (National Toxicology Program)

K-Known to be carcinogenic, K-May reasonably be anticipated to be carcinogenic

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

Other adverse effects No further relevant information available.

• USGHS

Printing date 10/31/2016 Version Number 1.2 Reviewed on 10/31/2016

Trade name: Bituthene Liquid Membrane & Deck Prep Part B

(Cont. from page 6)

13 Disposal considerations

Waste treatment methods

Recommendation:



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

Transport information	
UN-Number DOT, IMDG, IATA	Not applicable.
UN proper shipping name DOT, IMDG, IATA	Not applicable.
Transport hazard class(es)	
DOT, IMDG, IATA Class	Not applicable.
Packing group DOT, IMDG, IATA	Not applicable.
Environmental hazards: Marine pollutant:	No
Special precautions for user	Not applicable.
Transport/Additional informati	ion: Not classified as a dangerous good for transport by road, rail or air.
DOT Remarks:	Not Regulated.
UN "Model Regulation":	Not applicable.

15 Regulatory information

SARA (Superfund Amendments and Reauthorization Act)

Section 302/304 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 Reportable Ingredients (Chemicals present below reporting threshold are exempt):

101-68-8 Diphenylmethane-4,4'-di-isocyanate

30.9%

SARA Section 312/Tier I & II Hazard Categories:

Health Hazard - Carcinogenicity

Health Hazard - Acute toxicity (any route of exposure)

Health Hazard - Skin Corrosion or Irritation

Health Hazard - Respiratory or Skin Sensitization

Health Hazard - Serious eye damage or eye irritation

Health Hazard - Specific target organ toxicity (single or repeated exposure)

North America Chemical Inventory Status

TSCA (Toxic Substances Control Act - United States):

All ingredients are listed or exempt from listing unless otherwise noted below.

CEPA (Canadian DSL):

All ingredients are listed or exempt from listing unless otherwise noted below.

Right to Know Ingredient Disclosure:

39310-05-9 Methylenebis(isocyanatobenzene) polymer

(Cont. on page 8)

Printing date 10/31/2016 Version Number 1.2 Reviewed on 10/31/2016

Trade name: Bituthene Liquid Membrane & Deck Prep Part B

68956-74-1 Quaterphenyls 26140-60-3 Terphenyl plasticiser unhydrogenated California Proposition 65 Chemicals known to cause cancer: None of the ingredients is listed. Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. Chemicals known to cause developmental toxicity: None of the ingredients is listed. **Carcinogenicity Categories EPA** (Environmental Protection Agency) 101-68-8 Diphenylmethane-4,4'-di-isocyanate D, CBD TLV-ACGIH (THE American Conference of Governmental Industrial Hygienists) Human Carcinogen - A1 Confirmed, A2 Suspected, A3 Unknown Relevance, A4 Not Classifiable None of the ingredients is listed.

16 Other information

The data included herein are presented in accordance with various environment, health and safety regulations. It is the responsibility of a recipient of the data to remain currently informed on chemical hazard information, to design and update its own program and to comply with all national, federal, state and local laws and regulations applicable to safety, occupational health, right-to-know and environmental protection.

Department issuing SDS:

None of the ingredients is listed.

GCP Applied Technologies 62 Whittemore Avenue Cambridge, MA 02140 USA USA: +1-617-876-1400 (24 hours)

+1-800-354-5414

Date of preparation / last revision 10/31/2016 / 1.1

The first date of preparation 08/03/2006

Number of revision times and the latest revision date 1.2 / 10/31/2016

NIOSH-Cancer (National Institute for Occupational Safety and Health)

Volatile Organic Compounds (VOC) reported per the Emission Standards. (gr/L)

■ USGHS

10 gr/L (as applied)