

# Accu-Lube® LB-4600

## Light Viscosity MQL

### FEATURES

- Economical, light-duty minimum quantity lubricant
- Light-duty machining, sawing and cutting
- Aluminum extrusion machining and sawing
- Vegetable-based, biodegradable lubricant
- Non-staining, burns off cleanly in post heat treating
- For ferrous & nonferrous metals, aluminum and titanium
- Clean with soap and water

### APPLICATIONS

- Light-duty machining, sawing and cutting
- Aluminum extrusion machining and sawing

### DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

### HANDLING

None required under normal usage.

### STORAGE

Keep containers tightly closed in a dry, cool and well-ventilated place.

### DISPOSAL

Consult the appropriate state, regional, or local regulations for additional requirements.



### PHYSICAL PROPERTIES

Appearance / Physical State	Liquid
Odor	Mild
Melting / Freezing Point	No data available
Boiling Point / Range	>150°C
Vapor Pressure	No data available
Partition Coefficient	No data available
Percent volatile	No data available
Flammability	No data available
Propellant	N/A
VOC Content	5.91 g/l
Color	Purple
Flash Point	>150°C
Density	No data available
Evaporation Rate	No data available
Vapor density	No data available
Auto-Ignition Temperature	No data available
Viscosity	No data available
Specific Gravity	0.86
Temperature Range	No data available
4-Ball Weld Load	No data available

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
LB4600	1 gal	jug	4	34 lbs
LB4655	55 gal	drum	1	454 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved