## **Rustlick**

## **TECHNICAL DATA SHEET**

## **ULTRACUT Pro CF**

Bioresistant, chlorine free water-soluble oil metalworking fluid concentrate

**DESCRIPTION** 

ULTRACUT Pro CF is a premium chlorine free water-soluble oil cutting & grinding fluid with maximum bioresistance and non-chlorinated extreme-pressure additives for heavyduty machining with ferrous & nonferrous metals.

**APPLICATION** 

Moderate to heavy-duty machining and grinding

**ADVANTAGES** 

- Extremely resistant to bacteria and fungus
- Exceptionally long sump life
- Outstanding corrosion protection
- Great workpiece quality
- Dramatically extends tool life
- Increased productivity

**MATERIAL COMPATIBILITY** 

Recommended for ferrous/nonferrous metals, aluminum, titanium, brass, bronze and copper.

PHYSICAL PROPERTIES

Concentrate Color	Golden yellow to light brown
Dilute Color	Milky white
Odor	Mild, characteristic
pH at 10%	9.7
Specific Gravity	0.96
Density	8.0 lbs/gal (960 kg/m <sup>3</sup> )
Flash Point	> 200°F (93°C)
Boiling Point	> 212°F (100°C)
Chlorine	0%
Mineral Oil	50%
Refractometer Index (% Brix)	10:1 (10%) = 9.2
	20:1 (5%) = 4.6
	30:1 (3%) = 3.1

**DILUTION RATIOS** 

Light-duty machining	30:1	(3%)
Moderate-duty machining	20:1	(5%)
Heavy-duty machining	10:1	(10%)

These dilution ratios should only be used as general guidelines and are not exact specifications. Contact your Rustlick Sales Representative for an application specific recommendation.

**AVAILABLE SIZES** 

**HEALTH AND SAFETY** 

Use proper safety equipment. Avoid contact with skin, eyes, and clothes. Avoid inhaling vapor or mist. Keep away from extreme heat. Keep container closed when not in use. For complete Health and Safety information refer to product Safety Data Sheet (SDS). Product SDS can be downloaded from www.itwprofessionalbrands.com.

The information in this document is believed to be accurate at the date of issue. Because conditions of use are beyond manufacturer's control no guarantee or warranty is expressed or implied.

Effective Date: 07/30/2010