

# **TECHNICAL DATA SHEET**

# **WS-500A**

Water-Soluble Oil Metalworking Fluid Concentrate

#### **DESCRIPTION**

WS-500A is a quality moderate-duty, water-soluble oil with non-chlorinated extreme-pressure additives that are ideal suited for machining titanium. It has lubricity for extended tool life and offers great corrosion protection.

#### **APPLICATIONS**

- Light to moderate-duty operations
- General machining

## **MATERIALS COMPATIBILITY**

- Recommended for ferrous metals, aluminum, and titanium
- Limited use for brass, bronze, and copper

## PHYSICAL PROPERTIES

Concentrate Color	Dark brown
Dilute Color	Milky white
pH at 10%	9.2
Specific Gravity	
Density	7.8 lbs/gal (934 kg/m <sup>3</sup> )
Flash Point	
Boiling Point	212°F (100°C)
Chlorine	
Mineral Oil	74%
Refractometer Readings	10:1 = 11.0
<b>G</b>	20:1 = 5.6
	30:1 = 3.1

#### **DILUTION RATIOS**

•	Milling, drilling, boring, turning, threading, broaching	):1
-	Form grinding	5:1
•	Centerless grinding25:1 – 30	):1

## **AVAILABLE IN**

5 gal	74055
55 gal	74555

# **HEALTH AND SAFETY**

Refer to SDS (Safety Data Sheet) for complete information on health and safety on our web site at www.itwprofessionalbrands.com.

For additional information please contact our Customer Service Department at 800-241-8334.

Revision: July 29, 2008