



### 631 Aerosol

Moisture-displacing, long-term rust preventative

**DESCRIPTION**

631 Aerosol is a moisture-displacing rust preventative and penetrate with two-year indoor corrosion protection. It protects against corrosion with a thin oily-film and can be easily removed with aqueous cleaner.

**APPLICATIONS**

For corrosion and rust prevention  
Spray on wherever protection is needed

**MATERIALS COMPATIBILITY**

Recommended for ferrous and nonferrous metals

**PHYSICAL PROPERTIES**

- Color*.....Amber
- Specific Gravity* .....0.81
- Density* .....6.8 lbs/gal (810 kg/m<sup>3</sup>)
- Flash Point*.....-156°F (-104°C)
- Boiling Point*.....Not available
- Chlorine*.....None
- VOCs*.....72%
- Mineral Oil*.....86%

**DILUTION RATIOS**

DO NOT DILUTE

**AVAILABLE SIZES**

12 oz. aerosol (6/case) .....71101

**HEALTH AND SAFETY**

Use proper safety equipment. Avoid contact with skin, eyes, and clothes. Avoid inhaling vapor or mist. Keep away from extreme heat. Keep container closed when not in use. For complete Health and Safety Information refer to product Safety Data Sheet (SDS) which can be downloaded at [www.itwprofessionalbrands.com](http://www.itwprofessionalbrands.com).

For more information contact 800-241-8334.

The information in this document is believed to be accurate at the date of issue. Because conditions of use are beyond manufacturer's control no guarantee or warranty is expressed or implied.



**631**

Moisture-displacing, long-term rust preventative

**DESCRIPTION**

631 is a moisture-displacing rust preventative and penetrate with two-year indoor corrosion protection. It protects against corrosion with a thin oily-film and can be easily removed with aqueous cleaner.

**APPLICATIONS**

For corrosion and rust prevention  
Apply by brushing or dipping

**MATERIALS COMPATIBILITY**

Recommended for ferrous and nonferrous metals

**PHYSICAL PROPERTIES**

- Color*.....Brown
- Specific Gravity* .....0.82
- Density* .....6.8 lbs/gal (820 kg/m<sup>3</sup>)
- Flash Point*.....180°F (82°C)
- Boiling Point*.....250°F (121°C)
- Chlorine*.....None
- VOCs*.....72%
- Mineral Oil*.....86%

**DILUTION RATIOS**

DO NOT DILUTE

**AVAILABLE SIZES**

- 1 gallon (4/case)* .....71011
- 5 gallon*.....71051
- 55 gallons*.....71551

**HEALTH AND SAFETY**

Use proper safety equipment. Avoid contact with skin, eyes, and clothes. Avoid inhaling vapor or mist. Keep away from extreme heat. Keep container closed when not in use. For complete Health and Safety Information refer to product Safety Data Sheet (SDS) which can be downloaded at [www.itwprofessionalbrands.com](http://www.itwprofessionalbrands.com).

For more information contact 800-241-8334.

The information in this document is believed to be accurate at the date of issue. Because conditions of use are beyond manufacturer's control no guarantee or warranty is expressed or implied.