

SmartlockPro® Slim GFCI with Audible Trip Alert



Instant Audible Alert Indicates Power Interruption

GFCI protection is vital to ensure electrical safety in both residential and commercial settings. A power interruption due to a ground fault provides important protection to people but can shut down freezers, sump pumps and other necessary equipment if left undetected. Often, however, GFCIs in garages, basements or large commercial kitchens may be located in an out-of-the-way place such as a back corner or storage area making daily visual checks for tripping unlikely. The new SmartlockPro Slim GFCI with Audible Alert is the smart solution.

When a condition exists causing the SmartlockPro Slim GFCI with Audible Alert to trip, users will be alerted by the sounding of an audible alarm. This audible alert indicates that power has been disconnected from loads plugged into or fed from the GFCI so users can immediately assess the reason and reset the device. The GFCI with Audible Alert offers all the outstanding benefits you expect from SmartlockPro products, including our patented reset/lockout feature. Plus, the slim profile is compact and easy to install in any wallbox, even shallow ones.

- NEC® requirement for garages, basements, commercial kitchens and other critical loads
- Audible alert indicates the device needs to be reset



Features and Benefits

GFCI

- Slim design is easy to install in any wallbox
- External wiring clamps show proper wire seating
- Standard self-grounding clip
- Tamper-resistant to meet the latest National Electrical Code® child safety requirements
- Reset lockout prevents reset if the GFCI is damaged and cannot respond to a ground fault
- Impact resistant face and body
- Limited Two-Year Warranty

Audible Alarm

- Audible alarm sounds when the GFCI trips, providing an alert that power has been disconnected from load(s) plugged into or fed from the GFCI*
- Indicator light provides visual status


*Audible alarm will NOT sound if the circuit breaker has tripped and disconnected power.

Agency Standards and Certifications


- UL Standard 943 Class A (GFCI) and 498 (Receptacle)
- UL Listed (File #E48380)
- CSA C22.2 - No. 144.1-06 (GFCI) and No. 42 (Receptacle)
- CSA Listed (File #LR-57811)
- NOM - 003: ANCE
- Meets Federal Specification WC-596

INDICATOR LIGHT AND AUDIBLE ALERT			
GFCI Status	Light	Audible Alert	Power
GFCI Properly Wired			
Tripped (RESET button out)	On	On	Off
Set (RESET button in)	Off	Off	On
GFCI Miswired (line/load reversed)			
Tripped (RESET button out)	Off	Off	OFF- Review instructions for correct wiring
Set (RESET button in)	n/a - will not reset	n/a - will not reset	

Dimensional Drawing



Cat. No. A7599



Cat. No. A7899

Ordering Information

Description	Rating	Cat. No.	Color
Tamper-Resistant Slim Series GFCI with Audible Trip Alert	15A-125V Receptacle, 20A-125V Feed-Through	R02-A7599-0KW 001-A7599-00I 002-A7599-00W 006-A7599-00T	White Ivory White Light Almond
	20A-125V Receptacle, 20A-125V Feed-Through	R02-A7899-0KW 001-A7899-00I 002-A7899-00W 006-A7899-00T	White Ivory White Light Almond

Leviton Manufacturing Co., Inc. World Headquarters

201 North Service Road, Melville, NY 11747-3138
 Telephone: 1-800-323-8920 FAX: 1-800-832-9538
 Tech Line (8:30AM-7:00PM E.T. Monday-Friday): 1-800-824-3005



Visit our Website at: www.leviton.com/gfci

© 2014 Leviton Manufacturing Co., Inc. All rights reserved.
 All trademarks are the property of their respective owners.

