

## Commercial Spec Grade Tamper-Resistant Receptacles

Side & Back and Side Wired Versions



Leviton is committed to your safety and to making sure our tamper-resistant commercial spec grade receptacles meet or exceed all existing codes and standards. NEC (National Electrical Code) requirements for commercial facilities necessitate the use of tamper-resistant receptacles and, to bring you more options, we have expanded our receptacle offering with tamper-resistant side wired receptacles. Additionally, we have redesigned the core devices to improve the overall performance of our full line — all to ensure that not only do you have more choices, but smarter choices.

### Features & Benefits:

- Mechanical shutter mechanism prevents access to contacts unless a two-pronged plug is inserted, helping ensure that foreign objects will be locked out
- Ultrasonically welded for additional assembly security
- Body and face made of high impact thermoplastic for durability
- Convenient break-off plaster ears for best flush alignment
- Self-grounding clip staked on, will never fall off
- Easily accessible break-off tabs when split feed wiring is required; allows easy two circuit conversion
- Back & Side Wired version has been redesigned with external wiring clamps to provide visual verification of termination
- Six color offering available to match any décor: Brown, White, Ivory, Black, Gray, Light Almond



## Specifications

Cat. No.	TBR15	TBR20	TCR15	TCR20
<b>Electrical Specifications</b>				
Amperage	15A	20A	15A	20A
Voltage	125V	125V	125V	125V
NEMA	5-15R	5-20R	5-15R	5-20R
Grounding	Self-Grounding			
Pole	2			
Wire	3			
Dielectric Voltage	Withstands 2000V per UL498			
Current Limiting	Full Rated Current			
Temperature Rise	Max 30C after 100 cycles OL at 150 percent rated current			
<b>AC Horsepower Rating</b>				
At Rated Voltage	1/2HP	1HP	1/2HP	1HP
<b>Environmental Specifications</b>				
Flammability	Rated V-2 per UL94			
Operating Temperature	-40C to +60C			
<b>Material Specifications</b>				
Face Material	Thermoplastic			
Body Material	Thermoplastic			
Line Contacts	Brass .031 Thick			
Terminal Clamps	Brass .031 Thick		—	
Terminal Screws	Plated Steel 8-32			
Grounding Screw	Plated Steel 8-32			
Strap Material	Zinc Plated Steel			
Ground Clip	Brass			
Shutter Mechanism	Delrin® Acetal			
<b>Mechanical Specifications</b>				
Terminal ID	Brass-Hot, Green-Ground, Silver-Neutral			
Terminal Accom.	14-10 AWG			
Wire Types	Solid or Stranded Building Wire			
Product ID	Ratings Permanently Marked on Device			
Termination	Back & Side		Side	
<b>Standards &amp; Certifications</b>				
NEMA	WD-1 WD-6			
ANSI	C-73			
cULus	File E13399			
NOM	057			
<b>Warranties</b>				
Warranty	10 Year Limited			

## Ordering Information

Cat. No.	Description	Color	Cat. No.	Description	Color
TBR15	15A, Back & Side Wired	Brown	TBR20	20A, Back & Side Wired	Brown
TBR15-W	15A, Back & Side Wired	White	TBR20-W	20A, Back & Side Wired	White
TBR15-I	15A, Back & Side Wired	Ivory	TBR20-I	20A, Back & Side Wired	Ivory
TBR15-E	15A, Back & Side Wired	Black	TBR20-E	20A, Back & Side Wired	Black
TBR15-GY	15A, Back & Side Wired	Gray	TBR20-GY	20A, Back & Side Wired	Gray
TBR15-T	15A, Back & Side Wired	Lt. Almond	TBR20-T	20A, Back & Side Wired	Lt. Almond
TCR15	15A, Side Wired	Brown	TCR20	20A, Side Wired	Brown
TCR15-W	15A, Side Wired	White	TCR20-W	20A, Side Wired	White
TCR15-I	15A, Side Wired	Ivory	TCR20-I	20A, Side Wired	Ivory
TCR15-E	15A, Side Wired	Black	TCR20-E	20A, Side Wired	Black
TCR15-GY	15A, Side Wired	Gray	TCR20-GY	20A, Side Wired	Gray
TCR15-T	15A, Side Wired	Lt. Almond	TCR20-T	20A, Side Wired	Lt. Almond

### Leviton Manufacturing Co., Inc.

201 N Service Rd, Melville, NY 11747  
 Telephone: 1-800-323-8920 • FAX: 1-800-832-9538  
 Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): 1-800-824-3005

### Leviton Manufacturing of Canada, Ltd.

165 Hymus Blvd, Pointe-Claire, QC H9R 1E9  
 Telephone: 1-800-469-7890 • FAX: 1-800-563-1853

### Leviton S. de R.L. de C.V.

Lago Tana 43, Col. Huichapan, Miguel Hidalgo, CP 11290 México DF  
 Tel. (+52) 55-5082-1040 • Fax: (+52) 55-5386-1797 • www.leviton.com.mx

Visit our Website at: [www.leviton.com/industrial](http://www.leviton.com/industrial) email: [industrial@leviton.com](mailto:industrial@leviton.com)

© 2014 Leviton Manufacturing Co., Inc. All rights reserved.

## Dimensions

Typical for Commercial Spec Grade TR Receptacles

