


New & Improved!

Industrial Grade Isolated Ground GFCI Duplex Receptacles



Patented SmartlockPro® protection detects and prevents against line-load reversal miswiring, and prevents resetting when ground fault protection has been lost

Ordering Information

Description		Isolated Ground	
		15A	20A
ORDER ID	Orange	X7599-IGO	X7899-IGO
	Brown*	X7599-IG	X7899-IG
	Ivory*	X7599-IGI	X7899-IGI
	White*	X7599-IGW	X7899-IGW
	Black*	X7599-IGE	X7899-IGE
	Gray*	X7599-IGG	X7899-IGG
	Lt. Almond*	X7599-IGT	X7899-IGT
	Red*	X7599-IGR	X7899-IGR

* Special Order Configurations


Common Applications

- Educational Facilities
- Office Environments
- Computer Labs
- Outdoor Retail Locations
- A/V Locations


Specifications

Description	Industrial Grade Isolated Ground Duplex Receptacles
AC Horsepower Rating	
At Rated Voltage	1 HP
Electrical Specifications	
Amperage	15A or 20A
Voltage	125VAC
NEMA	5-15R or 5-20R
Grounding	Isolated ground
Pole	2
Wire	3
Dielectric Voltage	Withstands 1250VAC per UL 943 and CSA-C22.2 No. 144.1-06
Short Circuit Current Rating	10kA
Trip Level	Class A, 5mA plus or minus 1mA
Temperature Rise	Max 30 °C after 250 cycles OL at 200 percent rated current
Environmental Specifications	
Flammability	Rated V-0 per UL94
Relative Humidity	20% to 90% non-condensing
Operating Temperature	-35 °C to 66 °C
Material Specifications	
Face Material	PBT
Body Material	Polycarbonate
Line Contacts	Brass
Mounting Screws	Plated Steel
Grounding Screw	Plated Steel
Strap Material	Galvanized Steel
Ground Clip	Brass
Mechanical Specifications	
Terminal ID	Brass-Hot, Silver-Neutral, Green-Ground
Terminal Accommodation	14-10 AWG solid or stranded
Product ID	Ratings permanently marked on device
Termination	Back or Side Wiring
Standards & Certifications	
NEMA	WD-1 & WD-6
ANSI	C-73
Certification/Listing	UL, CSA, NOM-ANCE
Applicable Standards	UL 498 and 943, CSA C22.2 Nos. 42 and 144, FedSpec W-C-596
Guarantees	
Product Warranty	2 Year Limited

Dimensions



Front View



Side View

Visit our Website at:
www.leviton.com/industrial
 email: industrial@leviton.com

Q-902

Leviton Manufacturing Co., Inc.

201 N Service Rd, Melville, NY 11747
 Telephone: 1-800-323-8920 • FAX: 1-800-832-9538
 Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): 1-800-824-3005

© 2014 Leviton Manufacturing Co., Inc. All rights reserved.

052014

