

Revision Number: 011.0 Issue date: 08/05/2014

# 1. PRODUCT AND COMPANY IDENTIFICATION

**LOCTITE SI 5900 INSTANT GASKET** IDH number: Product name: 743914

known as Ready Gasket 190ml AE

Product type: Silicone Sealant Item number: 40480 Restriction of Use: None identified Region: **United States** Contact information:

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

Telephone: (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

WARNING: CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1

#### PICTOGRAM(S)



### **Precautionary Statements**

IDH number: 743914

Avoid breathing mist or spray. Wash thoroughly after handling. Contaminated work clothing Prevention:

should not be allowed out of the workplace. Wear eye and face protection. Wear protective

IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for Response:

several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical

attention. Take off contaminated clothing.

Storage: Not prescribed

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Reinforcing filler	Proprietary	30 - 60	
Silicone Resin	Proprietary	10 - 30	
Norflurane	811-97-2	5 - 10	
Oximino silane	Proprietary	1 - 5	
Octadecanoic acid	57-11-4	1 - 5	
Reactive Silane	Proprietary	0.1 - 1	
Reactive Silane	Proprietary	0.1 - 1	

<sup>\*</sup> Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. If symptoms develop and persist, get medical attention.

Skin contact: Wipe off paste with paper towel or cloth. Wash with soap and water. If

symptoms develop and persist, get medical attention.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. If eye irritation persists, consult a specialist.

**Ingestion:** Do not induce vomiting. Seek medical advice.

Symptoms: See Section 11.

### 5. FIRE FIGHTING MEASURES

Extinguishing media: Foam, dry chemical or carbon dioxide.

**Special firefighting procedures:**Use water spray to keep fire exposed containers cool and disperse vapors.

Unusual fire or explosion hazards: Contents under pressure. Closed containers may rupture (due to build up of

pressure) when exposed to extreme heat.

Hazardous combustion products: Oxides of Silicon Oxides of carbon. Formaldehyde

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow spill to enter sewage systems or open bodies of water.

Clean-up methods: Maintain good ventilation for large spills. Scrape up as much material as

possible. Place scrap material in a well ventilated area and allow to cure to

ubber.

# 7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and

cause eye irritation.

Storage: Store in a cool, dry, well-ventilated area.

IDH number: 743914

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER	
Reinforcing filler	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None	
Silicone Resin	None	None	None	None	
Norflurane	None	None 1,000 ppm (4,240 mg/m3) TWA		None	
Oximino silane	None	None	None	None	
Octadecanoic acid	10 mg/m3 TWA	None	None	None	
Reactive Silane	None	None	None	None	
Reactive Silane	None	None	None	None	

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed

established exposure limits exists.

**Eye/face protection:** Safety goggles or safety glasses with side shields.

**Skin protection:**Use impermeable gloves and protective clothing as necessary to prevent skin

contact.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Aerosol, Paste

Color: Black

Odor:
Odor threshold:
PH:
Vapor pressure:
Boiling point/range:
Melting point/ range:
Vapor density:
Not available.
Mild, Petroleum
Not available.
Not available.
Not available.
Not available.
Not available.
Not available.

Flash point: > 93.00 °C (> 199.4 °F)

Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Evaporation rate:

Not available.
Not available.
Not available.

Solubility in water: Polymerizes on contact with water.

Partition coefficient (n-octanol/water):

VOC content:

Viscosity:

Decomposition temperature:

Not available.

3.90 %; 50.70 g/l

Not available.

Not available.

### 10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur

**Hazardous decomposition** 

products:

IDH number: 743914

Oxides of carbon. Oxides of silicon. Methyl ethyl ketoxime formed during cure. Formaldehyde.

**Incompatible materials:** Polymerizes on contact with water.

Reactivity: Not available.

Conditions to avoid: Moisture.

### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

#### Potential Health Effects/Symptoms

**Inhalation:** Inhalation of mist or spray may cause irritation of the respiratory tract and nasal passages.

When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible

limit.

**Skin contact:** Causes skin irritation. May cause allergic skin reaction.

**Eye contact:** Causes serious eye irritation.

**Ingestion:** Not expected under normal conditions of use. May be harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Reinforcing filler	Oral LD50 (RAT) = 6,450 mg/kg	Nuisance dust	
Silicone Resin	None	Irritant	
Norflurane	None	Cardiac, Central nervous system, Irritant, Respiratory, Skin	
Oximino silane	None	Irritant, Allergen	
Octadecanoic acid	Oral LD50 (RAT) = 4.6 g/kg	Irritant	
Reactive Silane	None	Irritant, Allergen	
Reactive Silane	None	Irritant, Allergen	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Reinforcing filler	No	No	No
Silicone Resin	No	No	No
Norflurane	No	No	No
Oximino silane	No	No	No
Octadecanoic acid	No	No	No
Reactive Silane	No	No	No
Reactive Silane	No	No	No

# 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

#### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:
Hazard class or division:
Identification number:
UN 1950
Packing group:
None

International Air Transportation (ICAO/IATA)

**Proper shipping name:** Aerosols, non-flammable

Hazard class or division: 2.2 Identification number: UN 1950 Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: AEROSOLS
Hazard class or division: 2.2
Identification number: UN 1950
Packing group: None

### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: Propylene oxide (CAS# 75-56-9). Ethylene oxide (CAS# 75-21-8).

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health None above reporting de minimis

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

**Canada Regulatory Information** 

IDH number: 743914

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Catherine Bimler, Regulatory Affairs Specialist

**Issue date:** 08/05/2014

Product name: LOCTITE SI 5900 INSTANT GASKET known as Ready Gasket 190ml AE Page 5 of 6

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.