# **Fb2**

# SAFETY DATA SHEET

## 1. Identification

Product identifier LPS® Tapmatic® AquaCut

Other means of identification

**Part Number** 01216, 01228, 01205

Recommended use A water-based cutting fluid designed for use on steel, aluminum and other metals except

magnesium.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Manufacturer

**Company name** ITW Pro Brands **Address** 4647 Hugh Howell Rd.

Tucker, GA 30084

Country (U.S.A.)

Tel: +1 770-243-8800

In Case of Emergency 1-800-424-9300 (inside U.S.)

+001 703-527-3887 (outside U.S.)

Website www.lpslabs.com

E-mail lpssds@itwprobrands.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Sensitization, skin

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

**Hazard statement** May cause an allergic skin reaction.

**Precautionary statement** 

Prevention Avoid breathing mist or vapor. Contaminated work clothing must not be allowed out of the

workplace. Wear protective gloves.

**Response** If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

Category 1

Wash contaminated clothing before reuse.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None known.

#### 3. Composition/information on ingredients

#### **Mixtures**

| Chemical name     | Common name and synonyms | CAS number | %       |  |
|-------------------|--------------------------|------------|---------|--|
| Cinnamic Aldehyde |                          | 104-55-2   | 0.1 - 1 |  |

#### 4. First-aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

IngestionRinse mouth. Get medical attention if symptoms occur.Most importantMay cause an allergic skin reaction. Dermatitis. Rash.

symptoms/effects, acute and delayed

delayed
Indication of immediate

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

medical attention and special treatment needed

**General information** 

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

Move containers from fire area if you can do so without risk.

equipment/instructions Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

**General fire hazards** No unusual fire or explosion hazards noted.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

### 7. Handling and storage

Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Avoid breathing mist or vapor. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

#### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

# US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components                | Туре | Value                |  |
|---------------------------|------|----------------------|--|
| Isopropanol (CAS 67-63-0) | PEL  | 980 mg/m3<br>400 ppm |  |

| Components                          | Туре                       | Value         |          |
|-------------------------------------|----------------------------|---------------|----------|
| Phosphoric Acid (CAS<br>7664-38-2)  | PEL                        | 1 mg/m3       |          |
| Sodium Hydroxide (CAS<br>1310-73-2) | PEL                        | 2 mg/m3       |          |
| US. ACGIH Threshold Limit Value     | s                          |               |          |
| Components                          | Туре                       | Value         |          |
| Isopropanol (CAS 67-63-0)           | STEL                       | 400 ppm       |          |
|                                     | TWA                        | 200 ppm       |          |
| Phosphoric Acid (CAS<br>7664-38-2)  | STEL                       | 3 mg/m3       |          |
|                                     | TWA                        | 1 mg/m3       |          |
| Sodium Hydroxide (CAS<br>1310-73-2) | Ceiling                    | 2 mg/m3       |          |
| Triethanolamine (CAS<br>102-71-6)   | TWA                        | 5 mg/m3       |          |
| US. NIOSH: Pocket Guide to Cher     | nical Hazards              |               |          |
| Components                          | Туре                       | Value         |          |
| Isopropanol (CAS 67-63-0)           | STEL                       | 1225 mg/m3    |          |
|                                     |                            | 500 ppm       |          |
|                                     | TWA                        | 980 mg/m3     |          |
|                                     |                            | 400 ppm       |          |
| Phosphoric Acid (CAS<br>7664-38-2)  | STEL                       | 3 mg/m3       |          |
| •                                   | TWA                        | 1 mg/m3       |          |
| Sodium Hydroxide (CAS<br>1310-73-2) | Ceiling                    | 2 mg/m3       |          |
| US. Workplace Environmental Ex      | posure Level (WEEL) Guides |               |          |
| Components                          | Туре                       | Value         | Form     |
| Propylene Glycol (CAS<br>57-55-6)   | TWA                        | 10 mg/m3      | Aerosol. |
| ogical limit values                 |                            |               |          |
| ACGIH Biological Exposure Indic     | 96                         |               |          |
| Components Value                    |                            | imen Sampling |          |

<sup>\* -</sup> For sampling details, please see the source document.

Appropriate engineering controls

Isopropanol (CAS 67-63-0) 40 mg/l

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Urine

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Acetone

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

# 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.

**Form** Liquid. Color Blue green. Odor Cinnamon. Odor threshold Not established

8 - 9 pН

Not established Melting point/freezing point 212 °F (100 °C) Initial boiling point and boiling

range

Flash point None

**Evaporation rate** 1 (water = 1)Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

None

(%)

Flammability limit - upper

None

(%)

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%)

Vapor pressure 18 mm Hg @ 20°C

~0.6 Vapor density

Not available. Relative density

Solubility(ies)

100 % in water Solubility (water)

**Partition coefficient** < 1

(n-octanol/water)

**Auto-ignition temperature** > 33.8 °F (> 1 °C) **Decomposition temperature** Not established Not established **Viscosity** 

Other information

Not explosive. **Explosive properties** Heat of combustion Not established **Oxidizing properties** Not oxidizing.

Percent volatile 95 %

0.99 - 1.01 @ 20°C Specific gravity

VOC 0 % per U.S. State and Federal Consumer Product Regulations

**CARB** 

# 10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. **Chemical stability** 

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides.

# 11. Toxicological information

## Information on likely routes of exposure

Prolonged inhalation may be harmful. Inhalation

Material name: LPS® Tapmatic® AquaCut

Skin contact May cause an allergic skin reaction.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not

been observed in humans.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

**Acute toxicity** Not known.

Components **Species Test Results** 

Cinnamic Aldehyde (CAS 104-55-2)

**Acute Dermal** 

LD50 Rabbit 1260 ml/kg, 24 Hours

Oral

LD50 Rat 2220 mg/kg

Isopropanol (CAS 67-63-0)

**Acute Dermal** 

16.4 ml/kg, 24 Hours LD50 Rabbit

Oral

LD50 Rat 4.7 g/kg

Phosphoric Acid (CAS 7664-38-2)

**Acute** Oral

LD50 Rat 1.7 ml/100g

Propylene Glycol (CAS 57-55-6)

**Acute** 

**Dermal** 

Rabbit LD50 > 2000 mg/kg, 24 Hours

Oral

LD50 Rat 22000 mg/kg

Triethanolamine (CAS 102-71-6)

**Acute** 

**Dermal** 

Rabbit LD50 > 2000 mg/kg

Oral

LD50 Rat 6400 mg/kg

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

**ACGIH Carcinogens** 

Isopropanol (CAS 67-63-0) A4 Not classifiable as a human carcinogen.

01216, 01228, 01205 Version #: 01 Issue date: 09-21-2016

## IARC Monographs. Overall Evaluation of Carcinogenicity

Triethanolamine (CAS 102-71-6) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** May be harmful if absorbed through skin. Prolonged inhalation may be harmful.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not

been observed in humans.

**Further information** Symptoms may be delayed.

# 12. Ecological information

**Ecotoxicity**The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Components           |               | Species                                 | Test Results                 |
|----------------------|---------------|---|------------------------------|
| Isopropanol (CAS 67- | 63-0)         |   |                              |
| Aquatic              |               |   |                              |
| Fish                 | LC50          | Bluegill (Lepomis macrochirus)          | > 1400 mg/l, 96 hours        |
| Propylene Glycol (CA | S 57-55-6)    |   |                              |
| Aquatic              |               |   |                              |
| Crustacea            | EC50          | Water flea (Daphnia magna)              | > 10000 mg/l, 48 hours       |
| Fish                 | LC50          | Fathead minnow (Pimephales promelas)    | 710 mg/l, 96 hours           |
| Sodium Hydroxide (Ca | AS 1310-73-2) |   |                              |
| Aquatic              |               |   |                              |
| Crustacea            | EC50          | Water flea (Ceriodaphnia dubia)         | 34.59 - 47.13 mg/l, 48 hours |
| Fish                 | LC50          | Western mosquitofish (Gambusia affinis) | 125 mg/l, 96 hours           |
| Triethanolamine (CAS | S 102-71-6)   |   |                              |
| Aquatic              |               |   |                              |
| Crustacea            | EC50          | Water flea (Ceriodaphnia dubia)         | 565.2 - 658.3 mg/l, 48 hours |
| Fish                 | LC50          | Fathead minnow (Pimephales promelas)    | 10610 - 13010 mg/l, 96 hours |

Persistence and degradability Expected to biodegrade.

**Bioaccumulative potential** 

Partition coefficient n-octanol / water (log Kow)

LPS® Tapmatic® AquaCut < 1
Isopropanol 0.05
Propylene Glycol -0.92
Triethanolamine -1

Mobility in soilNo data available.Other adverse effectsNone known.

# 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Material name: LPS® Tapmatic® AquaCut

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

# 15. Regulatory information

**US federal regulations** 

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Phosphoric Acid (CAS 7664-38-2) Listed. Sodium Hydroxide (CAS 1310-73-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Yes

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Cinnamic Aldehyde (CAS 104-55-2)

Isopropanol (CAS 67-63-0)

Phosphoric Acid (CAS 7664-38-2)

Low priority

High priority

**US state regulations** WARNING: This product contains a chemical known to the State of California to cause cancer.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Isopropanol (CAS 67-63-0) Phosphoric Acid (CAS 7664-38-2)

#### International Inventories

| Country(s) or region        | Inventory name   | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia                   | Australian Inventory of Chemical Substances (AICS)                     | No                     |
| Canada                      | Domestic Substances List (DSL)   | Yes                    |
| Canada                      | Non-Domestic Substances List (NDSL)                                    | Yes                    |
| China                       | Inventory of Existing Chemical Substances in China (IECSC)             | Yes                    |
| Europe                      | European Inventory of Existing Commercial Chemical Substances (EINECS) | No                     |
| Europe                      | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                       | Inventory of Existing and New Chemical Substances (ENCS)               | No                     |
| Korea                       | Existing Chemicals List (ECL)  | No                     |
| New Zealand                 | New Zealand Inventory  | Yes                    |
| Philippines                 | Philippine Inventory of Chemicals and Chemical Substances (PICCS)      | Yes                    |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory                          | Yes                    |

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

**Issue date** 09-21-2016

Version # 01

Disclaimer ITW Pro Brands cannot anticipate all conditions under which this information and its product, or

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless

specified in the text.

**Revision information**This document has undergone significant changes and should be reviewed in its entirety.

Material name: LPS® Tapmatic® AquaCut

SDS US