

SAFETY DATA SHEET

1. Identification

Product identifier	LPS® PF® Solvent	
Other means of identification	a. / /aa	
Part Number	61420	
Recommended use	A solvent agent designed for removing grease, oil and other residues from metal, power cable and fiber optic cable surfaces.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier Manufacturer	/Distributor information	
Manufacturer		
Company name	ITW Pro Brands	
Address	4647 Hugh Howell Rd.	
	Tucker, GA 30084	
Country	(U.S.A.)	
	Tel: +1 770-243-8800	
In Case of Emergency	1-800-424-9300 (inside U.S.)	
	+001 703-527-3887 (outside U.S.)	
Website	www.lpslabs.com	
E-mail	lpssds@itwprobrands.com	
2. Hazard(s) identification		
Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Compressed gas
Health hazards	Sensitization, skin	Category 1
	Aspiration hazard	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Danger	
Hazard statement	Extremely flammable aerosol. Contains gas swallowed and enters airways. May cause a	under pressure; may explode if heated. May be fatal if an allergic skin reaction.
Precautionary statement		
Prevention	flame or other ignition source. Pressurized of	ot surfaces No smoking. Do not spray on an open container: Do not pierce or burn, even after use. Avoid must not be allowed out of the workplace. Wear
Response	If swallowed: Immediately call a poison cent with plenty of water. If skin irritation or rash contaminated clothing before reuse.	ter/doctor. Do NOT induce vomiting. If on skin: Wash occurs: Get medical advice/attention. Wash
Storage	Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	
Disposal	Dispose of contents/container in accordance	e with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None known.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Naphtha Petroleum, Hydrotreated Heavy		64742-48-9	80 - 90
d-Limonene		5989-27-5	1 - 10
Carbon Dioxide		124-38-9	1 - 5

4. First-aid measures

4. First-aid measures	
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Not likely, due to the form of the product.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water spray. Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when

Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage,	Level 3 Aerosol.
including any incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

PEL it Values Type STEL TWA to Chemical Hazards Type STEL	9000 mg/m3 5000 ppm Value 30000 ppm 5000 ppm Value
Type STEL TWA to Chemical Hazards Type	Value 30000 ppm 5000 ppm
Type STEL TWA to Chemical Hazards Type	30000 ppm 5000 ppm
STEL TWA to Chemical Hazards Type	30000 ppm 5000 ppm
TWA to Chemical Hazards Type	5000 ppm
to Chemical Hazards Type	
Туре	Value
	Value
STEL	
	54000 mg/m3
	30000 ppm
TWA	9000 mg/m3
	5000 ppm
No biological exposure limits noted f	or the ingredient(s).
should be matched to conditions. If a or other engineering controls to main) air changes per hour) should be used. Ventilation rates applicable, use process enclosures, local exhaust ventilation, atain airborne levels below recommended exposure limits. If lished, maintain airborne levels to an acceptable level.
s, such as personal protective equipn	nent
Wear safety glasses with side shield	s (or goggles).
Wear appropriate chemical resistant supplier.	gloves. Suitable gloves can be recommended by the glove
Wear appropriate chemical resistant	clothing. Use of an impervious apron is recommended.
If permissible levels are exceeded us air-supplied respirator.	se NIOSH mechanical filter / organic vapor cartridge or an
Wear appropriate thermal protective	clothing, when necessary.
after handling the material and befor	bserve good personal hygiene measures, such as washing e eating, drinking, and/or smoking. Routinely wash work remove contaminants. Contaminated work clothing should no
	No biological exposure limits noted for Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main exposure limits have not been establ s, such as personal protective equipm Wear safety glasses with side shield Wear appropriate chemical resistant supplier. Wear appropriate chemical resistant If permissible levels are exceeded us air-supplied respirator. Wear appropriate thermal protective When using do not smoke. Always o after handling the material and befor clothing and protective equipment to

Appearance

Physical state	Gas.	
Form	Aerosol.	
Color	Clear water-white.	
Odor	Orange.	
Odor threshold	Not available.	
рН	Not applicable	
Melting point/freezing point	Not available.	
Initial boiling point and boiling range	365 °F (185 °C) @760 mm Hg	
Flash point	> 141.8 °F (> 61.0 °C) Tag Closed Cup	
Evaporation rate	< 0.1 BuAc = 1	
Flammability (solid, gas) Flammable gas.		
Upper/lower flammability or exp	losive limits	
Flammability limit - lower (%)	0.7 %	
Flammability limit - upper (%)	5.3 %	
Explosive limit - lower (%)	Not available.	
Explosive limit - upper (%)	Not available.	
Vapor pressure	0.48 mm Hg @ 20°C	
Vapor density	> 1 (air = 1)	
Relative density	Not available.	
Solubility(ies)		
Solubility (water)	Negligible	
Partition coefficient (n-octanol/water)	Not Determined	
Auto-ignition temperature	635 °F (335 °C)	
Decomposition temperature	Not available.	
Viscosity	1.5 cSt @ 25°C	
Other information		
Explosive properties	Not explosive.	
Heat of combustion	> 30 kJ/g	
Oxidizing properties	Not oxidizing.	
Percent volatile	100 %	
Specific gravity	0.74 - 0.78 @20°C	
VOC	CARB 97.24 % per US State and Federal Consumer Product Regulations	
10. Stability and reactivity		
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.	
Chemical stability Material is stable under normal conditions.		
Possibility of hazardous Hazardous polymerization does not occur.		

Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.	
Skin contact	May cause an allergic skin reaction.	
Eye contact	Direct contact with eyes may cause temporary irritation.	

Ingestion	Droplets of the product chemical pneumonia.	aspirated into the lungs through	ingestion or vomiting may cause a serious
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause an allergic skin reaction. Dermatitis. Rash.		
Information on toxicological ef	iffects		
Acute toxicity	May be fatal if swallowe	d and enters airways. May caus	se an allergic skin reaction.
Components	Species	1	lest Results
d-Limonene (CAS 5989-27-5)			
Acute			
Oral			
LD50	Rat	>	2000 mg/kg
Naphtha Petroleum, Hydrotreate	d Heavy (CAS 64742-48-9)		
Acute			
Dermal			
LD50	Rabbit	>	• 1900 mg/kg, 24 Hours
Inhalation			
<i>Vapor</i> LC50	Rat		4.06 mg/L 4 Hours
	nai	>	• 4.96 mg/l, 4 Hours
Oral LD50	Rat	Л	820 mg/kg
			020 mg/kg
Skin corrosion/irritation	-	may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes	may cause temporary irritation	
Respiratory or skin sensitization			
Respiratory sensitization	Not a respiratory sensit		
Skin sensitization	May cause sensitization by skin contact. No data available to indicate product or any components present at greater than 0.1% are		
Germ cell mutagenicity	mutagenic or genotoxic		
Carcinogenicity	This product is not cons	idered to be a carcinogen by IA	RC, ACGIH, NTP, or OSHA.
IARC Monographs. Overall	-	-	
d-Limonene (CAS 5989 OSHA Specifically Regulat Not regulated. US. National Toxicology Pr	ed Substances (29 CFR 1	910.1001-1050)	carcinogenicity to humans.
Not listed.			
Reproductive toxicity	This product is not expe	ected to cause reproductive or d	evelopmental effects.
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	May be fatal if swallowe	d and enters airways.	
Chronic effects	Prolonged inhalation may be harmful.		
Further information	Symptoms may be delayed.		
12. Ecological informatio	n	-	
Ecotoxicity			ous. However, this does not exclude the
-	possibility that large or	requent spills can have a harm	ful or damaging effect on the environment.
Components	Species	1	Test Results
d-Limonene (CAS 5989-27-5 Aquatic	5)		
Crustacea	EC50 Water fl	ea (Daphnia pulex)	69.6 mg/l, 48 hours
Fish	LC50 Fathead	minnow (Pimephales promelas	i) 0.619 - 0.796 mg/l, 96 hours

Persistence and degradability	Expected to biodegrade.	
Bioaccumulative potential		
Partition coefficient n-octar d-Limonene	nol / water (log Kow) 4.232	
Mobility in soil	No data available.	
Other adverse effects	None known.	
13. Disposal consideratio	ns	
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.	
	D003: Waste Reactive material	
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:	

	under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
	D003: Waste Reactive material
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

00	1	
	UN number	UN1950
	UN proper shipping name	Aerosols, flammable
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not available.
	Environmental hazards	
	Marine pollutant	No
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
	Special provisions	N82
	Packaging exceptions	306
	Packaging non bulk	None
	Packaging bulk	None
ΙΑΤ	A	
	UN number	UN1950
	UN proper shipping name	Aerosols, flammable
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not available.
	Environmental hazards	No.
	• •	Read safety instructions, SDS and emergency procedures before handling.
	Other information	
	Passenger and cargo	Allowed with restrictions.
	aircraft	
	Cargo aircraft only	Allowed with restrictions.
IME		
	UN number	UN1950
	UN proper shipping name	Aerosols, flammable, MARINE POLLUTANT
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1

2 Marine pollutant

IATA; IMDG



General information

IMDG Regulated Marine Pollutant. Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) Not regulated. CERCLA Hazardous Substance List (40 CFR 302.4) Not listed. SARA 304 Emergency release notification Not regulated. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

	-	
Hazard	categories	

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes chemical

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated. (SDWA)

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Naphtha Petroleum, Hydrotreated Heavy (CAS 64742-48-9)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date Version #	07-18-2016 01
Disclaimer	ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	This document has undergone significant changes and should be reviewed in its entirety.