



# Micro-X NU

## Fast Evaporating Contact Cleaner



### FEATURES

- Contains NO Chlorinated solvents, safe on plastics
- NSF Certified: K2 Registration #142149 (aerosol)
- Removes dirt, flux, moisture, dust, oxides, and other contaminants
- Ideal for electronic and fine parts
- Quick Penetration
- VOC Compliant in all 50 states

### APPLICATIONS

- Connectors
- Circuit boards
- Contacts
- Controls
- Fluid Systems
- Instrumentation
- Keyboards

### SPECIFICATIONS AND APPROVALS

- NSF International

**IS (IDENTIFICATION SYSTEM)**

### AVAILABLE PRODUCTS

Part No.		Net Contents	Container	Case Pack	Case Wt.
US	Canada				
06616	N/A	11 wt. oz./312 g/417 mL	aerosol	12	12 lbs.

### PROPERTIES

Appearance/physical state	Gas
Odor	Mild
Melting point/freezing point	-198.4°F (-128°C) estimated
Boiling point/range	140.9 °F (60.5°C)
Vapor pressure	352.53 mm Hg @ 38°C
Partition coefficient	Not Established
Percent volatile	100%
Flammability limit	lower: 0.6%, upper: 7%
Propellant	HFC-134a
VOC Content	74% (600g/L)
Color	Clear
Flash point	< 1.4°F (< -17.0°C) TCC
Relative density	N/A
Evaporation rate	<1 BuAc (Ethyl Ether = 1)
Vapor density	>1 (air = 1)
Auto-ignition temperature	582.8°F (306°C)
Viscosity	< 3 cSt @ 25°C
Specific Gravity (water=1)	0.8 - 0.82 @ 20°C
Temperature Range °F(°C)	N/A

### DIRECTIONS

Hold can 6-8 inches (15-20 cm) away and spray directly on surface to remove any contaminants. **DO NOT USE ON ENERGIZED ELECTRICAL EQUIPMENT IN OPERATION AND ALLOW SURFACE TO DRY BEFORE RESTART.**

### HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not re-use empty containers. Do not breathe gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling.

### STORAGE

Store locked up in a well-ventilated place. Keep container tightly closed. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition.

### DISPOSAL INFORMATION

Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations.



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.lpslabs.com](http://www.lpslabs.com)

©2018 ITW Pro Brands • LPS® is a registered trademark of Illinois Tool Works All Rights Reserved • TDS06616 • 180214