



Electro 140° Contact Cleaner



FEATURES

- Superior Wetting and Penetrating Action
- Controlled Evaporation
- Flash Point 140°F (60°C)
- Non-Conductive and Leaves no Residue
- Safe to use on most surfaces
- Inverts Spray Valve

APPLICATIONS

- Coin Counters & Chutes
- Connectors
- Contacts
- Fluid Systems
- Office Equipment
- Relays and Controls
- Semiconductor Assemblies
- Switches
- Telephone Equipment
- Printed Circuits

SPECIFICATIONS AND APPROVALS

- Learjet LES 1239J
- McDonnell Douglas CSD #1*
- Bombardier (Canadair) BAPS 180-009
- Caterpillar
- Ford Motor Co.
- General Motors Co.
- Martin Marietta MMS-M2-10028
- ASTM F-945
- Kodak
- Tampa Electric Co.
- Kimberly-Clark

*Does not conform to Stress Cracking Test

IS (IDENTIFICATION SYSTEM)



AVAILABLE PRODUCTS

Part No.		Net Contents	Container	Case Pack	Case Wt.
US	Canada				
00916	C00916	11 wt. oz./312 g/389 mL	16 oz.	12	12 lbs.

PROPERTIES

Appearance/physical state	Gas
Odor	Mild, Ether-like
Melting point/freezing point	N/A
Boiling point/range	345.2°F (174°C)
Vapor pressure	0.49 mm Hg @ 20°C
Partition coefficient	<1
Percent volatile	100%
Flammability limit	lower: 1.2%, upper: 13.1%
Propellant	Carbon Dioxide
VOC Content	96.8%
Color	Colorless
Flash point	>140.0°F (> 60.0°C) (TCC)
Relative density	N/A
Evaporation rate	< 0.1 (BuAc = 1)
Vapor density	5.1 (air = 1)
Auto-ignition temperature	>500°F (> 260°C)
Viscosity	N/A
Specific Gravity (water=1)	0.78 - 0.81 @ 20°C
Dielectric Strength (ASTM D-877)	15.14 kV
Surface Tension	25.9 dynes/cm @ 77°F (25°C)

DIRECTIONS

Hold can 6-8 inches (15-20 cm) away from electronic components and spray directly on surface to clean. May attack certain plastics.

HANDLING

Pressurized container: do not pierce or burn, even after use. Wash thoroughly after handling. Wear eye protection/face protection.

STORAGE

Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Keep away from heat, hot surface sparks, open flames, and other ignition sources.

DISPOSAL INFORMATION

Dispose of waste and residues in accordance with local authority requirements.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.lpslabs.com

©2018 ITW Pro Brands • LPS® is a registered trademark of Illinois Tool Works All Rights Reserved • TDS00916 • 180214