



BFX™ ALL-PURPOSE CLEANER

VALUE PERFORMANCE

The water-based, industrial strength degreaser has the same great formula and is now more earth-friendly and non-staining.



INDUSTRIAL DEGREASER TECHNICAL DATA SHEET

FEATURES

- Industrial strength for hard-to-remove grease and oil
- Non-corrosive formula inhibits flash-rusting
- Rinses clean to eliminate residue and surface contamination
- Water-based and biodegradable for safer cleaning alternative
- Nonfood Compounds Program Listed Category Code: C1 Registration #130101

SPECIFICATIONS AND APPROVALS

- Nonfood Compounds Program Listed Category Code: C1 Registration #130101



PACKAGE SIZES

Net Contents	Part No.
28 fl. oz. (828 mL) trigger	05528
1 gal. (3.78 L)	05501
5 gal. (18.93 L)	05505
55 gal. (208 L)	05555

APPLICATION DILUTION CHART

BFX	Water	=	BFX	Water
1 to	4 parts	=	32 fl. oz	1 gallon
1 to	5 parts	=	26 fl. oz	1 gallon
1 to	10 parts	=	13 fl. oz	1 gallon
1 to	20 parts	=	6.5 fl. oz	1 gallon
1 to	40 parts	=	3 fl. oz	1 gallon
1 to	80 parts	=	1.5 fl. oz	1 gallon
1 to	100 parts	=	1.3 fl. oz	1 gallon
1 to	128 parts	=	1 fl. oz	1 gallon
1 to	150 parts	=	.85 fl. oz	1 gallon

APPLICATIONS

- Aluminum
- Carbon
- Carpet
- Chrome
- Computer Casing
- Counters
- Diesel Fuel
- Dip Tanks
- Engines
- Fiberglass
- Floor Scrubbers
- Grease
- Grease Filters
- Machinery
- Metal Prepping
- Painted Surfaces
- Parts Washers
- Pressure Sprayers
- Road Tar
- Smoke
- Soot
- Spot Cleaning
- Stainless Steel
- Tile and Grout
- Tumblers
- Vehicles
- Vents
- Vinyl
- Windows
- Work Benches



BFX™ ALL-PURPOSE CLEANER

VALUE PERFORMANCE

PROPERTIES

Appearance/physical state	Liquid	Color	Colourless to light yellow
Odor	Sassafrass	Vapor pressure	17.5 mm Hg @ 20 °C
Evaporation rate	1 BuAc	Vapor density	>1
Boiling point °F(°C)	212 °F (100 °C)	Flash point °F(°C)	None
Specific gravity (water=1)	1.02 @ 20 °C	Flash point method	Tag-Closed Cup
VOCs	0%	Chemical base	Alkaline, aqueous solution
Flammable limits (estimated)	Not Established	Viscosity	1 cSt @ 20 °C
Volatiles	99%	Solubility in water	100%
Density	8.50 lb/gal estimated	pH	11.8
HMIS 1996	1, 0, 0	NFPA	1, 0, 0
HMIS III	1, 0, 0		

HANDLING

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure. Do not get this material on clothing. Do not use in areas without adequate ventilation. Wear personal protective equipment. Observe good industrial hygiene practices. Wash thoroughly after handling. Use care in handling/storage. Conditions for safe storage, including any incompatibilities. Keep tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Use care in handling/storage.

DISPOSAL

This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

DIRECTIONS

Turn red nozzle to spray or stream position. Pull trigger to spray. BFX is also available in bulk sizes.

STORAGE

Avoid discharge into water courses or onto the ground. Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : WWW.LPSLABS.COM

LPS® Laboratories • An Illinois Tool Works Company

4647 Hugh Howell Road • Tucker, GA 30084 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2014 LPS® Laboratories • LPS® and BFX™ are registered trademarks of Illinois Tool Works • All Rights Reserved • Form #TDS_BFX • Rev. 7/2014