

# MasterEmaco S 488CI

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/05/2020

 2.0
 12/31/2020
 000000243937
 Date of first issue: 06/05/2020

#### **SECTION 1. IDENTIFICATION**

Emergency telephone

Product name : MasterEmaco S 488CI

Product code : 00000000057546592 00000000057546592

Manufacturer or supplier's details

Company name of supplier : Master Builders-Admixtures US,LLC

Address : 23700 CHAGRIN BLVD Beachwood OH 44122

ChemTel: +1-813-248-0585 USA: +1-800-255-3924 Contract

Number MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### GHS classification in accordance with 29 CFR 1910.1200

Serious eye damage/eye

irritation

Category 1

Skin corrosion/irritation : Category 2

Carcinogenicity (Inhalation) : Category 1A (Lung)

Specific target organ toxicity

- single exposure

Category 3 (respiratory tract irritation)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 1 (Lung)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 2 (Kidney, Immune system)

### **GHS** label elements

Hazard pictograms







Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.

H315 Causes skin irritation.

H350i May cause cancer by inhalation. H335 May cause respiratory irritation.

H372 Causes damage to organs (lung) through prolonged or

repeated exposure (inhalation).

H373 May cause damage to organs (Kidney, Immune system)

through prolonged or repeated exposure if inhaled.



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/05/2020

 2.0
 12/31/2020
 000000243937
 Date of first issue: 06/05/2020

Precautionary Statements

### Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P201 Obtain special instructions before use.

P271 Use only outdoors or in a well-ventilated area.

P260 Do not breathe dust or mist.

P202 Do not handle until all safety precautions have been read and understood.

P270 Do not eat, drink or smoke when using this product. P264 Wash face, hands and any exposed skin thoroughly after handling.

### Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/ physician. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P362 + P364 Take off contaminated clothing and wash it before reuse.

#### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

### Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

### Other hazards

None known.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : modified cement mortar

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Cement, portland, chemicals	65997-15-1	>= 25 - < 75
crystalline silica	14808-60-7	>= 25 - < 75
Silicon dioxide	7631-86-9	>= 1 - < 15
Iron oxide	1309-37-1	>= 0 - < 7
Limestone	1317-65-3	>= 0 - < 5
Calcium sulphate	7778-18-9	>= 0 - < 5
calcium oxide	1305-78-8	>= 1 - < 5
2,2-dimethylpropane-1,3-diol	126-30-7	>= 0.3 - < 3
magnesium oxide	1309-48-4	>= 0 - < 3
Gypsum (Ca(SO4).2H2O)	13397-24-5	>= 0 - < 3
sodium nitrite	7632-00-0	>= 0 - < 1

Version **Revision Date:** SDS Number: Date of last issue: 06/05/2020 000000243937 Date of first issue: 06/05/2020 2.0 12/31/2020

#### **SECTION 4. FIRST AID MEASURES**

General advice Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled After inhalation of dust.

Keep patient calm, remove to fresh air.

If difficulties occur: Seek medical attention.

In case of skin contact After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

Hold eyes open and rinse slowly and gently with water for 15 In case of eye contact

to 20 minutes. Remove contact lenses, if present, after first 5

minutes, then continue rinsing.

If eye irritation persists, consult a specialist.

If swallowed Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Do not induce vomiting unless told to by a poison control cen-

ter or doctor.

Most important symptoms and effects, both acute and

delayed

Notes to physician

Eye damage Skin irritation

Treat symptomatically.

# **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Foam

> Water spray Dry powder

Carbon dioxide (CO2)

Product itself is non-combustible. Only the packaging materials can catch fire. The extinguishing agents normally used are

sufficient.

Unsuitable extinguishing

media

water jet

Specific hazards during fire

fighting

Product is not combustible or explosive.

Exposure to decomposition products may be a hazard to

health.

Hazardous combustion prod- :

ucts

harmful vapours

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

# **SECTION 6. ACCIDENTAL RELEASE MEASURES**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/05/2020

 2.0
 12/31/2020
 000000243937
 Date of first issue: 06/05/2020

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Avoid dust formation. Avoid breathing dust.

Ensure adequate ventilation.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Sweep up and shovel into suitable containers for disposal.

Avoid dust formation.
Rinse with plenty of water.

Keep in suitable, closed containers for disposal.

### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against :

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling : Avoid formation of respirable particles.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Containers should be stored tightly sealed in a dry place.

Materials to avoid : Segregate from metals.

Segregate from acids and bases.

Segregate from oxidants.

Segregate from foods and animal feeds.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	



# MasterEmaco S 488CI

Quartz (SiO2)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV
		TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		REL value (Respirable dust)	0.05 mg/m3	NIOSH
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (respir- able dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m3	OSHA CARC
		TWA (Res- pirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
Cement, portland, chemicals	65997-15-1	TWA value (Respirable fraction)	1 mg/m3	ACGIHTLV
		REL value (Total)	10 mg/m3	NIOSH
		REL value (Respirable)	5 mg/m3	NIOSH
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value	50 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
		TWA (Res- pirable par- ticulate mat-	1 mg/m3	ACGIH



# MasterEmaco S 488CI

	1	ter)	1	I
		TWA (Res-	5 mg/m3	NIOSH REL
		pirable)	l a mg/ma	
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total	15 mg/m3	OSHA Z-1
		dust) `	J	
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Dust)	50 Million parti- cles per cubic foot	OSHA Z-3
calcium oxide	1305-78-8	TWA value	2 mg/m3	ACGIHTLV
		REL value	2 mg/m3	NIOSH
		PEL	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	2 mg/m3	ACGIH
		TWA	2 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0
Gypsum (Ca(SO4).2H2O)	13397-24-5	TWA value (Inhalable fraction)	10 mg/m3	ACGIHTLV
		REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Res- pirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1



# MasterEmaco S 488CI

		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Inhal- able particu- late matter)	10 mg/m3 (Calcium)	ACGIH
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Silica, amorphous, fumed, crystfree	112945-52-5	REL value	6 mg/m3	NIOSH
		TWA value	0.8 mg/m3	29 CFR 1910.1000 (Table Z-3)
		TWA value	20 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
		TWA (Dust)	20 Million parti- cles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA	6 mg/m3	NIOSH REL



# MasterEmaco S 488CI

			(Silica)	
Iron oxide	1309-37-1	TWA value (Respirable fraction)	5 mg/m3	ACGIHTLV
		REL value (Dust and fume)	5 mg/m3 (iron (Fe))	NIOSH
		PEL (fumes/smok e)	10 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (fumes/smok e)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Respirable particulate matter)	5 mg/m3	ÀCGIH
		TWA (dust and fume)	5 mg/m3 (Iron)	NIOSH REL
		TWA (Fumes)	10 mg/m3	OSHA Z-1
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
	4000 40 4	TWA (Fumes)	10 mg/m3	OSHA PO
magnesium oxide	1309-48-4	TWA value (Inhalable fraction)	10 mg/m3	ACGIHTLV
		PEL (Total particulate)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total partic- ulate)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Inhal- able particu- late matter)	10 mg/m3	ACGIH
		TWA (fume, total particu- late)	15 mg/m3	OSHA Z-1
		TWA (Fume - total particu- late)	10 mg/m3	OSHA P0
Calcium sulphate	7778-18-9	TWA value (Inhalable fraction)	10 mg/m3	ACGIHTLV
		REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/05/2020

 2.0
 12/31/2020
 000000243937
 Date of first issue: 06/05/2020

		(Table Z-1)
PEL (Total	15 mg/m3	29 CFR
dust)		1910.1000
		(Table Z-1)
TWA value	5 mg/m3	29 CFR
(Respirable		1910.1000
fraction)		(Table Z-1-A)
TWA value	15 mg/m3	29 CFR
(Total dust)		1910.1000
		(Table Z-1-A)
TWA (Res-	5 mg/m3	NIOSH REL
pirable)		
TWA (total)	10 mg/m3	NIOSH REL
TWA (total	15 mg/m3	OSHA Z-1
dust)		
TWA (respir-	5 mg/m3	OSHA Z-1
able fraction)		
TWA (Total	15 mg/m3	OSHA P0
dust)	- / -	00114 50
TWA (respir-	5 mg/m3	OSHA P0
able dust		
fraction)	40/0	400111
TWA (Inhal-	10 mg/m3	ACGIH
able particu-	(Calcium)	
late matter)		

**Engineering measures** : Provide local exhaust ventilation to maintain recommended

P.E.L.

Personal protective equipment

Respiratory protection : Breathing protection if dusts are formed.

Wear a NIOSH-certified (or equivalent) particulate respirator.

Hand protection

Remarks : Chemical resistant protective gloves Manufacturer's direc-

tions for use should be observed because of great diversity of

types.

Eye protection : Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Eye wash bottle with pure water

Skin and body protection : Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Protective measures : Avoid contact with the skin, eyes and clothing.

Avoid inhalation of dusts.

In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene

and safety practice.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**



# MasterEmaco S 488CI

Version Revision Date: SDS Number: Date of last issue: 06/05/2020 2.0 12/31/2020 000000243937 Date of first issue: 06/05/2020

Appearance : powder

Color : dark gray

Odor : faint, earthy

Odor Threshold : Not determined due to potential health hazard by inhalation.

pH : approx. 12 - 13 (68 °F / 20 °C)

(as aqueous suspension)

Melting temperature : > 1,832 °F / > 1,000 °C

Boiling point : Not applicable

Flash point : Not applicable

Evaporation rate : The product is a non-volatile solid.

Flammability (solid, gas) : not flammable

Upper explosion limit / Upper

flammability limit

As a result of our experience with this product and our

knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance

with the intended use.

Lower explosion limit / Lower

flammability limit

As a result of our experience with this product and our

knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance

with the intended use.

Vapor pressure : No data available

Relative vapor density : The product is a non-volatile solid.

Bulk density : approx. 1.23 g/cm3

Solubility(ies)

Water solubility : dispersible  $(68 \, ^{\circ}\text{F} \, / \, 20 \, ^{\circ}\text{C})$ 

Solubility in other solvents : No applicable information available.

Viscosity

Viscosity, dynamic : Not applicable

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : not fire-propagating

Self-heating substances : No data available

Sublimation point : No applicable information available.



# MasterEmaco S 488CI

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/05/2020

 2.0
 12/31/2020
 000000243937
 Date of first issue: 06/05/2020

Molecular weight : No applicable information available.

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac- : No decomposition if stored and applied as directed.

ions

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong bases

Strong acids

Hazardous decomposition : No hazardous decomposition products if stored and handled

products as prescribed/indicated.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Acute toxicity**

Not classified based on available information.

#### Skin corrosion/irritation

Causes skin irritation.

## Serious eye damage/eye irritation

Causes serious eye damage.

# Respiratory or skin sensitization

### Skin sensitization

Not classified based on available information.

### Respiratory sensitization

Not classified based on available information.

#### **Product:**

Remarks : Chromate in this product has been reduced. Sensitization due

to chromate within stated shelf-live is unlikely.

# Germ cell mutagenicity

Not classified based on available information.

## Carcinogenicity

May cause cancer by inhalation.

# Reproductive toxicity

Not classified based on available information.

#### STOT-single exposure

May cause respiratory irritation.

### STOT-repeated exposure

Causes damage to organs (Lung) through prolonged or repeated exposure if inhaled. May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.



# MasterEmaco S 488CI

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/05/2020

 2.0
 12/31/2020
 000000243937
 Date of first issue: 06/05/2020

#### **Aspiration toxicity**

Not classified based on available information.

#### **Further information**

**Product:** 

Remarks : The product has not been tested. The statement has been

derived from the properties of the individual components.

#### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

### **Product:**

### **Ecotoxicology Assessment**

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

# Persistence and degradability

**Product:** 

Biodegradability : Remarks: Not applicable for inorganic substances.

### **Components:**

sodium nitrite:

Biodegradability : Remarks: Not applicable

Stability in water : Remarks: Not applicable

### Bioaccumulative potential

**Product:** 

Bioaccumulation : Remarks: No data available.

### **Components:**

### 2,2-dimethylpropane-1,3-diol:

Partition coefficient: n- : log Pow: -0.15 (77 °F / 25 °C)

octanol/water Method: Partition coefficient (n-octanol/water), Shake-flask

method GLP: no

sodium nitrite:

Partition coefficient: n-

octanol/water

Remarks: Study scientifically not justified.

## Mobility in soil

#### **Product:**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/05/2020

 2.0
 12/31/2020
 000000243937
 Date of first issue: 06/05/2020

Distribution among environmental compartments  Remarks: Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater is not expected.

The substance will not evaporate into the atmosphere from

the water surface.

### Other adverse effects

#### **Product:**

Results of PBT and vPvB

assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional ecological infor-

mation

: There is a high probability that the product is not acutely

harmful to aquatic organisms.

The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

### **Disposal methods**

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater. Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

# **SECTION 14. TRANSPORT INFORMATION**

### International Regulations

#### **UNRTDG**

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

# **Domestic regulation**

### **49 CFR**

Not regulated as a dangerous good

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/05/2020

 2.0
 12/31/2020
 000000243937
 Date of first issue: 06/05/2020

#### **SECTION 15. REGULATORY INFORMATION**

# **EPCRA - Emergency Planning and Community Right-to-Know**

### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
sodium nitrite	7632-00-0	100	49751

### **US State Regulations**

# Pennsylvania Right To Know

calcium oxide	1305-78-8
Iron oxide	1309-37-1
magnesium oxide	1309-48-4
Limestone	1317-65-3
Silicon dioxide	7631-86-9
Calcium sulphate	7778-18-9
Gypsum (Ca(SO4).2H2O)	13397-24-5
Quartz (SiO2)	14808-60-7
Cement, portland, chemicals	65997-15-1

# **New Jersey Right To Know**

calcium oxide	1305-78-8
Iron oxide	1309-37-1
magnesium oxide	1309-48-4
Limestone	1317-65-3
Calcium sulphate	7778-18-9
Quartz (SiO2)	14808-60-7
Cement, portland, chemicals	65997-15-1

### California Prop. 65

WARNING: This product can expose you to chemicals including Quartz (SiO2), which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

### The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed as

active on the TSCA Inventory or are in compliance with a

TSCA Inventory exemption.

### **TSCA list**

The following substance(s) is/are subject to a Significant New Use Rule: sodium nitrite 7632-00-0


# **SECTION 16. OTHER INFORMATION**

### **Further information**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/05/2020

 2.0
 12/31/2020
 000000243937
 Date of first issue: 06/05/2020

#### NFPA 704:



Special hazard

### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

29 CFR 1910.1000 (Table Z- : OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000

3)

29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR

1910.1001-1050)

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

3) / TWA value

29 CFR 1910.1001-1050 / : OSHA Action level:

OSHA Action level

29 CFR 1910.1001-1050 / : Time Weighted Average (TWA):

TWA value

ACGIH / TWA : 8-hour, time-weighted average
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/05/2020

 2.0
 12/31/2020
 000000243937
 Date of first issue: 06/05/2020

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan): ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date : 12/31/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE



# MasterEmaco S 488CI

Version Revision Date: SDS Number: Date of last issue: 06/05/2020 2.0 12/31/2020 000000243937 Date of first issue: 06/05/2020

, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN