

## MasterSeal HLM 5000TRGR

Version 1.0      Revision Date: 07/20/2020      SDS Number: 000000260791      Date of last issue: -  
Date of first issue: 07/20/2020

---

**SECTION 1. IDENTIFICATION**

Product name : MasterSeal HLM 5000TRGR  
Product code : 00000000051677373 00000000051677373

**Manufacturer or supplier's details**

Company name of supplier : Master Builders-Admixtures US,LLC  
Address : 23700 CHAGRIN BLVD  
Beachwood OH 44122  
Emergency telephone : ChemTel: +1-813-248-0585 USA: +1-800-255-3924 Contract  
Number MIS9240420

**Recommended use of the chemical and restrictions on use**

Recommended use : Product for construction chemicals  
Restrictions on use : Reserved for industrial and professional use.

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

FLAMMABLE LIQUIDS : 3  
Skin corrosion/irritation : 2  
Serious eye damage/eye irritation : 1  
Carcinogenicity : 2  
Reproductive toxicity : 1B  
Reproductive toxicity : 1B  
Specific target organ toxicity : 1 (Central nervous system)  
- repeated exposure

**GHS label elements**

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapour.  
H318 Causes serious eye damage.  
H315 Causes skin irritation.  
H351 Suspected of causing cancer.  
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.  
H360 May damage fertility or the unborn child.

Precautionary Statements : **Prevention:**

## MasterSeal HLM 5000TRGR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/20/2020	000000260791	Date of first issue: 07/20/2020

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P201 Obtain special instructions before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe dust or mist.  
P202 Do not handle until all safety precautions have been read and understood.  
P243 Take action to prevent static discharges.  
P241 Use explosion-proof [electrical/ ventilating/ lighting/ .?] equipment.  
P270 Do not eat, drink or smoke when using this product.  
P264 Wash face, hands and any exposed skin thoroughly after handling.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P242 Use only non-sparking tools.

**Response:**

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.  
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

**Storage:**

P405 Store locked up.  
P403 + P235 Store in a well-ventilated place. Keep cool.

**Disposal:**

P501 Dispose of contents/container to appropriate hazardous waste collection point.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : No data available.

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Solvent naphtha (petroleum), light arom.	64742-95-6	>= 0.3 - < 3
calcium oxide	1305-78-8	>= 7 - < 10
Stoddard solvent	8052-41-3	>= 5 - < 10
toluene-2,6-diisocyanate	91-08-7	>= 0.1 - < 0.2
dibutyltin dilaurate	77-58-7	>= 0.2 - < 0.3
talc	14807-96-6	>= 25 - < 50

## MasterSeal HLM 5000TRGR

Version 1.0      Revision Date: 07/20/2020      SDS Number: 000000260791      Date of last issue: -  
 Date of first issue: 07/20/2020

Asphalt	8052-42-4	$\geq 5 - < 15$
Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100oF (19cSt at 40 oC). It contains relatively few normal paraffins.]	64742-52-5	$\geq 3 - < 7$

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
 Consult a physician.  
 Show this material safety data sheet to the doctor in attendance.  
 Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
 If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.  
 If on skin, rinse well with water.  
 If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
 In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
 Continue rinsing eyes during transport to hospital.  
 Remove contact lenses.  
 Protect unharmed eye.  
 Keep eye wide open while rinsing.  
 If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
 Do NOT induce vomiting.  
 Do not give milk or alcoholic beverages.  
 Never give anything by mouth to an unconscious person.  
 If symptoms persist, call a physician.  
 Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : None known.
- Notes to physician : Treat symptomatically.

## SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam  
 Water spray  
 Dry powder  
 Carbon dioxide (CO<sub>2</sub>)

## MasterSeal HLM 5000TRGR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/20/2020	000000260791	Date of first issue: 07/20/2020

- 
- |  |   |   |
|--|---|---|
| Unsuitable extinguishing media                 | : | High volume water jet   |
| Specific hazards during fire fighting          | : | Do not allow run-off from fire fighting to enter drains or water courses.   |
| Further information                            | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains.<br>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.<br>For safety reasons in case of fire, cans should be stored separately in closed containments.<br>Use a water spray to cool fully closed containers. |
| Special protective equipment for fire-fighters | : | Wear self-contained breathing apparatus for firefighting if necessary.  |
- 

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- |   |   |   |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | Use personal protective equipment.<br>Remove all sources of ignition.<br>Evacuate personnel to safe areas.<br>Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.               |
| Environmental precautions   | : | Prevent product from entering drains.<br>Prevent further leakage or spillage if safe to do so.<br>If the product contaminates rivers and lakes or drains inform respective authorities.   |
| Methods and materials for containment and cleaning up               | : | Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). |
- 

**SECTION 7. HANDLING AND STORAGE**

- |   |   |  |
|---|---|--|
| Advice on protection against fire and explosion | : | Do not spray on a naked flame or any incandescent material.<br>Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).<br>Keep away from open flames, hot surfaces and sources of ignition.  |
| Advice on safe handling                         | : | Avoid formation of aerosol.<br>Do not breathe vapors/dust.<br>Avoid exposure - obtain special instructions before use.<br>Avoid contact with skin and eyes.<br>For personal protection see section 8.<br>Smoking, eating and drinking should be prohibited in the application area.<br>Take precautionary measures against static discharges.<br>Provide sufficient air exchange and/or exhaust in work rooms.<br>Open drum carefully as content may be under pressure.<br>To avoid spills during handling keep bottle on a metal tray.<br>Dispose of rinse water in accordance with local and national regulations. |

## MasterSeal HLM 5000TRGR

Version 1.0      Revision Date: 07/20/2020      SDS Number: 000000260791      Date of last issue: -  
Date of first issue: 07/20/2020

- Conditions for safe storage : no smoking  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep container tightly closed and in a well-ventilated place.  
Keep away from heat.  
Avoid all sources of ignition: heat, sparks, open flame.
- Materials to avoid : Segregate from foods and animal feeds.
- Further information on storage stability : No decomposition if stored and applied as directed.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
dibutyltin dilaurate	77-58-7	TWA value	0.1 mg/m <sup>3</sup> (tin (Sn))	ACGIHTLV
		STEL value	0.2 mg/m <sup>3</sup> (tin (Sn))	ACGIHTLV
		REL value	0.1 mg/m <sup>3</sup> (tin (Sn))	NIOSH
		PEL	0.1 mg/m <sup>3</sup> (tin (Sn))	29 CFR 1910.1000 (Table Z-1)
		TWA value	0.1 mg/m <sup>3</sup> (tin (Sn))	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.1 mg/m <sup>3</sup> (Tin)	OSHA Z-1
		TWA	0.1 mg/m <sup>3</sup> (Tin)	ACGIH
		STEL	0.2 mg/m <sup>3</sup> (Tin)	ACGIH
		TWA	0.1 mg/m <sup>3</sup> (Tin)	OSHA P0
		TWA	0.1 mg/m <sup>3</sup> (Tin)	NIOSH REL
toluene-2,6-diisocyanate	91-08-7	STEL value (Inhalable fraction and vapor)	0.005 ppm	ACGIHTLV
		Skin Designation (Inhalable fraction and vapor)		ACGIHTLV

## MasterSeal HLM 5000TRGR

Version 1.0      Revision Date: 07/20/2020      SDS Number: 000000260791      Date of last issue: -  
 Date of first issue: 07/20/2020

		TWA value (Inhalable fraction and vapor)	0.001 ppm	ACGIHTLV
		C	0.02 ppm 0.14 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable fraction and vapor)	0.001 ppm	ACGIH
		STEL (Inhalable fraction and vapor)	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.04 mg/m <sup>3</sup>	OSHA P0
		STEL	0.02 ppm 0.15 mg/m <sup>3</sup>	OSHA P0
calcium oxide	1305-78-8	TWA value	2 mg/m <sup>3</sup>	ACGIHTLV
		REL value	2 mg/m <sup>3</sup>	NIOSH
		PEL	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		TWA value	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA	2 mg/m <sup>3</sup>	ACGIH
		TWA	2 mg/m <sup>3</sup>	NIOSH REL
		TWA	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA	5 mg/m <sup>3</sup>	OSHA P0
Asphalt	8052-42-4	TWA value (Inhalable fraction)	0.5 mg/m <sup>3</sup> (benzene solubles)	ACGIHTLV
		Ceil_Time (fumes/smoke)	5 mg/m <sup>3</sup>	NIOSH
		TWA value (Inhalable fume)	0.5 mg/m <sup>3</sup> (benzene solubles)	ACGIHTLV
		TWA (Fume, inhalable fraction)	0.5 mg/m <sup>3</sup> (benzene soluble aerosol)	ACGIH
		C (Fumes)	5 mg/m <sup>3</sup>	NIOSH REL
talc	14807-96-6	TWA value (Respirable fraction)	2 mg/m <sup>3</sup>	ACGIHTLV
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (respirable dust fraction)	2 mg/m <sup>3</sup>	OSHA P0
		TWA (Respirable)	2 mg/m <sup>3</sup>	NIOSH REL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA (Res-	2 mg/m <sup>3</sup>	ACGIH

## MasterSeal HLM 5000TRGR

Version 1.0      Revision Date: 07/20/2020      SDS Number: 000000260791      Date of last issue: -  
 Date of first issue: 07/20/2020

		pirable particulate matter)		
Stoddard solvent	8052-41-3	TWA value	100 ppm	ACGIHTLV
		REL value	350 mg/m3	NIOSH
		Ceil_Time	1,800 mg/m3	NIOSH
		PEL	500 ppm 2,900 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 525 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		C	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0
Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100oF (19cSt at 40 oC). It contains relatively few normal paraffins.]	64742-52-5	TWA value (Inhalable fraction)	5 mg/m3	ACGIHTLV
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

**Engineering measures** : No applicable information available.

**Personal protective equipment**

Respiratory protection : Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

## MasterSeal HLM 5000TRGR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/20/2020	000000260791	Date of first issue: 07/20/2020

Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Protective measures	:	Avoid inhalation of dusts/mists/vapours. Avoid contact with the skin, eyes and clothing. Avoid prolonged and/or repeated contact with the skin. Handle in accordance with good building materials hygiene and safety practice.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	:	liquid
Color	:	black
pH	:	neutral to slightly alkaline
Boiling range	:	307.99 - 700.00 °F / 153.33 - 371.11 °C
Flash point	:	123 °F / 51 °C  Method: Standard Method of Test for Flash Point by Setafash Closed Tester
Evaporation rate	:	No applicable information available.
Flammability (solid, gas)	:	Flammable. Method: derived from flash point
Upper explosion limit / Upper flammability limit	:	7.0 %(V)
Lower explosion limit / Lower flammability limit	:	0.9 %(V)
Vapor pressure	:	No data available
Relative vapor density	:	Heavier than air.
Relative density	:	No applicable information available.
Density	:	approx. 10.8 lb/USg (72 °F / 22 °C)
Bulk density	:	900 - 1,600 kg/m <sup>3</sup>
Solubility(ies)	:	
Water solubility	:	slightly soluble
Solubility in other solvents	:	No applicable information available.
Partition coefficient: n-octanol/water	:	No data available.
Autoignition temperature	:	No data available



## MasterSeal HLM 5000TRGR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/20/2020	000000260791	Date of first issue: 07/20/2020

---

Decomposition temperature : Vapors may form explosive mixture with air.  
No decomposition if stored and handled as prescribed/indicated.

Viscosity

    Viscosity, dynamic : No data available.

    Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive  
Not explosive

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.  
Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Causes serious eye damage.

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

## MasterSeal HLM 5000TRGR

Version 1.0      Revision Date: 07/20/2020      SDS Number: 000000260791      Date of last issue: -  
Date of first issue: 07/20/2020

---

**Carcinogenicity**

Suspected of causing cancer.

**Reproductive toxicity**

May damage fertility or the unborn child.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration hazard expected.

**Further information****Product:**

Remarks : Solvents may degrease the skin.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential****Components:****Solvent naphtha (petroleum), light arom.:**

Partition coefficient: n-octanol/water : log Pow: 3.17  
Method: other (calculated)  
GLP: no

**calcium oxide:**

Partition coefficient: n-octanol/water : Remarks: The value has not been determined because the substance is inorganic.

**Stoddard solvent:**

Partition coefficient: n-octanol/water : log Pow: 3.5 - 6.4 (68 °F / 20 °C)  
Method: Partition coefficient (n-octanol/water), HPLC method.

**toluene-2,6-diisocyanate:**

Partition coefficient: n-octanol/water : log Pow: 3.74  
Method: other (calculated)

## MasterSeal HLM 5000TRGR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/20/2020	000000260791	Date of first issue: 07/20/2020

---

**dibutyltin dilaurate:**

Partition coefficient: n-octanol/water : log Pow: 3.17 (69.4 °F / 20.8 °C)  
 pH: 6.1 - 6.3  
 Method: Partition coefficient (n-octanol/water), Shake-flask method  
 GLP: yes

**talc:**

Partition coefficient: n-octanol/water : Remarks: not applicable

**Asphalt:**

Partition coefficient: n-octanol/water : Remarks: not applicable

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms.  
 The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.  
 Dispose of in accordance with national, state and local regulations.  
 Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 1263  
 Proper shipping name : PAINT  
 Class : 3  
 Packing group : III  
 Labels : 3

**IATA-DGR**

UN/ID No. : UN 1263  
 Proper shipping name : PAINT  
 Class : 3

## MasterSeal HLM 5000TRGR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/20/2020	000000260791	Date of first issue: 07/20/2020

Packing group : III  
 Labels : Flammable Liquids  
 Packing instruction (cargo aircraft) : 366  
 Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 1263  
 Proper shipping name : PAINT  
 Class : 3  
 Packing group : III  
 Labels : 3  
 EmS Code : F-E, S-E  
 Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

UN/ID/NA number : UN 1263  
 Proper shipping name : PAINT, COMBUSTIBLE LIQUID  
 Class : C  
 Packing group : III  
 Labels : Combustible Liquid  
 ERG Code : 128  
 Marine pollutant : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**SECTION 15. REGULATORY INFORMATION**

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

toluene-2,6-diisocyanate 91-08-7

**US State Regulations****Pennsylvania Right To Know**

calcium oxide	1305-78-8
Asphalt	8052-42-4
talc	14807-96-6
Stoddard solvent	8052-41-3
Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20	64742-52-5

## MasterSeal HLM 5000TRGR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/20/2020	000000260791	Date of first issue: 07/20/2020

---

through C50 and produces a finished oil of at least 100 SUS at 100oF (19cSt at 40 oC). It contains relatively few normal paraffins.]

4-methyl-m-phenylene diisocyanate 584-84-9

**New Jersey Right To Know**

calcium oxide 1305-78-8

talc 14807-96-6

Stoddard solvent 8052-41-3

Distillates (petroleum), hydrotreated heavy naphthenic; 64742-52-5

Baseoil — unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100oF (19cSt at 40 oC). It contains relatively few normal paraffins.]

toluene-2,6-diisocyanate 91-08-7

**California Prop. 65**

WARNING: This product can expose you to chemicals including toluene-2,6-diisocyanate, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The ingredients of this product are reported in the following inventories:**


TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

**SECTION 16. OTHER INFORMATION****Further information**


**MasterSeal HLM 5000TRGR**

Version 1.0      Revision Date: 07/20/2020      SDS Number: 000000260791      Date of last issue: -  
 Date of first issue: 07/20/2020

**NFPA 704:**



**HMIS® IV:**



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- 29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):
- 29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- ACGIHTLV / Skin Designation : Skin Designation:
- ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):
- ACGIHTLV / TWA value : Time Weighted Average (TWA):
- NIOSH / Ceil\_Time : Ceiling Limit Value and Time Period (if specified):
- NIOSH / REL value : Recommended exposure limit (REL):
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
- NIOSH REL / C : Ceiling value not be exceeded at any time.
- OSHA P0 / TWA : 8-hour time weighted average

## MasterSeal HLM 5000TRGR

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/20/2020	000000260791	Date of first issue: 07/20/2020

OSHA P0 / STEL	:	Short-term exposure limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-1 / C	:	Ceiling
OSHA Z-3 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/20/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO

**MasterSeal HLM 5000TRGR**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07/20/2020	000000260791	Date of first issue: 07/20/2020

---

DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN