

MasterSeal P 222

Version Revision Date: SDS Number: Date of last issue: -
1.0 09/02/2020 000000631960 Date of first issue: 09/02/2020

SECTION 1. IDENTIFICATION

Product name : MasterSeal P 222
Product code : 000000000050394883 000000000050394883
Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Master Builders Solutions Canada Inc.
Address : 1800 CLARK BLVD
 Brampton ON L6T 4M7
Emergency telephone : ChemTel: +1-813-248-0585;

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.


SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

FLAMMABLE LIQUIDS : 2
Acute toxicity (Inhalation) : 4
Skin corrosion/irritation : 2
Serious eye damage/eye irritation : Category 2A
Respiratory sensitization : Category 1
Skin sensitization : Category 1
Reproductive toxicity : 2
Specific target organ toxicity : 3
- single exposure
Specific target organ toxicity : 2 (Lung, Auditory organ)
- repeated exposure
Short-term (acute) aquatic hazard : 3

GHS label elements

MasterSeal P 222

Version 1.0 Revision Date: 09/02/2020 SDS Number: 000000631960 Date of last issue: -
 Date of first issue: 09/02/2020

- Hazard pictograms : 
- Signal Word : Danger
- Hazard Statements : H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H315 Causes skin irritation.
 H332 Harmful if inhaled.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.
 H361d Suspected of damaging the unborn child.
 H373 May cause damage to organs (Lung, Auditory organ) through prolonged or repeated exposure.
 H402 Harmful to aquatic life.
- Precautionary Statements : **Prevention:**
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P271 Use only outdoors or in a well-ventilated area.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe dust or mist.
 P243 Take action to prevent static discharges.
 P273 Avoid release to the environment.
 P284 In case of inadequate ventilation wear respiratory protection.
 P201 Obtain special instructions before use.
 P241 Use explosion-proof [electrical/ ventilating/ lighting/ .?] equipment.
 P202 Do not handle until all safety precautions have been read and understood.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P240 Ground and bond container and receiving equipment.
 P242 Use only non-sparking tools.
 P264 Wash face, hands and any exposed skin thoroughly after handling.
- Response:**
 P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P314 Get medical advice/ attention if you feel unwell.
 P332 + P313 If skin irritation occurs: Get medical advice/ atten-

MasterSeal P 222

Version 1.0 Revision Date: 09/02/2020 SDS Number: 000000631960 Date of last issue: -
 Date of first issue: 09/02/2020

tion.
 P362 + P364 Take off contaminated clothing and wash it before reuse.
 P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.
 P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Storage:

P233 Keep container tightly closed.
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No data available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
Methylethylketone	78-93-3	>= 10 - < 15
ethylbenzene	100-41-4	>= 3 - < 5
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	>= 10 - < 15
toluene	108-88-3	>= 0 - < 0.2
xylene	1330-20-7	>= 15 - < 20
methylenediphenyl diisocyanate	26447-40-5	>= 3 - < 10

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing. Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Do not leave the victim unattended.

If inhaled : Keep patient calm, remove to fresh air, seek medical attention.
 Call a physician or poison control center immediately. If unconscious, place in recovery position and seek medical advice.

In case of skin contact : Immediately wash thoroughly with soap and water, seek med-

MasterSeal P 222

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/02/2020	000000631960	Date of first issue: 09/02/2020

- ical attention.
- If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
- Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
- Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause respiratory irritation.
Suspected of damaging the unborn child.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Foam
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : nitrogen oxides
fumes/smoke
carbon black
vapor
isocyanate

MasterSeal P 222

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/02/2020	000000631960	Date of first issue: 09/02/2020

- Further information : Keep containers cool by spraying with water if exposed to fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.
- Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Special protective equipment for fire-fighters : Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.
- Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Clear area.
Ensure adequate ventilation.
Wear suitable personal protective clothing and equipment.
Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Do not discharge into drains/surface waters/groundwater.
- Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Dike spillage.
- Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
Use only explosion-proof equipment.
Keep away from open flames, hot surfaces and sources of ignition.

MasterSeal P 222

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/02/2020	000000631960	Date of first issue: 09/02/2020

- Advice on safe handling : Provide suitable exhaust ventilation at the processing machines.
Ensure thorough ventilation of stores and work areas.
Avoid aerosol formation.
When handling heated product, vapours of the product should be ventilated, and respiratory protection used.
Wear respiratory protection when spraying.
Danger of bursting when sealed gastight.
Protect against moisture.
If bulging of drum occurs, transfer to well ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.
- Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : no smoking
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.
- Materials to avoid : Observe VCI storage rules.
- Recommended storage temperature : 0 °C
- Further information on storage stability : Minimum storage temperature:

MasterSeal P 222

Version 1.0 Revision Date: 09/02/2020 SDS Number: 000000631960 Date of last issue: -
 Date of first issue: 09/02/2020

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Methylethylketone	78-93-3	STEL value	300 ppm	ACGIHTLV
		TWA value	200 ppm	ACGIHTLV
		REL value	200 ppm 590 mg/m3	NIOSH
		STEL value	300 ppm 885 mg/m3	NIOSH
		PEL	200 ppm 590 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	200 ppm 590 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		STEL value	300 ppm 885 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	200 ppm 590 mg/m3	CA AB OEL
		STEL	300 ppm 885 mg/m3	CA AB OEL
		TWA	50 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL
		TWAEV	50 ppm 150 mg/m3	CA QC OEL
		STEV	100 ppm 300 mg/m3	CA QC OEL
		TWA	200 ppm	ACGIH
STEL	300 ppm	ACGIH		
ethylbenzene	100-41-4	TWA value	20 ppm	ACGIHTLV
		STEL value	125 ppm 545 mg/m3	NIOSH
		REL value	100 ppm 435 mg/m3	NIOSH
		PEL	100 ppm 435 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 435 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		STEL value	125 ppm 545 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	100 ppm 434 mg/m3	CA AB OEL
		STEL	125 ppm 543 mg/m3	CA AB OEL
TWA	20 ppm	CA BC OEL		

SAFETY DATA SHEET

MasterSeal P 222

Version 1.0 Revision Date: 09/02/2020 SDS Number: 000000631960 Date of last issue: -
 Date of first issue: 09/02/2020

		STEV	125 ppm 543 mg/m3	CA QC OEL
		TWAEV	100 ppm 434 mg/m3	CA QC OEL
		TWA	20 ppm	ACGIH
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	TWA value	0.005 ppm	ACGIHTLV
		REL value	0.005 ppm 0.05 mg/m3	NIOSH
		Ceil_Time	0.020 ppm 0.2 mg/m3	NIOSH
		CLV	0.02 ppm 0.2 mg/m3	29 CFR 1910.1000 (Table Z-1)
		CLV	0.02 ppm 0.2 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.005 ppm 0.05 mg/m3	CA AB OEL
		TWA	0.005 ppm	CA BC OEL
		C	0.01 ppm	CA BC OEL
		TWA	0.005 ppm	CA ON OEL
		C	0.02 ppm	CA ON OEL
		TWAEV	0.005 ppm 0.051 mg/m3	CA QC OEL
		TWA	0.005 ppm	ACGIH
toluene	108-88-3	TWA value	20 ppm	ACGIHTLV
		REL value	100 ppm 375 mg/m3	NIOSH
		STEL value	150 ppm 560 mg/m3	NIOSH
		TWA value	100 ppm 375 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		STEL value	150 ppm 560 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		max. conc.	500 ppm	29 CFR 1910.1000 (Table Z-2)
		CLV	300 ppm	29 CFR 1910.1000 (Table Z-2)
		TWA value	200 ppm	29 CFR 1910.1000 (Table Z-2)
		TWA	50 ppm 188 mg/m3	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	50 ppm 188 mg/m3	CA QC OEL
		TWA	20 ppm	ACGIH
xylene	1330-20-7	TWA value	100 ppm	ACGIHTLV

MasterSeal P 222

Version 1.0 Revision Date: 09/02/2020 SDS Number: 000000631960 Date of last issue: -
 Date of first issue: 09/02/2020

		STEL value	150 ppm	ACGIHTLV
		PEL	100 ppm 435 mg/m ³	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 435 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		STEL value	150 ppm 655 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		REL value	100 ppm 435 mg/m ³	NIOSH
		STEL value	150 ppm 655 mg/m ³	NIOSH
		TWA	100 ppm 434 mg/m ³	CA AB OEL
		STEL	150 ppm 651 mg/m ³	CA AB OEL
		TWAEV	100 ppm 434 mg/m ³	CA QC OEL
		STEV	150 ppm 651 mg/m ³	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.
 When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and change out schedules are in place.
 For emergency or non-routine, high exposure situations, including confined space entry, use a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

Hand protection

Remarks : Chemical resistant protective gloves should be worn to prevent all skin contact. Suitable materials may include chloroprene rubber (Neoprene) nitrile rubber (Buna N) chlorinated polyethylene polyvinylchloride (Pylox) butyl rubber fluoroelastomer (Viton) depending upon conditions of use.
 The suitability for a specific workplace should be discussed with the producers of the protective gloves.

MasterSeal P 222

Version 1.0 Revision Date: 09/02/2020 SDS Number: 000000631960 Date of last issue: -
Date of first issue: 09/02/2020

- Eye protection : Tightly fitting safety goggles (chemical goggles).
Wear face shield if splashing hazard exists.
Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Cover as much of the exposed skin as possible to prevent all skin contact.
Suitable materials may include saran-coated material depending upon conditions of use.
Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Protective measures : Wear protective clothing as necessary to prevent contact.
Eye wash fountains and safety showers must be easily accessible.
Observe the appropriate PEL or TLV value.
- Hygiene measures : Wash soiled clothing immediately.
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : amber
- Odor : solvent
- Odor Threshold : No data available
- pH : neutral to slightly alkaline
- Melting point : No applicable information available.
- Freezing point : No applicable information available.
- boiling temperature : approx. 79.44 - 202.22 °C
- Flash point : 2.78 °C
- Evaporation rate : No applicable information available.

MasterSeal P 222

Version 1.0 Revision Date: 09/02/2020 SDS Number: 000000631960 Date of last issue: -
Date of first issue: 09/02/2020

Flammability (solid, gas) : Highly flammable.

Upper explosion limit / Upper flammability limit : 11.5 %(V)

Lower explosion limit / Lower flammability limit : 1.0 %(V)

Vapor pressure : No data available

Relative vapor density : Heavier than air.

Relative density : 1.04

Density : approx. 1.04 g/cm³ (20 °C)

Solubility(ies)
Water solubility : slightly soluble (20 °C)

Solubility in other solvents : No applicable information available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity
Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive
Not explosive

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : No data available

Metal corrosion rate : Corrosive effects to metal are not anticipated.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

MasterSeal P 222

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/02/2020	000000631960	Date of first issue: 09/02/2020

Incompatible materials	:	Strong acids Strong bases Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Harmful if inhaled.

Product:

Acute oral toxicity	:	ATE: > 5,000 mg/kg
Acute inhalation toxicity	:	ATE: 12.5 mg/l Remarks: Determined for vapor ATE: > 5.0000 mg/l Remarks: Determined for mist
Acute dermal toxicity	:	ATE: > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Product:

Remarks : Causes sensitization.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

MasterSeal P 222

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/02/2020	000000631960	Date of first issue: 09/02/2020

Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration hazard expected.

Further information**Product:**

Remarks : The product has not been tested. The statement has been derived from the properties of the individual components.

Remarks : Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential**Components:****Methylethylketone:**

Partition coefficient: n-octanol/water : log Pow: 0.29
Method: other (measured)
GLP: no data
Remarks: Information taken from reference works and the literature.

ethylbenzene:

Partition coefficient: n-octanol/water : Pow: 4,170 (20 °C)
log Pow: 3.6 (20 °C)
pH: 7.8
Method: Partition coefficient
GLP: yes

Diphenylmethane-4,4'-diisocyanate (MDI):

Partition coefficient: n-octanol/water : log Pow: 4.51 (22 °C)
pH: 7
Method: Partition coefficient (n-octanol/water), HPLC method.

MasterSeal P 222

Version 1.0 Revision Date: 09/02/2020 SDS Number: 000000631960 Date of last issue: -
Date of first issue: 09/02/2020

GLP: no

toluene:

Partition coefficient: n-octanol/water : log Pow: 2.73 (20 °C)
pH: 7
Method: other (measured)
GLP: no data
Remarks: Information taken from reference works and the literature.

xylene:

Partition coefficient: n-octanol/water : log Pow: 3.12 - 3.20 (25 °C)
Method: other (calculated)
GLP: no
Remarks: Information taken from reference works and the literature.

methylenediphenyl diisocyanate:

Partition coefficient: n-octanol/water : log Pow: 4.51 (22 °C)
pH: 7
Method: Partition coefficient (n-octanol/water), HPLC method.
GLP: no

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with national, state and local regulations.
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION**International Regulations**

MasterSeal P 222

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/02/2020	000000631960	Date of first issue: 09/02/2020

UNRTDG

UN number : UN 1993
 Proper shipping name : FLAMMABLE LIQUID, N.O.S.
 (XYLENE, DIPHENYLMETHANDIISOCYANATE, ISOMERES
 UND HOMOLOGUES)
 Class : 3
 Packing group : II
 Labels : 3

IATA-DGR

UN/ID No. : UN 1993
 Proper shipping name : FLAMMABLE LIQUID, N.O.S.
 (XYLENE, METHYLETHYLKETONE)
 Class : 3
 Packing group : II
 Labels : Flammable Liquids
 Packing instruction (cargo
 aircraft) : 364
 Packing instruction (passen-
 ger aircraft) : 353

IMDG-Code

UN number : UN 1993
 Proper shipping name : FLAMMABLE LIQUID, N.O.S.
 (XYLENE, METHYLETHYLKETONE)
 Class : 3
 Packing group : II
 Labels : 3
 EmS Code : F-E, S-E
 Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

UN number : UN 1993
 Proper shipping name : FLAMMABLE LIQUID, N.O.S.
 (XYLENE, METHYLETHYLKETONE)
 Class : 3
 Packing group : II
 Labels : 3
 ERG Code : 128
 Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**The ingredients of this product are reported in the following inventories:**

DSL : On the inventory, or in compliance with the inventory

MasterSeal P 222

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/02/2020	000000631960	Date of first issue: 09/02/2020

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A)	:	OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	:	OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
29 CFR 1910.1000 (Table Z-2)	:	OSHA Table Z-2 (Toxic and Hazardous Substances) 29 CFR 1910.1000
ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	:	American Conference of Governmental Industrial Hygienists - threshold limit values (US)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
NIOSH	:	NIOSH Pocket Guide to Chemical Hazards (US)
29 CFR 1910.1000 (Table Z-1-A) / CLV	:	Ceiling Limit Value:
29 CFR 1910.1000 (Table Z-1-A) / STEL value	:	Short Term Exposure Limit (STEL):
29 CFR 1910.1000 (Table Z-1-A) / TWA value	:	Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / CLV	:	Ceiling Limit Value:
29 CFR 1910.1000 (Table Z-1) / PEL	:	Permissible exposure limit
29 CFR 1910.1000 (Table Z-2) / CLV	:	Ceiling Limit Value:
29 CFR 1910.1000 (Table Z-2) / TWA value	:	Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-2) / max. conc.	:	Maximum concentration:
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIHTLV / STEL value	:	Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value	:	Time Weighted Average (TWA):
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA BC OEL / C	:	ceiling limit
CA ON OEL / C	:	Ceiling Limit (C)
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWA EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value
NIOSH / Ceil_Time	:	Ceiling Limit Value and Time Period (if specified):
NIOSH / REL value	:	Recommended exposure limit (REL):

MasterSeal P 222

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/02/2020	000000631960	Date of first issue: 09/02/2020

NIOSH / STEL value : Short Term Exposure Limit (STEL):

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 09/02/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED

MasterSeal P 222

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/02/2020	000000631960	Date of first issue: 09/02/2020

WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

CA / EN