## SAFETY DATA SHEET



Issuing Date 12-Nov-2014 Revision date 10-Aug-2018

#### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Sure Klean® Weather Seal Blok-Guard® & Graffiti Control 15

Other means of identification

Product Code(s) 40390 UN number UN1866

Recommended use of the chemical and restrictions on use

Recommended use Restricted to professional users.
Uses advised against No information available

Details of the supplier of the safety data sheet

**Manufacturer Address** 

PROSOCO, Inc. 3741 Greenway Circle Lawrence, Kansas 66046

Emergency telephone number

8:00 AM – 5:00 PM CST Monday-Friday 785-865-4200 NON-BUSINESS HOURS (INFOTRAC) 800-535-5053

#### 2. HAZARDS IDENTIFICATION

#### Classification

| Skin corrosion/irritation         | Category 2  |
|-----------------------------------|-------------|
| Serious eye damage/eye irritation | Category 2A |
| Carcinogenicity                   | Category 2  |
| Aspiration hazard                 | Category 1  |
| Flammable liquids                 | Category 3  |

#### Label elements

#### **Emergency Overview**

## Warning

#### Hazard statements

Causes skin irritation
Causes serious eye irritation
Suspected of causing cancer
May be fatal if swallowed and enters airways
Flammable liquid and vapor



Appearance clear Physical state Liquid Odor Petroleum

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/ /equipment

Use only non-sparking tools

Take precautionary measures against static discharge

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep cool

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Acetic acid vapors form as by-product following hydrolysis reaction with water or humid air.

#### Other information

- May be harmful if swallowed
- · May be harmful in contact with skin

No information available

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical name              | CAS No.    | Weight-% | Trade Secret |
|----------------------------|------------|----------|--------------|
| Mineral Spirits            | 64742-88-7 | 60 - 100 | *            |
| Polydimethyl siloxane diol | 70131-67-8 | 10 - 30  | *            |
| 1,2,4-trimethylbenzene     | 95-63-6    | 3 - 7    | *            |
| Xylene                     | 1330-20-7  | 1 - 5    | *            |
| Cumene                     | 98-82-8    | 0.1 - 1  | *            |
| Ethylbenzene               | 100-41-4   | 0.1 - 1  | *            |

<sup>\*</sup> The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. FIRST AID MEASURES

## **Description of first aid measures**

General advice In case of accident or unwellness, seek medical advice immediately (show directions for

use or safety data sheet if possible).

**Eye contact** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

persist, call a physician.

**Skin Contact** Wash off immediately with soap and plenty of water. If skin irritation persists, call a

physician.

**Inhalation**Move to fresh air in case of accidental inhalation of vapors or decomposition products. If

breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with

skin. Use barrier to give mouth-to-mouth resuscitation. Call a physician.

**Ingestion** Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water.

Never give anything by mouth to an unconscious person. Call a physician.

**Self-protection of the first aider** Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms May be fatal if swallowed and enters airways. Causes serious eye irritation. Causes skin

irritation. May be harmful if inhaled.

Indication of any immediate medical attention and special treatment needed

### 5. FIRE-FIGHTING MEASURES

#### Suitable Extinguishing Media

Use. Dry chemical. Carbon dioxide (CO2). Water spray (fog). Foam. Alcohol resistant foam.

Unsuitable Extinguishing Media Caution: Use of water spray when fighting fire may be inefficient.

#### Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

**Personal precautions** Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate

ventilation, especially in confined areas. Keep people away from and upwind of spill/leak. Pay attention to flashback. Take precautionary measures against static discharges. Use

personal protective equipment as required.

**Environmental precautions** 

**Environmental precautions** Prevent product from entering drains. Do not allow into any sewer, on the ground or into

any body of water. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later

disposal.

Methods for cleaning up

Dam up. Pick up and transfer to properly labeled containers. Soak up with inert absorbent material. Take precautionary measures against static discharges. Use only non-sparking tools. Ground and bond containers when transferring material.

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling

Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Use with local exhaust ventilation. Do not smoke. Use personal protection recommended in Section 8.

#### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away

from heat. Keep out of the reach of children.

**Incompatible materials** Incompatible with oxidizing agents.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure Guidelines** 

| Chemical name                     | ACGIH TLV                     | OSHA PEL  | NIOSH IDLH  |
|-----------------------------------|-------------------------------|---|---|
| 1,2,4-trimethylbenzene<br>95-63-6 |                               |   | TWA: 25 ppm<br>TWA: 125 mg/m <sup>3</sup>   |
| Xylene<br>1330-20-7               | STEL: 150 ppm<br>TWA: 100 ppm | TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m³ |   |
| Cumene<br>98-82-8                 | TWA: 50 ppm                   | TWA: 50 ppm TWA: 245 mg/m³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m³ (vacated) S* S*                                     | IDLH: 900 ppm<br>TWA: 50 ppm<br>TWA: 245 mg/m³                                      |
| Ethylbenzene<br>100-41-4          | TWA: 20 ppm                   | TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m³ | IDLH: 800 ppm<br>TWA: 100 ppm<br>TWA: 435 mg/m³<br>STEL: 125 ppm<br>STEL: 545 mg/m³ |

NIOSH IDLH Immediately Dangerous to Life or Health

Other information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

Engineering Controls Showers

Eyewash stations

Ventilation systems. Ground/bond container and receiving equipment.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Petroleum

**Skin and body protection** Wear protective gloves and protective clothing.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

Odor

provided in accordance with current local regulations.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical state Liquid
Appearance clear

Color colorless Odor threshold No information available

PropertyValuesRemarks • MethodpHNot ApplicableNot Applicable

pHNot ApplicableMelting point / freezing point °FNo information available

Boiling point / boiling range
Flash point

No information available
38 °C / 100 °F

Flash point

Evaporation rate

Flammability (solid, gas)

Flammability Limit in Air

38 °C / 100 °F

No information available

No information available

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available
No information available

Specific gravity .802 Water solubility negligible

Solubility in other solvents
Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity
No information available

**Explosive properties**Not Applicable
Oxidizing properties
Not Applicable

#### 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### **Chemical stability**

Stable under recommended storage conditions.

#### Possibility of hazardous reactions

None under normal processing.

#### **Conditions to avoid**

Heat, flames and sparks.

#### **Incompatible materials**

Incompatible with oxidizing agents.

#### **Hazardous decomposition products**

Acetic acid. silicon dioxide. Carbon oxides. Unidentified organic compounds.

#### 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Product Information May be fatal if swallowed and enters airways May be harmful by inhalation, ingestion, or

skin absorption

**Inhalation** Avoid breathing vapors or mists. May be harmful if inhaled. Aspiration into lungs can

produce severe lung damage.

**Eye contact** Avoid contact with eyes. Causes serious eye irritation.

**Skin Contact** Avoid contact with skin. Causes skin irritation.

**Ingestion** Do not taste or swallow. May be fatal if swallowed. Potential for aspiration if swallowed.

**Component Information** 

| Chemical name                     | LD50/Oral            | LD50/Dermal              | Inhalation LC50                                |
|-----------------------------------|----------------------|--------------------------|--|
| Mineral Spirits<br>64742-88-7     | > 5000 mg/kg (Rat)   | = 3000 mg/kg ( Rabbit )  | > 5.28 mg/L (Rat)4 h                           |
| 1,2,4-trimethylbenzene<br>95-63-6 | = 3400 mg/kg (Rat)   | > 3160 mg/kg ( Rabbit )  | = 18 g/m³ (Rat) 4 h                            |
| Xylene<br>1330-20-7               | = 4300 mg/kg ( Rat ) | > 1700 mg/kg ( Rabbit )  | = 5000 ppm (Rat) 4 h = 47635<br>mg/L (Rat) 4 h |
| Cumene<br>98-82-8                 | = 1400 mg/kg (Rat)   | > 3160 mg/kg ( Rabbit )  | = 39000 mg/m³ ( Rat ) 4 h                      |
| Ethylbenzene<br>100-41-4          | = 3500 mg/kg (Rat)   | = 15354 mg/kg ( Rabbit ) | = 17.2 mg/L (Rat) 4 h                          |

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Causes serious eye irritation. Causes skin irritation. May be fatal if swallowed and enters

airways.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** No information available. **Germ cell mutagenicity** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical name            | ACGIH | IARC     | NTP | OSHA |
|--------------------------|-------|----------|-----|------|
| Xylene<br>1330-20-7      | -     | Group 3  | -   | -    |
| Cumene<br>98-82-8        | -     | Group 2B | -   | X    |
| Ethylbenzene<br>100-41-4 | A3    | Group 2B | -   | X    |

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

**Chronic toxicity** May cause adverse effects on the bone marrow and blood-forming system.

Target organ effects central nervous system, Eyes, Respiratory system, Skin, blood.

**Aspiration hazard** May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 3912 mg/kg
ATEmix (dermal) 2701 mg/kg mg/l
ATEmix (inhalation-dust/mist) 18.9 mg/l

## 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

| Chemical name                     | Algae/aquatic plants        | Fish  | Toxicity to    | Crustacea                  |
|-----------------------------------|-----------------------------|---|----------------|----------------------------|
|                                   |                             |   | microorganisms | 100 101 5                  |
| Mineral Spirits                   | 450: 96 h                   | 800: 96 h Pimephales                                    | -              | 100: 48 h Daphnia magna    |
| 64742-88-7                        | Pseudokirchneriella         | promelas mg/L LC50 static                               |                | mg/L EC50                  |
| 4.0.4 trips of built a reason     | subcapitata mg/L EC50       | 7.40 0.00 00 h Dimonhalaa                               |                | C.44: 40 h Danhais mana    |
| 1,2,4-trimethylbenzene<br>95-63-6 | -                           | 7.19 - 8.28: 96 h Pimephales                            | -              | 6.14: 48 h Daphnia magna   |
| 95-63-6                           |                             | promelas mg/L LC50<br>flow-through                      |                | mg/L EC50                  |
| Vulono                            |                             | 13.4: 96 h Pimephales                                   | _              | 3.82: 48 h water flea mg/L |
| Xylene<br>1330-20-7               | -                           | promelas mg/L LC50                                      | -              | EC50 0.6: 48 h Gammarus    |
| 1330-20-7                         |                             | flow-through 2.661 - 4.093:                             |                | lacustris mg/L LC50        |
|                                   |                             | 96 h Oncorhynchus mykiss                                |                | lacustris mg/L LC30        |
|                                   |                             | mg/L LC50 static 13.5 - 17.3:                           |                |                            |
|                                   |                             | 96 h Oncorhynchus mykiss                                |                |                            |
|                                   |                             | mg/L LC50 13.1 - 16.5: 96 h                             |                |                            |
|                                   |                             | Lepomis macrochirus mg/L                                |                |                            |
|                                   |                             | LC50 flow-through 19: 96 h                              |                |                            |
|                                   |                             | Lepomis macrochirus mg/L                                |                |                            |
|                                   |                             | LC50 7.711 - 9.591: 96 h                                |                |                            |
|                                   |                             | Lepomis macrochirus mg/L                                |                |                            |
|                                   |                             | LC50 static 23.53 - 29.97: 96                           |                |                            |
|                                   |                             | h Pimephales promelas                                   |                |                            |
|                                   |                             | mg/L LC50 static 780: 96 h                              |                |                            |
|                                   |                             | Cyprinus carpio mg/L LC50                               |                |                            |
|                                   |                             | semi-static 780: 96 h                                   |                |                            |
|                                   |                             | Cyprinus carpio mg/L LC50                               |                |                            |
|                                   |                             | 30.26 - 40.75: 96 h Poecilia                            |                |                            |
| _                                 |                             | reticulata mg/L LC50 static                             |                |                            |
| Cumene                            |                             | 6.04 - 6.61: 96 h Pimephales                            | <del>-</del>   | 0.6: 48 h Daphnia magna    |
| 98-82-8                           | Pseudokirchneriella         | promelas mg/L LC50                                      |                | mg/L EC50 7.9 - 14.1: 48 h |
|                                   | subcapitata mg/L EC50       | flow-through 4.8: 96 h                                  |                | Daphnia magna mg/L EC50    |
|                                   |                             | Oncorhynchus mykiss mg/L                                |                | Static                     |
|                                   |                             | LC50 flow-through 2.7: 96 h<br>Oncorhynchus mykiss mg/L |                |                            |
|                                   |                             | LC50 semi-static 5.1: 96 h                              |                |                            |
|                                   |                             | Poecilia reticulata mg/L                                |                |                            |
|                                   |                             | LC50 semi-static  |                |                            |
| Ethylbenzene                      | 4.6: 72 h                   | 11.0 - 18.0: 96 h                                       | -              | 1.8 - 2.4: 48 h Daphnia    |
| 100-41-4                          | Pseudokirchneriella         | Oncorhynchus mykiss mg/L                                |                | magna mg/L EC50            |
|                                   | subcapitata mg/L EC50 438:  | LC50 static 4.2: 96 h                                   |                |                            |
|                                   | 96 h Pseudokirchneriella    | Oncorhynchus mykiss mg/L                                |                |                            |
|                                   | subcapitata mg/L EC50 2.6 - | LC50 semi-static 7.55 - 11:                             |                |                            |
|                                   | 11.3: 72 h                  | 96 h Pimephales promelas                                |                |                            |
|                                   | Pseudokirchneriella         | mg/L LC50 flow-through 32:                              |                |                            |
|                                   | subcapitata mg/L EC50       | 96 h Lepomis macrochirus                                |                |                            |
|                                   | static 1.7 - 7.6: 96 h      | mg/L LC50 static 9.1 - 15.6:                            |                |                            |
|                                   | Pseudokirchneriella         | 96 h Pimephales promelas                                |                |                            |
|                                   | subcapitata mg/L EC50       | mg/L LC50 static 9.6: 96 h                              |                |                            |
|                                   | static                      | Poecilia reticulata mg/L                                |                |                            |
|                                   |                             | LC50 static   |                |                            |

## Persistence and degradability

# 40390 Sure Klean® Weather Seal Blok-Guard® & Graffiti Control 15

No information available.

#### **Bioaccumulation**

No information available.

| Chemical name          | Partition coefficient |
|------------------------|-----------------------|
| 1,2,4-trimethylbenzene | 3.63                  |
| 95-63-6                |                       |
| Xylene                 | 3.15                  |
| 1330-20-7              |                       |
| Cumene                 | 3.55                  |
| 98-82-8                |                       |
| Ethylbenzene           | 3.118                 |
| 100-41-4               |                       |

Other adverse effects No information available

## 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

#### 14. TRANSPORT INFORMATION

**DOT**Not regulated (If shipped in NON BULK packaging by ground transport)

UN number UN1866 UN proper shipping name Resin Solution

Transport hazard class(es) 3
Packing group III

<u>IATA</u>

UN number UN1866 UN proper shipping name Resin Solution

Transport hazard class(es) 3
Packing group III

**IMDG** 

UN number UN1866 UN proper shipping name Resin Solution

Transport hazard class(es) 3
Packing group

## 15. REGULATORY INFORMATION

**International Inventories** 

# 40390 Sure Klean® Weather Seal Blok-Guard® & Graffiti Control 15

TSCA Complies DSL/NDSL Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

#### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical name                    | CAS No.   | Weight-% | SARA 313 - Threshold<br>Values % |
|----------------------------------|-----------|----------|----------------------------------|
| 1,2,4-trimethylbenzene - 95-63-6 | 95-63-6   | 3 - 7    | 1.0                              |
| Xylene - 1330-20-7               | 1330-20-7 | 1 - 5    | 1.0                              |
| Ethylbenzene - 100-41-4          | 100-41-4  | 0.1 - 1  | 0.1                              |

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

#### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical name            | CWA - Reportable<br>Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous<br>Substances |
|--------------------------|--------------------------------|------------------------|---------------------------|-------------------------------|
| Xylene<br>1330-20-7      | 100 lb                         | -                      | -                         | Х                             |
| Ethylbenzene<br>100-41-4 | 1000 lb                        | X                      | Х                         | X                             |

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|---------------|--------------------------|----------------|--------------------------|
| Xylene        | 100 lb                   | -              | RQ 100 lb final RQ       |
| 1330-20-7     |                          |                | RQ 45.4 kg final RQ      |
| Cumene        | 5000 lb                  | -              | RQ 5000 lb final RQ      |
| 98-82-8       |                          |                | RQ 2270 kg final RQ      |
| Ethylbenzene  | 1000 lb                  | <del>-</del>   | RQ 1000 lb final RQ      |
| 100-41-4      |                          |                | RQ 454 kg final RQ       |

#### **US State Regulations**

#### **California Proposition 65**

#### **U.S. State Right-to-Know Regulations**

| Chemical name          | New Jersey | Massachusetts | Pennsylvania |
|------------------------|------------|---------------|--------------|
| Mineral Spirits        | X          | -             | -            |
| 64742-88-7             |            |               |              |
| 1,2,4-trimethylbenzene | X          | X             | X            |
| 95-63-6                |            |               |              |
| Xylene                 | X          | X             | X            |
| 1330-20-7              |            |               |              |
| Cumene                 | X          | X             | X            |
| 98-82-8                |            |               |              |
| Ethylbenzene           | X          | X             | X            |

100-41-4

#### **16. OTHER INFORMATION**

NFPA Health hazards 2 Flammability 2 Instability 0 Physical and chemical

properties -

Health hazards 2 Flammability 2 Physical hazards 0 Personal protection X

Prepared By Regulatory Department

Issuing Date 12-Nov-2014
Revision date 10-Aug-2018
Revision Note

SDS sections updated

467815

#### Disclaimer

The information contained on the Safety Data Sheet has been compiled from data considered accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. PROSOCO, Inc. expressly disclaims any warranty express or implied as well as any liability for any injury or loss arising from the use of this information or the materials described. This data is not to be construed as absolutely complete since additional data may be desirable when particular conditions or circumstances exist. It is the responsibility of the user to determine the best precautions necessary for the safe handling and use of this product for his unique application. This data relates only to the specific material designated and is not to be used in combination with any other material. Many federal and state regulations pertain directly or indirectly to the product's end use and disposal of containers and unused material. It is the purchaser's responsibility to familiarize himself with all applicable regulations.

**End of Safety Data Sheet**