



P.O. Box 640
1800 Springhead Ch. Rd.
Willacoochee, Ga. 31650

912-534-6071
800-948-7870
912-534-6254(fax)

Subject: LM 400 - 4oz/sy (Typical) Non Woven Geotextile

This letter certifies that our LM 400, Non-woven filter fabric, meets the requirements for non-woven geotextile fabric. The average laboratory test values are as follows:

PROPERTY	TEST METHOD	UNIT	ROLL VALUE
Tensile Strength	ASTM D 4632	Lbs	100
Elongation	ASTM D 4632	%	50
Trapezoidal Tear	ASTM D 4533	Lbs	43
CBR Puncture Strength	ASTM D 6241	Lbs	300
AOS	ASTM D 4751	Sieve	70
Permittivity	ASTM D 4491	Sec-1	2.0
Water Flow Rate	ASTM D 4491	Gpm/ft	120
UV Resistance	ASTM D 4355	%/hours	70/500

Unless otherwise noted, this certification is based on testing conducted by our Quality Assurance & Quality Control testing laboratories at the time of manufacturing. L & M Supply Co., Inc. issued this letter of certification to indicate our commitment to providing our customers with a quality product which will meet or exceed the Typical Average Roll Values in accordance with the applicable American Society for Testing and Materials (ASTM) test method.

Respectfully,

Quentin McMillan