



safewaze.com | (P) 704-262-7893 | (F) 704-262-9051
 322 Industrial Court, Concord, NC 28025

TECHNICAL DATA SHEET

018-5010

7' Web Retractable w/
 Steel Locking Rebar Hook



Features and Benefits	Safewaze™ retractable lifelines are designed to be used as a single-person fall protection device. The 018-5010 features a unique clear plastic housing for enhanced unit inspection and a revolutionary internal braking system, which alleviates the need for an external shock pack in such a small, ergonomic SRL . Fall indicator is sewn into webbing.
Length of Web	7 ft (2.13 m)
Weight of Unit	3.8 lbs (1.72 kg)
Materials	High-strength clear plastic housing .77 in (19.5 mm) Ultrahigh Molecular Weight Webbing Forged steel rebar hook Steel triple-lock carabiner included
Hook Ratings	5,000 lbs (2267.96 kg) Tensile Strength 3,600 lbs (1632 kg) Gate Rated
Maximum Arresting Force	<1,800 lbs (816.47 kg)
Maximum Arrest Distance	Class A up to 24 in (60.96 cm) if used above Dorsal D-ring Class B up to 54 in (137.16 cm) if used up to a maximum of 2 ft below Dorsal D-ring
Maximum Working Load	ANSI 130-310 lbs (58.97-140.61 kg) OSHA up to 420 lbs (190.51 kg)
Webbing Tensile Strength	4,200 lbs (1905.09 kg)
Applicable Standards	Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32