## TECHNICAL DATA SHEET



<u>safewaze.com</u> | (P) 704-262-7893 | (F) 704-262-9051 322 Industrial Court, Concord, NC 28025

## **FS-FSP14095-W-RBH**

11' **CLASS A** Dual-Leg Web Retractable w/ Steel Rebar Hooks



Features and Benefits Safewaze™ retractable lifelines are designed to be used as a

single-person fall protection device. The FS-FSP14095-W-RBH features a mobility-enhancing swivel-top, a rugged and durable housing, and a unique braking system that eases shock in the event of a fall. Fall

indicator sewn into webbing.

**Length of Web** 11 ft (3.35 m)

Weight of Unit 10.20 lbs (4.63 kg)

Materials Aluminum housing

1 in (25.4 mm) Ultrahigh Molecular Weight webbing w/ sewn-in fall

indicator

Forged steel rebar hooks

Steel carabiner

Hook Ratings 5,000 lbs (2267.96 kg) Tensile Strength

3,600 lbs (1632 kg) Gate Rated

**Arresting Force** Max Force <1,800 lbs (816.47 kg); Avg Force <1,350 lbs (612.35 kg)

Maximum Arrest Distance <24 in (609.6 mm)

Maximum Working Load 310 lbs (140.61 kg)

Webbing Tensile Strength 4,200 lbs (1905.09 kg)

Applicable Standards Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32