TECHNICAL DATA SHEET



<u>safewaze.com</u> | (P) 704-262-7893 | (F) 704-262-9051 322 Industrial Court, Concord, NC 28025

FS-FSP15075-W-BWB

7' **CLASS A** Dual-Leg Web Retractable w/ In-Webbing Bracket and Snap Hooks



Features and Benefits Safewaze™ retractable lifelines are designed to be used as a single-

person fall protection device. The FS-FSP15075-W-BWB features a mobility-enhancing swivel-top, a rugged and durable housing, and a unique braking system that eases shock in the event of a fall.

Fall indicator sewn into webbing.

Length of Web 7 ft (2.13 m)

Weight of Unit 8.5 lbs (3.86 kg)

Materials Aluminum housing

1 in (25.4 mm) Ultrahigh Molecular Weight webbing w/ sewn-in fall

indicator

Forged steel snap hooks

Steel carabiner

Hook Ratings 5,000 lbs (2267.96 kg) Tensile Strength

3,600 lbs (1632 kg) Gate Rated

Arresting Force Max Force <1,800 lbs (816.47 kg); Avg Force <1,350 lbs (612.35 kg)

Maximum Arrest Distance <24 in (609.6 mm)

Maximum Working Load ANSI 130-310 lbs (58.97-140.61 kg)

OSHA up to 420 lbs (190.51 kg)

Webbing Tensile Strength 4,200 lbs (1905.09 kg)

Applicable Standards Meets OSHA 1926.502 - ANSI Z359.14 - ANSI A10.32