



## SW560-AF-DE-SE

### Arc Flash 6' Energy Absorbing Lanyard : Dielectric Snap Hook, Soft Loop

#### FEATURES :

- 40Cal/550F rated
- Mil-Spec flame & heat resistant nylon webbing
- 1 Snap hook
- 1 Soft loop
- Hook tensile strength : 5,000 lbs. (2268 kg)
- Hook gate rating : 3,600 lbs. (1633 kg)
- Single leg construction

#### ATTACHMENT POINT(S) :

- 1 Snap hook
- 1 Soft loop

#### ITEM LENGTH :

- 6' (1.8 m)

#### ITEM WEIGHT :

- 2.7 lbs. (1.2 kg)



#### USER WEIGHT CAPACITY

|      |                            |
|------|----------------------------|
| ANSI | 130-310 lbs. (59-140.6 kg) |
| OSHA | N/A                        |

#### STANDARD COMPLIANT WITH

|      |          |
|------|----------|
| ANSI | Z359.13  |
| OSHA | 1926.502 |
| ASTM | F887     |

#### SIZE(S)

|     |  |
|-----|--|
| N/A |  |
|     |  |
|     |  |
|     |  |
|     |  |
|     |  |
|     |  |
|     |  |

#### COMPONENT

#### MATERIAL SPECIFICATION

|             |                  |
|-------------|------------------|
| Webbing     | 1" Nylon         |
| Wear sleeve | Aramid           |
| Shock pack  | Nomex®           |
| Snap hook   | Dielectric       |
| Soft loop   | 1" Nylon; Aramid |
|             |                  |
|             |                  |
|             |                  |