

Revision Date 05/12/2014 Print Date 05/12/2014

#### 1. Identification

Product name Sikadur® Injection Gel Slow Part B

Supplier Sika Corporation

Address 201 Polito Avenue

Lyndhurst, NJ 07071

**USA** 

www.sikausa.com

Telephone (201) 933-8800

Telefax (201) 804-1076

Emergency telephone CHEMTREC: 800-424-9300

INTERNATIONAL: 703-527-3887

ehs@sika-corp.com

Recommended use of the

chemical and restrictions on

use

For further information, refer to the product technical data

sheet.

### 2. Hazards identification

#### **GHS Classification**

Skin irritation, Category 2 H315: Causes skin irritation. Serious eye damage, Category 1 H318: Causes serious eye damage. Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

Carcinogenicity, Category 1A H350: May cause cancer.

#### **GHS Label element**

Hazard pictograms







Signal Word

**Hazard Statements** : H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H350 May cause cancer.

**Precautionary Statements** : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear eye protection/ face protection.



Revision Date 05/12/2014 Print Date 05/12/2014

P280 Wear protective gloves.

P281 Use personal protective equipment as required.

#### Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/

P310 Immediately call a POISON CENTER or doctor/physician.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

#### Storage:

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Warning

: Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain,liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

See Section 11 for more detailed information on health effects and symptoms.

### 3. Composition/information on ingredients

# **Hazardous ingredients**

| Chemical Name                            | CAS-No.     | Concentration (%) |
|--|-------------|-------------------|
| Benzyl alcohol                           | 100-51-6    | >= 10 - < 20 %    |
| Trimethylhexamethylenediamine            | 25620-58-0  | >= 5 - < 10 %     |
| Cycloaliphatic polyamine                 | proprietary | >= 5 - < 10 %     |
| Isophoronediamine                        | 2855-13-2   | >= 2 - < 5 %      |
| 2,4,6-tris(dimethylaminomethyl)phenol    | 90-72-2     | >= 2 - < 5 %      |
| solvent naphtha (petroleum), heavy arom. | 64742-94-5  | >= 1 - < 2 %      |
| Quartz (SiO2)                            | 14808-60-7  | >= 0 - < 1 %      |
| Naphthalene, pure                        | 91-20-3     | >= 0 - < 1 %      |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

#### 4. First aid measures

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.



Revision Date 05/12/2014 Print Date 05/12/2014

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Induce vomiting immediately and call a physician.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

: irritant effects sensitizing effects carcinogenic effects

Allergic reactions
Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Protection of first-aiders : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in

attendance.

Notes to physician : Treat symptomatically.

# 5. Fire-fighting measures

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Specific extinguishing

methods

: Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Environmental precautions

: Use personal protective equipment. Deny access to unprotected persons.

: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

Revision Date 05/12/2014 Print Date 05/12/2014

respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

# 7. Handling and storage

Advice on safe handling : Do not breathe vapors or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is

being used.

Smoking, eating and drinking should be prohibited in the

application area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage Prevent unauthorized access.

Store in original container.

Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Store in accordance with local regulations.

Materials to avoid : no data available

#### 8. Exposure controls/personal protection

| Talc (Mg3H2(SiO3)4) | 14807-96-6 | OSHA P0  | TWA | 2 mg/m3<br>Respirable fraction                 |
|---------------------|------------|----------|-----|--|
|                     |            | ACGIH    | TWA | 0.1 fibre/cm3                                  |
|                     |            | ACGIH    | TWA | 2 mg/m3<br>Respirable fraction                 |
|                     |            | OSHA Z-3 | TWA | 20 Million particles<br>per cubic foot<br>Dust |
| Quartz (SiO2)       | 14808-60-7 | ACGIH    | TWA | 0.025 mg/m3<br>Respirable fraction             |
|                     |            | OSHA Z-3 | TWA | 30 mg/m3<br>/ %SiO2+2                          |



Revision Date 05/12/2014 Print Date 05/12/2014

|                   |         |          |      | total dust                           |
|-------------------|---------|----------|------|--------------------------------------|
|                   |         | OSHA Z-3 | TWA  | 10 mg/m3<br>/ %SiO2+2<br>respirable  |
|                   |         | OSHA Z-3 | TWA  | 250 mppcf<br>/ %SiO2+5<br>respirable |
|                   |         | OSHA P0  | TWA  | 0.1 mg/m3<br>Respirable fraction     |
| Naphthalene, pure | 91-20-3 | ACGIH    | TWA  | 10 ppm                               |
|                   |         | ACGIH    | STEL | 15 ppm                               |
|                   |         | OSHA Z-1 | TWA  | 10 ppm<br>50 mg/m3                   |
|                   |         | OSHA P0  | TWA  | 10 ppm<br>50 mg/m3                   |
|                   |         | OSHA P0  | STEL | 15 ppm<br>75 mg/m3                   |

## **Engineering measures**

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

# Personal protective equipment

Respiratory protection

: Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection Remarks

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is

necessary.

Eye protection : Safety eyewear complying with an approved standard should

# Jka ®

# Sikadur® Injection Gel Slow Part B

Revision Date 05/12/2014 Print Date 05/12/2014

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling the

product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

# 9. Physical and chemical properties

Appearance : paste Color : gray

Odor : amine-like

Odor Threshold : no data available

Flash point :  $> 212 \,^{\circ}\text{F} \, (> 100 \,^{\circ}\text{C})$ 

Ignition temperature : not applicable

Decomposition temperature : no data available

Lower explosion limit (Vol%) : no data available

Upper explosion limit (Vol%) : no data available

Flammability (solid, gas) : no data available

Oxidizing properties : no data available

Autoignition temperature : no data available

pH : no data available

Melting point/range /

Boiling point/boiling range

Freezing point

nint

Vapor pressure : no data available

Density : 1.65 g/cm3

at 68 °F (20 °C)

no data available

no data available

no data available

no data available

Water solubility : Note: slightly soluble

Partition coefficient: n-

octanol/water

Viscosity, dynamic

# Safety Data Sheet



# Sikadur® Injection Gel Slow Part B

Revision Date 05/12/2014 Print Date 05/12/2014

Viscosity, kinematic : > 20.5 mm2/s

at 104 °F (40 °C)

Relative vapor density : no data available

Evaporation rate : no data available

Burning rate : no data available

Volatile organic compounds

(VOC) content

: 13 g/l

# 10. Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous

Conditions to avoid

reactions

: Stable under recommended storage conditions.

: no data available

Incompatible materials : no data available

### 11. Toxicological information

### **Acute toxicity**

# **Product**

Acute oral toxicity : no data available

Acute inhalation toxicity : no data available

Acute dermal toxicity : no data available

**Ingredients:** 

Benzyl alcohol:

Acute oral toxicity : LD50 Oral rat: 1,230 mg/kg

Acute inhalation toxicity : LC50 rat: 4.178 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Isophoronediamine:

Acute oral toxicity : LD50 Oral rat: 1,030 mg/kg

#### Skin corrosion/irritation

### **Product**

Revision Date 05/12/2014 Print Date 05/12/2014

Result: Skin irritation

Causes skin irritation.

# Serious eye damage/eye irritation

# **Product**

Causes serious eye damage.

### Respiratory or skin sensitization

## **Product**

May cause an allergic skin reaction.

## Germ cell mutagenicity

**Product** 

Mutagenicity : no data available

Carcinogenicity

**Product** 

Carcinogenicity : May cause cancer.

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7 Group 2B: Possibly carcinogenic to humans Naphthalene, pure 91-20-3

NTP Known to be human carcinogen

Quartz (SiO2) 14808-60-7 Reasonably anticipated to be a human carcinogen

Naphthalene, pure 91-20-3

Reproductive Toxicity/Fertility

**Product** 

Reproductive toxicity : no data available

# Reproductive Toxicity/Development/Teratogenicity

**Product** 

Teratogenicity : no data available

# STOT-single exposure

**Product** 

Assessment: no data available

#### STOT-repeated exposure

Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain, liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Revision Date 05/12/2014

Print Date 05/12/2014

#### **Product**

Assessment: no data available

# **Aspiration toxicity**

# **Product**

no data available

## 12. Ecological information

Other information Do not empty into drains; dispose of this material and its

container in a safe way.

Avoid dispersal of spilled material and runoff and contact

with soil, waterways, drains and sewers.

# 13. Disposal considerations

# **Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

# 14. Transport information

DOT

Not dangerous goods

IATA

Not dangerous goods

**IMDG** 

Not dangerous goods

#### Special precautions for user

no data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

# 15. Regulatory information

Revision Date 05/12/2014 Print Date 05/12/2014

**TSCA list** : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

## **EPCRA - Emergency Planning and Community Right-to-Know**

## **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

# **SARA304 Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard

Chronic Health Hazard

SARA 302 : SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 313 : SARA 313: This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

Clean Air Act

**Ozone-Depletion** 

**Potential** 

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

California Prop 65 WARNING! This product contains a chemical known in the

State of California to cause cancer.

#### 16. Other information

#### **HMIS Classification**



**Caution:** HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the

# Safety Data Sheet

# Sa Si

# Sikadur® Injection Gel Slow Part B

Revision Date 05/12/2014

Print Date 05/12/2014

National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

#### **Notes to Reader**

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 05/12/2014

Material number: 183602